

# New developments and missing components of an optical synchronization system

Holger Schlarb DESY  
for the LbSyn team



V. Arsov, M. Bock, P. Gessler, M. Felber, K. Hacker, F. Loehl, B. Lorbeer, F. Ludwig,  
Matthiesen, B. Schmidt, A. Winter, J. Zemella  
(Deutsches Elektronen-Synchrotron)

K-H.



S. Schulz, L. Wissmann  
(Universität Hamburg)






## Present status & evaluation of optical synchronization system


- **Proof-of-principle experiments** performed for Master Laser Oscillator, Link stabilization, Laser to RF conversion and Laser to Laser locking (<1-10fs achievable)
  - **Engineering** of individual components on the way
  - Optical synchronization system is **very complex** (reliability), **cost** and **labor intensive**
  - Unclear for an accelerator and a larger system (>10 links)  
how much **diagnostics** and **redundancy** is required (remote control, software development)
  - Rigid system: time overlap with electron/photon beam,  
within cross-correlator required + dispersion compensation,  
phase shift of generated RF not simply possible
- Advantage:** unambiguousness of synchronization (bucket jump can be excluded)
- Disadvantage:** significant overhead required for implementation and commissioning  
as well as loss of flexibility
- Some solutions are not **appropriate for requirements** (cost versus benefit)

**Next steps:** simplification of system components and cost reduction

## Optical synchronization system



3



- Several operation points of accelerator  
 ⇒ e.g. BC0 is turned off it requires to **shift timings** of  
 Beam arrival monitor (schemes based on direct zero-crossing sampling)  
 Two-color optical cross-correlator for laser locking

**Missing: alternative to optical delay lines for timing shifts (open)**



- 2 end-stations in close vicinity (two links are too expensive!!!!)

**Missing: inexpensive optical link stabilization for short distances**

- RF generation at many locations (low cost version at reduced performance ~20fs)


**Missing: either an appropriate RF sub-distribution or  
 fiber link stabilization + L2RF converter**

# RF generation by direct conversion




## Pro:

- Small optical input power required ~ 5-10 mW sufficient
- Very cheap and easy to build (<1k€ for good components)
- Excess to entire frequency comb
- Gating or amplitude mod. allows to generate other freq.
- Drift stability <10fs over hours have been demonstrated (see talk Frank Ludwig)





## Cons.:

- Amplitude dependence (AM to PM conversion) 1-2 ps/mW@10mW hence  $\sigma_{dP/P} < 1e-3 \Rightarrow <10$  fs
- Temperature dependence 340fs/°C hence  $\sigma_T < 0.03$  °C  $\Rightarrow <10$  fs
- If high power amplifier is used: no control





Missing: compact direct conversion module including temperature stabilization suited for frequencies between 500 MHz – 3 GHz (PD selection, Ethernet interface, PD/BPF + Ampl. packaged,  $P_{out}=10$ dBm)


# RF based synchronization without phase det.



Beat in frequency domain by adding second pulse train





Balanced detection  $P(f_{n+1}) - P(f_n)$



## Link stabilization



6



Detection scheme has been patent by DESY


### Pro:

- Problem of photo detector is eliminated since only amplitudes are detected
- No dispersion compensation is required (as long as pulse is short enough)
- Timing overlap is not difficult (many working points, does not need to be exact!)
- Selection of filter: higher accuracy but smaller dynamic range
- Can be used to monitor the fiber length variation without correction (expensive)

### Cons:

- 1 fs is not realistic
- Loss changes at link arm would be detected as timing changes

# Short link experiment setup




Inloop and out-of-loop detector



Delay line (presently used for calibration)

Fiber (meanwhile exit room)

Sketch of experimental setup




# Short link experiment setup







# Short link experiment setup



# Layout of synchronization system at FLASH



- Implementation of entire system 06/2008 - 2010



- Short link to server more end-stations
- Synchronization of both photo injector lasers &
- Providing RF for 3th cavity (monitoring/source)
- Monitoring for 1.3GHz at Kryo hall
- Engineered version ~ spring 2010

## Other interesting developments



11

- PM fiber link to avoid polarization control (cost/reliability)
  - Problem:** no PM DCF fiber exists
  - Option:** PM link but SMF-DCF (stability)
- Optical down converter to avoid RF generation entirely
  - Problem:** 1) for amplitude detection a dynamic range of laser pulse readout of better than 80dB is required (10MHz BW), 60dB is typically achieved)  
2) cannot cope with large phase changes ( $< 1\text{deg}$ )  
3) too large costs
  - Option:** for CW machines, split A and  $\varphi$  detection
- XFEL 10MHz has been chosen
  - Problem:** 216MHz incompatible, have to switch to MLO with  $f_{\text{rep}}=200\text{MHz}$  but now  $1.3\text{GHz} \neq n f_{\text{rep}}$
  - Option:** Modification of Sagnac loop operation point  
Other interferometer style of L2RF converters
- Fiber with lower temperature coefficients
  - Problem:** index of refraction  $\sim 7\text{e-}6 / ^\circ\text{C}$  but expansion coefficient  $\sim 1\text{e-}7 / ^\circ\text{C}$



# Thanks for your attention