

## Detector Status

F.Forti, INFN and University, Pisa


# Overview

---

- ▶ The design of the detector is almost completely defined
- ▶ Updates to budget and schedule will be discussed at this meeting.
- ▶ The TDR is 80-90% complete and should be published in the next month or so.

...but...

- ▶ Need a clear and realistic schedule for the machine construction and the corresponding funding
- ▶ Eagerly waiting for ministerial review to happen in october.



# Detector Design Issues – all defined

System	Baseline	Issues (technical OR manpower; R&D)
MDI	Initial IR designed	Magnetic elements and radiation masks. Design of tungsten shields. Cryostats radius <b>Background simulations:</b> global map, detector occupancy
SVT	6-layer silicon	<b>Technology for Layer 0:</b> striplets, with pixels as upgrade path. Thin pixels R&D. Readout chip for strips. Mechanical design.
DCH	Stereo-axial He-based	Dimensions (inner radius, length) defined. Mechanical structure. Cluster counting option as upgrade
EMC	Barrel: CsI(Tl) Forw: LYSO	Electronics and trigger. Mechanical structure <b>Forward EMC technology:</b> hybrid LYSO+CsI(Tl) with Pure CsI as R&D. <b>Backward EMC:</b> cost/benefit analysis
PID	DIRC w/ FBLOCK	<b>FBLOCK design completed.</b> Photon detection defined. Mechanical structure designed <b>Forward PID:</b> cost/benefit analysis. Prove TOF technology.
IFR	Scintillator+ fibers	9 layers. <b>SiPM location defined.</b> Extra 10cm iron. Mechanical design of extra shield.
ETD	Synchronous const. latency	Fast link rad hardness. LI Trigger (jitter and rate). ROM designed. Link to computing for HLT.

# TDR process and timeline

- ▶ The Technical Design Report is an essential step to get funding and get the detector built.
- ▶ Funding and schedule
  - ▶ The TDR will contain an updated budget and a schedule for construction.
  - ▶ It will not be incorporate funding agencies intentions and commitments into the TDR:
    - ▶ → A separate financial document to detail the agencies contributions will be published later

## TDR Timeline

- ▶ June-July 2011:
  - ▶ setup SVN repository + initial outline
- ▶ September 2011
  - ▶ Detailed outline with page count + editorial responsibilities
  - ▶ Tentative institutional matrix of responsibilities and money allocation
- ▶ ~~December 2011~~ → March 2012
  - ▶ First (in)complete draft,
  - ▶ Decision about what is in and what is out
  - ▶ ~~Updated budget and schedule for construction~~
- ▶ ~~February 2012~~ → ~~June 2012~~ → September 2012
  - ▶ Complete draft into final editing
  - ▶ Final readers identified
- ▶ ~~July 2012~~ → September 2012
  - ▶ Updated budget and schedule for construction
- ▶ ~~September~~ → **October 2012: Publish**



## Contents

<b>1</b>	<b>Introduction</b>	<b>1</b>	
1.1	The Physics Motivation	1	
1.2	The SuperB Project Elements	1	
1.3	The Detector Technical Design Report	2	
<b>2</b>	<b>Accelerator Overview</b>	<b>7</b>	
<b>3</b>	<b>Detector Overview</b>	<b>9</b>	
3.1	Physics Performance	9	
3.2	Challenges on Detector Design	12	
3.3	Open Issues	14	
3.4	Detector R&D	14	
<b>4</b>	<b>Physics with SuperB</b>	<b>19</b>	
4.1	Introduction	19	
4.2	<i>B</i> and <i>D</i> decays	19	
4.2.1	Rare <i>B</i> decays	19	
4.2.2	Rare <i>D</i> decays	21	
4.2.3	CKM matrix and unitarity triangle	22	
4.2.4	<i>CP</i> violation in <i>B</i> decays	23	
4.2.5	<i>CP</i> violation in <i>D</i> decays	23	
4.2.6	Other symmetry tests	24	
4.2.7	Charm mixing	24	
4.2.8	<i>B</i> physics at the $\Upsilon(5S)$	25	
4.3	$\tau$ physics at SuperB	26	
4.3.1	Lepton flavor violation in $\tau$ decay	26	
4.3.2	<i>CP</i> violation in $\tau$ decay	27	
4.3.3	Measurement of the $\tau$ $g-2$ and EDM form factors	27	
4.4	SuperB Neutral Current Electroweak Physics Programme	28	
4.5	Exotic Spectroscopy in SuperB	29	
4.6	Direct searches	31	
4.7	Executive Summary	31	
<b>5</b>	<b>Machine Detector Interface and Backgrounds</b>	<b>37</b>	
5.1	Overview	M.Sullivan, M. Boscolo E.Paoloni, - 1 page	37
5.2	Backgrounds sources.	M.Sullivan, M.Boscolo, E.Paoloni, - 2 pages	37
5.3	Radiative Bhabha	37	
5.3.1	Simulation tools	37	
5.3.2	Losses at the beam-pipe	38	
5.3.3	Shield System	39	
5.4	Pairs Production	C.Rimbault - 2 pages	40

5.5	Touscheck background.	M.Boscolo - 2 pages	40
5.6	Beam gas background.	M.Boscolo - 2 pages	40
5.7	Synchrotron radiation background.	M.Sullivan - 2 pages	40
5.8	SVT background overview		40
5.9	DCH background overview	R.Cenci D.Lindemann - 2 pages	42
5.10	FTOF background overview	L.Burmistrov - 2 pages	42
5.11	FDIRC background overview		42
5.11.1	Shielding the FDIRC		43
5.11.2	Background rates in the FDIRC		43
5.11.3	Integrated charges and doses		43
5.12	EMC background overview.	S.Germani - 2 pages	43
5.13	IFR background overview	V.Santoro - 2 pages	45
5.14	ETD background overview	R.Cenci - 2 pages	45
5.15	SVT radiation monitor.	A.Di Ciaccio - 3 pages	45
5.16	Quick demounting.	M.Sullivan, F.Bosi, E.Paoloni - 4 pages	45
<b>6</b>	<b>Silicon Vertex Tracker</b>	<b>49</b>	
6.1	Overview	G.Rizzo - 12 pages	49
6.1.1	SVT and Layer0		49
6.1.2	SVT Requirements		51
6.1.2.1	Resolution		51
6.1.2.2	Acceptance		51
6.1.2.3	Efficiency		53
6.1.2.4	Background & Radiation Tolerance		53
6.1.2.5	Reliability		54
6.1.3	Baseline Detector Concept		54
6.1.3.1	Technology		54
6.1.3.2	Layout		54
6.1.3.3	Electronic Readout		56
6.1.3.4	Module design and Mechanical Support		58
6.1.4	Layer0 Pixel Upgrade		59
6.1.4.1	Motivations		59
6.1.4.2	Technology Options for Layer0 pixel upgrade		60
6.1.4.3	Pixel Module & Material Budget		62
6.1.5	R&D Main Activities		63
6.2	Backgrounds	R.Cenci - 4 pages	63
6.2.1	Pair production		64
6.2.2	Radiative Bhabha		64
6.2.3	Touschek		64
6.2.4	Beam Gas		64
6.2.5	Other sources		64
6.3	Detector Performance Studies	N.Neri - 6 pages	64
6.3.1	Introduction		64
6.3.2	The SVT layout		64
6.3.3	Impact of Layer0 on detector performance		65
6.3.4	Tracking performance		68
6.3.5	Impact of machine background on tracking performance		68

6.3.3	Particle Reconstruction with GEV/ice	72		
6.4	Silicon Sensors	L. Bosisio - 8 pages	72	
6.4.1	Requirements		72	
6.4.2	Sensor design and technology		73	
6.4.3	Wafer layout and quantities		76	
6.4.4	Prototyping and tests		76	
6.4.5	z-side strip connection options		76	
6.5	Fanout Circuits	L.Vitale - M.Presti 2+2 pages	77	
6.5.1	Fanouts for layer0		77	
6.5.1.1	Requirements		77	
6.5.1.2	Technology		77	
6.5.1.3	Design		77	
6.5.1.4	Prototyping and tests		77	
6.5.2	Fanouts for outer layers		77	
6.5.2.1	Requirements		77	
6.5.2.2	Material and production technique		78	
6.5.2.3	Design		78	
6.5.2.4	Tests and prototyping		78	
6.6	Electronics Readout	28 pages	79	
6.6.1	Readout chips	V.Re - 10	79	
6.6.1.1	Electronic Readout for Strip and Striplet Detectors		79	
6.6.2	Readout chips requirements		80	
6.6.3	Readout Chip Implementation		83	
6.6.4	R&D for strip readout chips		83	
6.6.5	Hybrid Design	M.Citterio - 10	85	
6.6.6	Data Transmission	M.Citterio - 10	85	
6.6.7	Power Supply	- 2	85	
6.7	Mechanical Support and Assembly	S.Bettarini/F.Bosi - 14 pages	85	
6.7.1	LR. Constraint		85	
6.7.2	Module Assembly		87	
6.7.3	Detector Assembly and Installation		88	
6.7.3.1	SVT Half Detector Assembly		88	
6.7.3.2	Mount L0 on the Be-pipe and L 1-5 on the W Shielding		88	
6.7.3.3	Installation of Complete Assembly into the SuperB Detector		89	
6.7.3.4	Quick Demounting		89	
6.7.4	Detector Placement and Survey		91	
6.7.4.1	Placement accuracy		91	
6.7.4.2	Survey with tracks		91	
6.7.5	Detector Monitoring		91	
6.7.5.1	Position Monitoring System		91	
6.7.5.2	Radiation Monitoring		91	
6.7.6	R&D Program		91	
6.7.6.1	Cables		91	
6.7.6.5	Cones and space frame		91	
6.7.6.6	Full-scale model of IR		91	
6.8	Layer0 Upgrade Options	G.Rizzo/L.Ratti - 10 pages	91	
6.8.1	Technology options		91	
6.8.1.1	Hybrid pixels		91	
6.8.1.2	Deep N-well CMOS monolithic sensors		93	
6.8.1.3	Monolithic pixels in CMOS quadruple well technology		94	
6.8.2	Overview of the R&D activity		94	
6.8.2.1	Front-end electronics for hybrid pixels in planar and 3D CMOS technology		94	
6.8.2.2	The Apsel DNW MAPS series		96	
6.8.2.3	The Apsel4well quadruple well monolithic sensor		99	
6.8.3	Radiation tolerance		101	
6.9	Services, Utilities and E.S. & H issues	- 4 pages	103	
6.9.1	Service and Utilities		103	
6.9.2	ES&H Issue		103	
<b>7</b>	<b>Drift Chamber</b>		<b>109</b>	
7.1	Overview	- Finocchiaro, Roney 10 pages	109	
7.1.1	Physics Requirements	- 3 pages	109	
7.1.2	Geometrical Constraints		109	
7.1.3	Machine Background Considerations	- Cenci 3 pages	109	
7.1.4	DCH Design Overview	- 2 pages	109	
7.1.5	Expected Performance	- 2 pages	109	
7.2	Design Optimization	- Finocchiaro, Hearty, Piccolio, Roney 9 pages	110	
7.2.1	Cluster Counting		110	
7.2.2	Cell Design and Layer Arrangement		110	
7.2.3	Gas Mixture		112	
7.2.4	R&D and Prototype Studies		113	
7.2.4.1	Prototype 1		113	
7.2.4.2	Prototype 2		113	
7.2.4.3	Single Cell Prototype(s)		117	
7.2.4.4	Aging studies: fields, gas gain		117	
7.2.5	R&D Future Developments		117	
7.3	Mechanical Design		117	
7.3.1	Endplates		118	
7.3.2	Inner cylinder		118	
7.3.3	Outer Cylinder		118	
7.3.4	Choice of wire and electrostatic stability		119	
7.3.5	Feed-through design		119	
7.3.6	Endplate system		119	
7.3.6.1	Supports for on-detector boards		119	
7.3.6.2	Cooling		119	
7.3.6.3	Shielding		119	

7.4.2	Standard Readout - charge measurements specifications . . . . .	119	8.3.2	MC Simulation . . . . .	133
7.4.2.1	Resolution . . . . .	119	8.3.3	Effect of Background on performance <i>Roberts</i> . . . . .	134
7.4.2.2	Dynamic range . . . . .	119	8.4	The Barrel FDIRC Detector Overview . . . . .	134
7.4.2.3	Linearity . . . . .	119	8.4.1	Impact on other systems <i>Benettoni, Simi, Vavra</i> . . . . .	134
7.4.3	Standard Readout - time measurements specifications . . . . .	119	8.4.2	Photodetectors . . . . .	134
7.4.3.1	Resolution . . . . .	120	8.4.3	Laser calibration system . . . . .	143
7.4.3.2	Dynamic Range . . . . .	120	8.4.4	FDIRC Mechanical Design . . . . .	145
7.4.3.3	Linearity . . . . .	120	8.4.5	Electronics readout, High and Low voltage . . . . .	155
7.4.4	Standard Readout - DCH Front-end system (block diagram) . . . . .	120	8.4.6	Integration issues . . . . .	160
7.4.5	Standard Readout - ON-DETECTOR electronics . . . . .	120	8.4.7	FDIRC R&D Results until now . . . . .	161
7.4.5.1	Very Front End Boards . . . . .	120	8.4.8	Ongoing FDIRC R&D . . . . .	164
7.4.6	Sampled Waveforms - specifications . . . . .	121	8.4.9	System Responsibilities and Management . . . . .	165
7.4.6.1	Resolution . . . . .	122	8.4.10	Cost, Schedule and Funding Profile . . . . .	165
7.4.6.2	Dynamic range . . . . .	122	8.5	A possible PID detector on the Super $B$ forward side . . . . .	165
7.4.6.3	Linearity . . . . .	122	8.5.1	Physics motivation and detector requirements . . . . .	165
7.4.7	Sampled Waveforms - DCH front-end system (block diagram) . . . . .	122	8.5.2	Forward PID R&D activities . . . . .	169
7.4.8	Sampled Waveforms - ON DETECTOR electronics . . . . .	122	8.5.3	The Forward task force . . . . .	173
7.4.8.1	Very Front End Boards . . . . .	122	8.5.4	The DIRC-like forward time-of-flight detector (FTOF) . . . . .	175
7.5	High Voltage system - <i>Martin</i> 1 page . . . . .	122	9	<b>Electromagnetic Calorimeter</b> . . . . .	185
7.5.1	HV distribution boards - Standard ReadOut . . . . .	122	9.1	Overview . . . . .	185
7.5.2	HV distribution boards - Sampled Waveforms . . . . .	122	9.1.1	Background and radiation issues . . . . .	185
7.6	Gas system - <i>Roney</i> 2 pages . . . . .	123	9.1.2	Simulation tools . . . . .	187
7.7	Calibration and monitoring - <i>Roney</i> 3 pages . . . . .	123	9.1.2.1	Fastsim . . . . .	187
7.7.0.1	Slow control systems . . . . .	123	9.1.2.2	FullSim . . . . .	188
7.7.0.2	Calibration . . . . .	123	9.2	Barrel Calorimeter . . . . .	188
7.7.0.3	Gas monitoring system . . . . .	123	9.2.1	Requirements Relevant to the Super $B$ Environment . . . . .	189
7.7.0.4	On-line monitor . . . . .	123	9.2.1.1	Crystal Aging at <i>BABAR</i> . . . . .	189
7.8	Integration - <i>Hearty, Lauciani</i> 6 pages . . . . .	123	9.2.1.2	Backgrounds . . . . .	190
7.8.1	Overall geometry and mechanical support . . . . .	123	9.2.2	Description of <i>BABAR</i> Barrel Calorimeter . . . . .	190
7.8.2	Cable supports and routing . . . . .	123	9.2.2.1	Mechanical design . . . . .	190
7.8.3	Access . . . . .	123	9.2.2.2	Readout . . . . .	192
7.8.4	Gas system . . . . .	123	9.2.2.3	Low-energy Source Calibration . . . . .	193
7.8.5	Off-detector electronics crates . . . . .	123	9.2.2.4	Light Pulser . . . . .	194
7.8.6	High voltage crates . . . . .	123	9.2.3	Performance of <i>BABAR</i> barrel . . . . .	196
7.8.7	Installation and alignment . . . . .	123	9.2.3.1	Energy and position resolution . . . . .	196
8	<b>Particle Identification</b> . . . . .	127	9.2.3.2	Gamma-gamma mass resolution . . . . .	196
8.1	Summary of Physics Requirements and Detector Performance goals . . . . .	127	9.2.3.3	Radiation Damage Effects on Resolution . . . . .	198
8.1.1	Physics requirements . . . . .	127	9.2.3.4	Expected Changes in Performance at Super $B$ . . . . .	198
8.1.2	Detector concept . . . . .	127	9.2.4	Electronics changes . . . . .	199
8.1.3	Charged Particle Identification . . . . .	129	9.2.4.1	Rationale for changes . . . . .	199
8.2	Particle Identification Overview . . . . .	129	9.2.4.2	Electronics design . . . . .	200
8.2.1	Experience of <i>BABAR</i> DIRC . . . . .	129	9.2.5	SLAC De-installation, Transport and Local Storage . . . . .	200
8.2.2	Barrel PID: Focusing DIRC /FDIRC/ . . . . .	129	9.2.6	Electronics refurbishment . . . . .	200
		129	9.2.7	Re-installation at Tor Vergata . . . . .	200



9.3.1.2	Optical and Simulation Topologies	201
9.3.1.3	Radiation Hardness	207
9.3.1.4	Specifications, Production and Testing	209
9.3.2	Readout and Electronics	209
9.3.2.1	APD Readout	209
9.3.2.2	Electronics Block diagram	210
9.3.2.3	Preamplifier	210
9.3.2.4	Shaper	210
9.3.2.5	Digitization	210
9.3.2.6	Requirements on mechanics	210
9.3.3	Calibrations	210
9.3.3.1	Initial LYSO calibration with source	210
9.3.3.2	Electronics calibration	211
9.3.3.3	Temperature monitoring and correction	211
9.3.4	Mechanical Structure	211
9.3.4.1	Crystals	211
9.3.4.2	Modules	213
9.3.4.3	Installation	213
9.3.4.4	Refurbishment of the BaBar structure	213
9.3.4.5	Spare FWD modules survey and tests	214
9.3.5	Tests on Beam	214
9.3.5.1	Description of apparatus	214
9.3.5.2	Description of the beams	215
9.3.5.3	Description of data and calibration	217
9.3.5.4	Electronics noise measurements	217
9.3.5.5	Temperature corrections	218
9.3.5.6	Algorithms and results	218
9.3.5.7	Test Beam at CERN	220
9.3.6	Alternatives	221
9.3.6.1	Full LYSO calorimeter	221
9.3.6.2	Pure CsI	224
9.3.6.3	BGO	224
9.3.6.4	Comparison among options	226
9.4	Backward Calorimeter	228
9.4.1	Requirements	229
9.4.1.1	Energy and angular resolution	229
9.4.1.2	Background rates	230
9.4.1.3	Radiation hardness	230
9.4.1.4	Solid angle, transition to barrel	231
9.4.2	Mechanical design	231
9.4.2.1	Calorimeter construction	232
9.4.2.2	Support and services	232
9.4.3	SiPM/MPPC readout	233
9.4.4	Electronics	234
9.4.6	Backward simulation	234
9.4.7	Performance in simulations	235
9.4.8	Impact on physics results	235
9.4.9	Use for particle identification	238
9.4.10	Discussion of task force conclusions	240
9.5	Trigger	240
9.5.1	Calorimeter readout trigger	240
9.5.1.1	Normal mode	240
9.5.1.2	Calibration mode	240
9.5.2	Calorimeter trigger primitives	240
9.6	Detector protection	240
9.6.1	Thermal shock	240
9.6.2	Mechanical shock, including earthquakes	240
9.6.3	Fluid spills	240
9.6.4	Electrical surges, outages	240
9.6.5	Radiation damage	240
9.7	Cost & Schedule	241
9.7.1	WBS structure	241
9.7.2	Gantt chart	241
9.7.3	Basis of estimates	241
9.7.4	Cost and schedule risks	241
	<b>10 Instrumented Flux Return</b>	<b>249</b>
10.1	Physics Requirements and Performance Goals	249
10.2	Detector Overview	249
10.2.1	The Absorber Structure	249
10.2.2	The Active Detector Choice	251
10.3	Backgrounds	251
10.3.1	Main background sources	251
10.3.1.1	Neutron Background	251
10.3.1.2	Charged Particles	252
10.3.1.3	Photon background	253
10.3.2	Background remediation	253
10.3.3	Radiation doses on the IFR detector	254
10.4	Identification Performances	254
10.4.1	Muon Detection	254
10.4.2	$K_L$ Detection	256
10.5	Detector R&D	256
10.5.1	Module Tests and Results	257
10.5.1.1	Scintillators	257
10.5.1.2	Fibers	257
10.5.1.3	Photodetectors	258
10.5.1.4	Other related studies	259
10.5.1.5	New R&D studies...	259
10.5.1.6	Detector R&D Summary	270

10.5.3 Design and construction of the IFR prototype . . . . .	260	12.7.2 Other Components . . . . .	297	
10.5.3.1 Beam Tests . . . . .	261	12.7.3 Software Infrastructure . . . . .	298	
10.5.3.2 Tests Results . . . . .	261	12.8 R&D for Electronics, Trigger and Data Acquisition and Online . . . . .	298	
10.6 Baseline Detector Design . . . . .	263	12.9 Organizational Structure of Electronics, Trigger, Data Acquisition and Online . . . . .	298	
10.6.1 System Layout . . . . .	263	12.10 Conclusions . . . . .	299	
10.6.2 Chamber Construction and Assembly . . . . .	264			
10.7 Front-End Electronics . . . . .	264	<b>13 Subdetector Electronics and Infrastructure</b> . . . . .	<b>303</b>	
10.7.1 Introduction . . . . .	264	13.1 Subsystem-specific Electronics . . . . .	303	
10.7.2 Photodetectors and PCBs . . . . .	264	13.1.1 SVT Electronics . . . . .	303	
10.7.2.1 Photodetector PCB and optical coupling to fibers . . . . .	264	13.1.2 DCH Electronics . . . . .	305	
10.7.2.2 Optical coupling to fibers . . . . .	265	13.1.2.1 Design Goals . . . . .	305	
10.7.2.3 Photodetector location . . . . .	265	13.1.2.2 DCH Front-end system (block diagram) . . . . .	305	
10.7.2.4 Photodetector choice . . . . .	266	13.1.2.3 Standard Readout - OFF DETECTOR electronics . . . . .	305	
10.7.2.5 Aging and background issues . . . . .	267	13.1.2.4 Sampled Waveforms - OFF DETECTOR electronics . . . . .	307	
10.7.2.6 Temperature requirements . . . . .	267	13.1.2.5 Front End Crates . . . . .	307	
10.7.3 IFR readout electronics: an overview . . . . .	268	13.1.2.6 Number of crates and links . . . . .	308	
10.8 Final assembly and installation . . . . .	268	13.1.2.7 ECS . . . . .	308	
10.9 ES&H issues . . . . .	268	13.1.2.8 Cabling . . . . .	308	
10.10 Structure of the IFR group . . . . .	268	13.1.2.9 Power Requirements . . . . .	308	
10.11 Cost and schedule . . . . .	268	13.1.3 PID Electronics . . . . .	309	
<b>11 Magnet and Flux Return</b> . . . . .	<b>273</b>	13.1.3.1 The TDC chip . . . . .	310	
<b>12 Electronics, Trigger, Data Acquisition and Online</b> . . . . .	<b>275</b>	13.1.3.2 The Front-end Crate . . . . .	311	
12.1 Open Issues for Pisa Meeting . . . . .	275	13.1.3.3 The Communication Backplane . . . . .	311	
12.2 Architecture Overview . . . . .	275	13.1.3.4 The PMT Backplane . . . . .	311	
12.2.1 Trigger Strategy . . . . .	276	13.1.3.5 Cooling and power supply . . . . .	311	
12.2.2 Trigger Rate and Event Size Estimation . . . . .	276	13.1.3.6 The front-end board . . . . .	312	
12.2.3 Dead Time and Buffer Queue Depth Considerations . . . . .	278	13.1.3.7 The crate controller board (FBC) . . . . .	312	
12.3 Electronics in the SuperB Radiation Environment . . . . .	278	13.1.4 EMC Electronics . . . . .	312	
12.4 Trigger and Event Data Chain . . . . .	279	13.1.5 IFR Electronics . . . . .	314	
12.4.1 Choice of Global Clock Frequency . . . . .	279	13.2 Electronics Infrastructure . . . . .	317	
12.4.2 Level-1 Trigger . . . . .	279	13.2.1 Power supplies, grounding and cabling . . . . .	317	
12.4.3 Fast Control and Timing System . . . . .	283	13.2.1.1 Power Supply to the Front-end: . . . . .	317	
12.4.4 Control and Data Links . . . . .	287	13.2.1.2 High Voltage Power Supply to the Detectors: . . . . .	321	
12.4.5 Common Front-End Electronics . . . . .	291	13.2.2 Grounding and Shielding . . . . .	321	
12.4.6 Read-Out Modules . . . . .	292	13.2.3 Cable Plant . . . . .	321	
12.4.7 Network Event Builder . . . . .	293			
12.4.8 High-Level Trigger Farm . . . . .	294			
12.4.9 Data Logging . . . . .	294			
12.5 System Integration and Error Handling . . . . .	295			
12.6 Control Systems . . . . .	295			
12.6.1 Electronics Control System . . . . .	296			
12.6.2 Detector Control System . . . . .	297			
12.6.3 Farm Control System . . . . .	297			
12.7 Other Systems . . . . .	297			
		<b>14 Software and Computing</b> . . . . .	<b>325</b>	
		14.1 Computing Overview . . . . .	F.Bianchi 2 pages . . . . .	325
		14.2 Tools to support detector studies . . . . .	F.Bianchi 1 pages . . . . .	325
		14.2.1 Full Simulation . . . . .	A. Di Simone - E. Paoloni - A. Perez 4 pages . . . . .	325
		14.2.1.1 Bruno: the SuperB full simulation software . . . . .	325	
		14.2.1.2 Geometry description . . . . .	325	
		14.2.1.3 Simulation input: Event generators . . . . .	326	
		14.2.1.4 Simulation output: Hits and MonteCarlo Truth . . . . .	326	
		14.2.1.5 Simulation optimization . . . . .	326	
		14.2.1.6 Staged simulation . . . . .	327	
		14.2.1.7 Interplay with fast simulation . . . . .	327	

14.2.2.2	Detector description	329
14.2.2.3	Interaction of particles with matter	329
14.2.2.4	Detector response	330
14.2.2.5	Reconstruction	330
14.2.2.6	Machine backgrounds	331
14.2.2.7	Analysis tools	332
14.2.2.8	Simulation validation and detector studies	332
14.2.3	Distributed computing tools G. Donvito - A. Fella - E. Luppi - S. Pardi L. Tomassetti 10 pages	332
14.2.3.1	Distributed resources	333
14.2.3.2	Distributed systems design: a bird's-eye view	334
14.2.3.3	The production system	334
14.2.3.4	The data analysis system prototype	336
14.2.3.5	The bookkeeping and data placement database	337
14.2.4	Collaborative tools M. Corvo - A. Gianoli - S. Longo - R. Stroili 2 pages	338
14.2.4.1	Overview	338
14.2.4.2	Authorization	338
14.2.4.3	Portal System	338
14.2.4.4	Document repository	339
14.2.4.5	Documentation	339
14.2.4.6	Code repository	340
14.2.4.7	Code packaging and distribution	341
14.3	Computing model outline F. Bianchi - A. Fella - C. Grandi - S. Luitz - E. Luppi - S. Pardi - L. Tomassetti 6 pages	341
14.3.1	Data processing	341
14.3.2	Resource estimate F.Bianchi - S. Luitz 4 pages	342
14.3.3	Computing Infrastructure F.Bianchi - S. Luitz - S. Pardi 4 pages	342
14.4	R & D program M. Corvo - G. Donvito - A. Fella - F. Giacomini - S. Longo - S. Pardi 8 pages	344
14.4.1	R & D on parallelization	344
14.4.2	GPU R & D	344
14.4.3	Framework R & D	345
14.4.4	DIRAC framework evaluation	348
14.4.4.1	Pilot jobs model	348
14.4.4.2	Dirac data management	349
14.4.4.3	DIRAC API	349
14.4.4.4	User Management	349
14.4.4.5	Tested Use Cases	349
14.4.4.6	SuperBDIRAC module	350
14.4.4.7	Building up a DIRAC Infrastructure for SuperB	350
14.4.4.8	Future Works	350
14.4.5	Data management and distributed storage R&D	350
14.4.5.1	Wan data access	351
14.4.5.4	Dynamic file catalogue technology	351
14.4.5.5	Storage system evaluation	351
4.6	Reconstruction Framework F. Bianchi 4 pages	351
4.7	Analysis Framework F. Bianchi 4 pages	351
	Summary F.Bianchi 1 pages	351
	<b>5. Mechanical Integration and Assembly</b>	351
	Introduction	351
	5.1 Magnet and Instrumented Flux Return	351
	5.1.1 Component Extraction	351
	5.1.2 Component Transport	351
	5.1.3 Sector Assembly	351
	<b>6. SuperB Collaboration and Project Management</b>	351
	6.1 Collaboration Membership	351
	6.2 SuperB Collaboration Council	351
	6.3 SuperB Spokesperson	351
	6.4 SuperB Executive Board	351
	6.5 SuperB Management Team and Management Plan	351
	6.6 International Finance Review Committee	351
	6.7 Interaction with the Cabibbo-Lab	351
	6.8 Communications	351
	6.9 Instruction Responsibilities	351
	<b>7. Schedule</b>	351
	7.1 Sector Costs	351
	7.2 Basis of Estimate	351
	7.3 Timeline	351



**MDI**





Eugenio Paoloni (+Alejandro Perez)

- **Several improvements to the detector model where implemented for Summer-2012 production (Geometry\_CABIBBO-V03)**
  - **Final focus:** more realistic W-shield compatible with space available and integration constrains. Conical shape of 3cm thick and cylindrical shape 4.5cm thick with increased external radius.
  - **SVT:** newest L0 model (F. Bosi). L1-5 model adapted to the SuperB angular coverage ( $\pm 300$  mrad)
  - **DCH:** Internal radius increased to make room for W-shield (265 → 265 mm); new foils of copper and Aluminium according to latest machanical drawings
  - **EMC:** Hybrid CsI-LYSO fwd-end-cap model and RadFET monitors
  - **IFR:** new iron/Boron-loaded-polyethylene shields
  - **Detector Hall:** more realistic model using Fabrizio Raffaeilli drawings
  - **Solenoidal detector field:** field was extending beyond the Super-conducting magnet volume and was not zero inside the FDIRC FBLOCK.
- **NOTE:** found a problem with FDIRC geometry related with the MaPMT photocathode using BK7. The problem was fixed (changing material to Aluminium) and committed but not in time for Summer-2012 production. Summer-2012 samples are still usable applying a post-production patch. New production will be run if needed.

# The machine background model

- We are continuously our background model. The usual samples have been studied
  - Rad-Bhabha with  $\Delta E/E = \kappa > 30\%$ . This is the main Rad-bhabha component giving backgrounds on the detector.
  - Pairs, Touschek HER/LER and Beam-Gas
- In this cycle we also produced for the first time two other background sources
  - Rad-Bhabha with  $0.5 < \kappa < 30\%$ 
    - This range models the a significant fraction of the total Rad-bhabha losses at the for  $|Z| > 10m$  (first downstream dipoles)
    - These losses can contribute significantly to the neutron cloud build up process
  - Synchrotron Radiation (SR). See next slide.

- SR energy spectrum is the soft X-ray, but the rates are huge (hundreds of watts)
- The final focus W-shield should be more than adequate to absorb SR-photons passing through the thin beam-pipe
- The small fraction of the SR radiation that will be reflected and diffused by the inner surface of the pipe eventually hitting the SVT will be evaluated with Bruno






**SVT**



Giuliana Rizzo



# SVT – Update (I)



- Most of the activity focused on the TDR completion:
  - Internal revision of the text started on completed sections (~ 75%)
  - Some of the parallel sessions devoted to TDR reading.

## Other significant progress:

1. New/more reliable simulation of the hit time resolution to define time window cut for reconstruction/offline occupancy
  - Now include noise effects and sim. results are able to reproduce time resolutions achieved in BaBar data.
2. With present background simulation and new time window cut SuperB average offline cluster occupancy ~ 2% (x5 safety included) only 2-3 times higher than average BaBar occu.
  - Studies on BaBar data in high background conditions (LI cluster occup. up to 5%) used to evaluate hit-to-track efficiency in SuperB : 95% with 3% cluster occu!



Layer	View	Shaping time	Offline time window (+/- 5x NEW time resolution) ns	offline cluster occupancy (x5 included)
0	1	25	100	0.023
0	2	25	100	0.015
1	phi	75	110	0.016
1	z	75	110	0.016
2	phi	100	120	0.015
2	z	100	120	0.017
3	phi	150	150	0.030
3	z	150	150	0.015
4	phi	500	500	0.027
4	z	500	500	0.022
5	phi	750	550	0.023
5	z	750	550	0.017

# CABIBBOLAB

# SVT – Update (II)

## 3. Fastim performance comparison for striplets and pixel in Layer0 completed

- As expected pixel performance more robust in high background (pixel occup. 200 times smaller than striplets) → main motivation for pixel upgrade for full luminosity.
  - With x5 background, sensitivity to S reduced by 15% with striplets, while only 3% degradation seen with pixel with same material budget assumed.
- Thinner pixel options can further improve S sensitivity even with nominal background






# SVT – Update (III)

4. Higher neutron fluence found in SVT (bug fix) and effect on FE noise reevaluated


- S/N marginal in L4-5 with 7.5 yrs x5 safety
- A few knobs to improve the situation. Reduce:
  - Reduce ambient temperature ( $T=12^{\circ}\text{C}$ , in this table) & shaping time. Neutron shield in the hall?

## R&D on pixel:

- INMAPS MAPS with high resistivity epi layer under test:
  - Better charge collection evident with Fe55 spectrum
  - Irradiation with neutrons performed (4 steps up to  $1 \times 10^{14} \text{ n/cm}^2$ ) and chips are being tested now.
- Getting ready for Nov. testbeam at CERN



Layer	View	Shaping time	S/N at the start of data taking	S/N in 75 ab-1	S/N in 75 ab-1 x5 bkg
0	1	25	17	17	16
0	2	25	17	17	16
1	phi	75	21	20	16
1	z	75	32	27	18
2	phi	100	22	20	16
2	z	100	34	27	18
3	phi	150	27	21	14
3	z	150	34	27	16
4	phi	500	22	17	10
4	z	500	29	19	11
5	phi	750	22	14	8
5	z	750	30	18	10



INMAPS CMOS process with 4 wells & high resistivity to improve charge collection efficiency and radiation resistance

September 19, 2012



DCH




Giuseppe Finocchiaro and Mike Roney

# DCH prototype beam tests at TRIUMF

- **Goals:**


- establish benefits of cluster counting on PID
- test amplifier prototypes
- study impact on PID of design choices (sense wire, cables, connectors, gas gain)
- Five prototype amplifiers provided by JP Martin (Montreal).
- Input impedance 50, 170 or 380  $\Omega$ ; chamber impedance = 380  $\Omega$ , terminated at non-readout end.
- High impedance gives better charge collection efficiency, but stray capacitance may give low bandwidth.
- Experimentally determine best performance.
- **NEXT BEAM TEST: November 2012 with LNF team bringing PROTO-2 28 sense wire chamber to TRIUMF**



Amplifier prototype mounted on single-cell DCH



Two single-channel DCH prototypes in the M11 beam at TRIUMF




Waveforms from prototypes with 20  $\mu\text{m}$  (red) and 30  $\mu\text{m}$  (blue) sense wire. Yellow curve is TOF signal

# Initial Cluster Counting Analysis with TRIUMF test beam data


- 140MeV/c  $\mu/\pi$
- Use a likelihood ratio:  $R = L_\mu/(L_\mu + L_\pi)$  to select muons ( $L_\mu$  and  $L_\pi$  are 2D Gaussians)

No. clusters vs  
Truncated Mean  
Blue = muons,  
Red = Pions



(a) Real data.

- Combining cluster counting with truncated mean substantially improves PID
- For 1% efficiency for pion selection, muon efficiency increases from 72% for truncated mean alone to 86% by adding cluster counting information




# New design (50% higher BW) of Proto II Preamp

## Requirements

- $BW \approx 350 \text{ MHz}$
- $Gain \geq 5 \text{ mV/fC}$
- $Noise \leq 2000 \text{ e rms}$


$Z_{IN}$  adapting & decoupling circuit



$BW \approx 350 \text{ MHz}$

$Z_{IN}$ decoupling	BFP740 SiGe Transistor ( $BW > 10 \text{ GHz}$ )
Preamp	MAX3658 ( $BW \geq 350 \text{ MHz}$ )
Amplifier	CLC1606 ( $BW \geq 1 \text{ GHz} @ G = 2$ )
Buffer_Daq	CLC1606 ( $BW \geq 1 \text{ GHz} @ G = 2$ )
Buffer_Trig	THS4503 ( $BW \geq 370 \text{ MHz} @ G = 1$ )

## DCH geometry option comparison



New FastSim configurations including:

- Updated inner radius (265mm)
- Updated inner cylinder thickness (0.5mm)
- Updated wire layout (previous studies used BaBar layout)
- 5 different endcap geometries/ DCH lengths



**PID**



Nicolas Arnaud and Jerry Va'vra

# FDIRC

- ▶ Added 8 inches of lead absorber to CRT to increase the cut off muon energy to  $\sim 2$  GeV.
- ▶ The scanning setup with IRS-2 electronics is working.
- ▶ FDIRC is in CRT and ready to start taking data.
- ▶ 512 pixels instrumented with the IRS-2 electronics.
- ▶  $\sim 97\%$  of channels working.
- ▶ First short dst file produced.
- ▶ Will start tuning the analysis soon.
- ▶ MC program is close to producing pixel constants.
- ▶ Measured the refraction index of SES-403 RTV.
- ▶ PID TDR chapter finished.
- ▶ Budget estimate for barrel PID is completed.
- ▶ Analysis of the Summer 2012 background production is ongoing
- ▶ Rad Bhabha rates lower (15-20%) than in Elba as fake hits were due to the use of a wrong material to simulate the MaPMT photocathode
- ▶ TDC chip (SCATS) tests ongoing at LAL – chip sent to Bari as well

# FTOF

- ▶ **Analysis of the Summer 2012 bkg samples in progress**
- ▶ **TDR section about the forward PID almost complete – FARICH report to be added (requested late)**
- ▶ **Still missing report from the integration group about the exact space available in the forward region of SuperB for the FTOF**



**EMC**



Claudia Cecchi and Frank Porter

## EMC at this meeting


- ▶ Wednesday 16:30-18:30
  - ▶ Chih-hsiang Cheng – Fastsim updates
  - ▶ Shawn Osier – Discussion of barrel transport
  - ▶ Criso Sciacca – Barrel transport options
  - ▶ Valerio Pettinacci – Forward mechanics
- ▶ Thursday 08:30-10:30
  - ▶ Elisa Manoni – Validation of the new implementation of fastsim
  - ▶ Stefano Germani – Updates on fullsim
  - ▶ Claudia&Frank – Discussion of TDR, budget,& schedule
- ▶ Thursday 11:00-13:00
  - ▶ Paolo Gauzzi – Updates on measurements for the noise study in the barrel
  - ▶ Alessandro Rossi - CsI measurements
  - ▶ Gerald Eigen – Backward EMC

## EMC status

- ▶ TDR
  - ▶ Mostly written, but significant pieces to finish
  - ▶ Editing is underway
- ▶ Budget&Schedule
  - ▶ Have begun to re-do white paper WBS
  - ▶ Work on schedule also begun; Detailed cost and schedule draft for barrel disassembly from Shawn Osier
- ▶ Simulations – Both fastsim and fullsim have been updated
- ▶ Two spare endcap modules shipped to Roma1 for mechanical studies

## Fullsim – Fastsim comparison

Fastsim and  
fullsin resolution  
energy  
resolution in  
good agreement.




# Spare endcap module shipping



View from IP



(Note the red...)








IFR

Wander Baldini




# The GELINA irradiation test

- 9-20 July at the GELINA facility (Geel, Belgium)
- The facility: 100 MeV linac, electrons on Uranium target + moderator to obtain a neutron beam similar to superB in the low energy range ( $\leq$  keV)
- Several Hamamatsu, FBK and SenSL devices:
  - 25,50,100  $\mu\text{m}$  pixels
  - 1x1, 3x3  $\text{mm}^2$  active area
  - Radiation Hard devices from Hamamatsu (3x3  $\text{mm}^2$ )
- Measured:
  - Dark Current/Noise vs dose
  - I-V curves
  - Threshold scan
  - Dark spectra for a subset of SiPMs
- Total integrated dose:  $1.86 \times 10^{10} \text{ n/cm}^2$  (about 2 running years x safety factor 5)





# Update on background simulation and shielding

- New MC production with more shielding all around the detector:
  - 10 cm Fe + 10 cm Polyethylene-Boron in front of each encap
  - 10cm Polyethylene-Boron external to the Barrel
  - 5cm Polyethylene-Boron between solenoid and L0
- Useful exercise to understand effect of shielding even if rather difficult to implement
- Clear effects on barrel and endcaps Layer 7, Endcaps L0 still exposed to high neutron flux



# Update on R&D

- Development in Bologna of a detailed FLUKA simulation and comparison with measured data for 25 and 200 cm scintillator bars
- Some adjustments needed but the overall behaviour is well reproduced (at a 10-20% level)
- Very useful (and time-saving) to understand effects of:
  - Fibers-SiPM misalignments (both axial and transversal)
  - Position/number of fibers in the scintillator



# The IFR workshop


- Held in Krakow 7-9 Sept.
- Many interesting discussions about all the main topics related to the IFR design and construction
- Many thanks to Our IFJ-PAN, AGH, CUT colleagues for the perfect organization



Instrumentation  
for muon and  $K_L^0$   
identification  
at Super Flavor Factories

On the way to the construction  
of the hadronic calorimeter  
and muon detector (IFR)  
for SuperB spectrometer:

- research and development work on silicon photomultipliers and readout electronics;
- mechanical design of the IFR;
- detector's response simulations;
- optimization of identification of pions and muons;
- fast data acquisition system;



Organizing Committee:

W. Bedlinski (INFN Ferrara) | R. Calabrese (INFN Ferrara) | M. Chruscinska (IFJ PAN) |  
W. Kwasnica (AGH) | T. Lesniak (IFJ PAN, *co-chair*) | B. Rachwał (WEMI PK) |  
M. Stachurski (IFJ PAN) | C. Sekulsz (IFJ PAN) | P. Romaszewski (WM PK) |  
T. Szymonnek (CYFRONET) | M. Szwedek (Perfect Travel) | J. Wimbergerfeld (IFJ)



# **TDR Status and next activities**

- The writing of the TDR is ~80% complete
- All our efforts, in the next weeks, will be dedicated to the TDR finalization

## **Other short term future activities:**

- Continue the irradiation test data analysis
- Finalization of the Testbeams data analysis
- Background studies and remediation
- .....



ETD/Online



Dominique Breton, Umberto Marconi, Steffen Luitz

# ETD Progress

- ▶ Things have been very quiet since Elba
- ▶ Main focus has been on completing the TDR
  - ▶ ETD/Online chapter almost complete
    - ▶ We have solutions for remaining design “issues”, to be discussed and agreed upon during this meeting
    - ▶ Major progress in “writing”, after this meeting ready for editorial review
  - ▶ Electronics chapter
    - ▶ Missing some subdetector contributions (in the new short format)
    - ▶ Some editorial work on “infrastructure” still required
  - ▶ WBS and cost estimates
    - ▶ Have been updated, however in-depth review of the subdetector electronics still required
      - Will do during this meeting
- ▶ We have 3 sessions – will use all time to go through TDR and WBS
  - ▶ 1<sup>st</sup> session: common ETD/Online
  - ▶ 2<sup>nd</sup> and 3<sup>rd</sup> sessions: Sub-Detectors
- ▶ Note: We should seriously consider changing the global clock from 59.5 to 39.66MHz (RF/8 -> RF/12)
  - This would allow the use of a lot of technology developed for LHC (components, links, even systems)
  - Would allow for savings in cost and effort – Will discuss during this meeting – sorry proposing this
  - so late! – The few people I talked to seemed quite positive .

# Integration

F.Raffaelli, W.Wisniewski


## Topics of Meeting of Detector Integration at SLAC and problems solved

- During the meeting we review all detector interface going through the reference Babar drawing comparing it to the SuperB reference drawing.
- We compare the available space for the SuperB services.
- We check the envelope of the sub-detector measuring the reusable Babar parts.
- We discuss the EMC transportation.
- We discuss the new backward shielding modularity and the BMC integration.
- We were able to update the detector envelope

## Survey was made and inspection was made after the meeting

- Forward calorimeter service envelope
- Wire chamber supports.
- Dirch inner tube measurements.


Its envelope (added thickness) can be evaluated, approximately and conservatively, 60 mm for the inner ring and 20 mm for the external area.



*FWD Cal calibration system*

Survey was made and inspection was made after the meeting

- Wire chamber supports



6613,00

1758,54

150,00

2295,00

1771,00

367,00

1809,62

1801,00

3110,62

1431,00

1559,00


3519,00

B


B

FDIRC

A-A ( 0,03 : 1 )



# Supporting the SuperB detectors backward end



Two half removable shielding

Quadrant removable shielding


Stationary shielding


# Supporting the SuperB detectors

Backward end


Stationary shielding  
with groove for cable  
passage for the read-  
out DCH and BCAL

QUADRANT  
REMOVABLE  
SHIELDING





19/09/12



# Interaction with accelerator team

- ▶ Need to be boosted, with more regular technical contact
- ▶ Large questions need to be addressed soon
  - ▶ IR Hall: dimensions, layout, services, power, cooling, cryo, etc.
  - ▶ Envelopes in Machine-Detector Interface. Strategies for mechanical integration between detector and machine
  - ▶ Commissioning strategy: the full 1.5T field **is** needed for machine commissioning. Big impact on detector assembly and commissioning strategy → being investigated
  - ▶ Overall schedule: need to start laying down the overall integrated schedule for accelerator and detector construction



# Agenda





All Plenary Sessions will be held in Aula G (Bldg B)



SuperB Collaboration Meeting  
Pisa University and INFN  
September 19 - 22, 2012  
AGENDA

Wednesday, September 19		Thursday, September 20		Friday, September 21		Saturday, September 22	
8:30	CLOSED MEETINGS	8:30	PARALLEL 2	8:30	PARALLEL 6	8:30	CLOSED MEETINGS
250	Technical Board <i>(restricted)</i>	131 248 250 230 133	SVT DCH PID EMC IFR	131 230	ETD 2 COMP + BKGND (Fullsim)	250	Technical Board TDR Editorial Board <i>(restricted)</i>
10:30	<i>Coffee Break and Registration</i>	10:30	<i>Coffee Break</i>	10:30	<i>Coffee Break</i>	10:30	<i>Coffee Break</i>
11:00	CLOSED MEETINGS	11:00	PARALLEL 3	11:00	PARALLEL 7	11:00	CLOSED MEETINGS
250	Technical Board <i>(restricted)</i>	131 248 250 230 133	SVT DCH PID EMC IFR	131 250	ETD 3 Integration	250	Technical Board TDR Editorial Board <i>(restricted)</i>
13:00	<i>Lunch and Registration</i>	13:00	<i>Lunch</i>	13:00	<i>Lunch</i>	13:00	<i>Adjourn</i>
14:00	PLENARY 1	14:00	PARALLEL 4	14:00	PLENARY 2	14:00	
10 20 20 20 20	Introduction and Status Welcome Meeting Goals ( <i>M. Giorgi</i> ) Physics ( <i>A. Bevan</i> ) Computing ( <i>F. Bianchi</i> ) Detector ( <i>F. Forti</i> )	131 250 230	ETD 1 MDI/Backgrounds COMP: R&D	30' 30' 20' 20' 15'	Accel and Cabibbo Lab Status Accel Status ( <i>A. Variola - phone</i> ) Cabibbo Lab Status ( <i>M. Giorgi</i> ) Integr, Inst, IR Hall Summary MDI Summary Comp Summary		
16:00	<i>Coffee Break and Registration</i>	16:00	<i>Lunch</i>	16:00	<i>Lunch</i>	16:00	<i>Adjourn</i>
16:30	PARALLEL 1	16:30	PARALLEL 5	16:30	PLENARY 3	16:30	
131 248 250 230 133 241	SVT DCH PID EMC IFR 17:30-19:30 - Ex Bd (restricted)	250 230	MDI/Backgrounds COMP: Distributed Comp	15' 15' 15' 15' 15' 15'	Summaries SVT DCH PID EMC IFR ETD		
18:30		18:30		18:30		18:30	
		20:00	Social Dinner				

