

## **SABRE**

Roma
Decemeber 10, 2015







# SABRE approved area: ground floor



# SABRE approved area: ground floor



# SABRE approved area



SABRE area: 11.30 x 16.00 m2

## SABRE Active Veto



Vessel already delivered in Priceton: 1.3 m diameter 1.5 m length Made out of low radioactivity steel

### **Liquid scintillator quantity:**


- Volume ≈ 2.25 m<sup>3</sup>
- Weight ≈ 2 ton

### <u>Scintillator options</u> (PPO to be added):

- 1,2,4 –Trimethylbenzene (PC)
  - Good scintillator performance
  - Known and high radio-purity level achievable
  - Infrastructures/competences available @ LNGS
- Linear Alkyl Benzene (LAB)
  - Interesting alternative to PC
  - Share JUNO Collaboration experience
- Different safety approaches for safety and environmental hazards (flammability, toxicity and disposal problems)
- At the moment the choice is PC+PPO to exploit the present Borexino facilities and expertise


## Preliminary Risk Assessment


Hall B: 125 m length x 15 m width x 18 m height (hemispherical)



- Hall B protected with safety containment and liquid collection grid
  - Further collecting pool around and under SABRE installation + optional double containment will be installed
- Hall B air inlet from Southern side + aspiration from Northern Side
  - SABRE can be decoupled from the rest of the Hall B
  - ICARUS capillary emergency air extraction for heavy vapors and gas
- Fire extinguishing system can be specifically developed: Red Devil?
- No major interferences with other Hall B activities
  - $\approx$  50 m distance from Xenon 1T (already assembled, cryogenic experiment)
  - WARP decommissioning


# SABRE PoP hybrid shielding





Bottom: PE (10 cm) + Pb (15 cm)

Lateral walls + top:  $H_2O$  tanks ( $\approx 90$  cm  $H_2O$  thickness)




Shielding set-up 4571 mm x 2743 mm H = 3520 mm

Lead 3571 mm x 2353 mm H = 100 mm


Upper Steel plate 4000 mm x 3500 mm H = 40 mm

Radon box 2742 mm x 1386 mm H = 1702 mm

# PoP hybrid shieling design




## Radon box



### Rn box

- GN2 fluxed
- "double containment for safety" (PC sensors, purge through a charcoal filter, ...)
- Catch basin (1/3 vessel volume is required)
- Sealing to access on the sides to PMTs and on top to the vessel upper flange


# Fluid handing scheme



## Aspetti tecnici per il sito

- Revisione/rimessa in servizio impianti ICARUS
- Sensoristica di sicurezza, controlli, allarmi, supervisione
- Prevenzione incendi
- Impianto acqua (riempimento/ svuotamento)
- Rifusione piombo
- Camera pulita ed impianti dedicati
- Revisione struttura servizi
- Circuito GN2
- Fluid handling (storage, purificazione, sicurezza)
- SRA, Hazop, procedure, coordinamento Sala B
- Aspetti ambientali
- Progettazione meccanica set-up completo
- Logistica, site management
- GLIMOS, RAE
- Infrastrutture di calcolo e rete

## **SABRE Detector**



Crystal dimensions: 3" diameter, 4" length Crystal shape and surface: to be discussed!

Crystal PMTs: 3"flat Hamamatsu R11065

LS veto PMTs: 8" semispherical Hamamatsu R5912


Vessel: 1.3 m diameter 1.5 m length

Liquid scintillator quantity:


Volume  $\approx 2.25 \text{ m}^3$ Weight  $\approx 2 \text{ ton}$ 

### SABRE DETECTOR TECHNICAL ASPECTS

- Crystal enclosures
- Crystal holders
- Crystal handling
- Veto PMT housing
- LS vessel connections
- Calibration source insertion system
- LS vessel internal sensors
- PC+PPO preparation, purification and handling
- LS vessel inner Rn extraction during operation
- PoP shielding set-up (included LS catching basin, Rn box, safety sensors,
- pipe/cable passthrough, water circuit)
- PoP shielding installation/opening/upgrade options
- Top flange removal, crystal removal
- Clean room connection to vessel option
- LS fluid handling (including vessel/pipes/storage) and safety
- PoP infrastructures and services
- Crystal PMT preamp
- PoP check-list and schedules
- Single crystal shielding set-up

















### SABRE PoP check-list

#### Crystal enclosure set-up

Crystal shape and surface?

Enclosure design

Sealing selection

Feedthrough selection

Reflective foil selection

PMT-crystal optical coupling

PMT bias and signal options, Bases & Preamp development

Connectors and cables

Drying system?

Glove box and handling

### LS vessel

Top flanges definition

**Crystal holders** 

Valves, safety valves, pipes for fluid handling, expansion volume

Crystal extraction/insertion system

Lumirror foil

Calibration system

PMT housing

PMT metal shielding, bases, feedthroughs, cables, connectors

Sensors (level, pressure, temperature ...)

Thermal insulation or termperature regulation system?

Internal Rn stripping?

### SABRE PoP check-list

### PoP hybrid shielding

MC simulations

Design and integration

PMT housing and connections

Top supporting structure and plate

Vessel fixing to ground

Vessel translation system?

Crystal insertion/ extraction system?

Source insertion system

Catch basin

Rn box (access to side and top flanges) and safety equipment

Fluid handling pipes and cables pass-through

Water tanks

Lead bottom layer (Pb melting)

Integration

### SABRE PoP check-list

#### **Preparation of the Hall B Site**

```
Clean room construction (glove box?, ..)

Material storage and workshop area preparation ("dirty area")

Infrastructures, utilities

Water circuit

Electrical plant

UPS

Lights

GN2 circuit

Network

LS fluid handling skid and LS storage

PC+PPO preparation and handling

Safety

Safety equipment, sensors and alarms, SCADA system

Fire prevention system
```

### Single crystal passive shielding preparation

Cu, Pb

**GN2** fluxed Radon box

## Documentazione richiesta da LNGS e CSN2

- Obiettivi, programma temporale attività PoP, finanziamenti, milestones
- Proposal PoP
- TDR PoP (inclusi funzionamento, manutenzione, decommissioning)
- Quantitative Risk Analysis (QRA)
- MoU
- Progetto Full Scale exp (TDR, finanziamenti, programma temporale)