



The ENUBET project: high precision neutrino flux measurements in conventional neutrino beams

M. Pozzato (INFN – Bologna)
on behalf of the ENUBET Collaboration
CNNP 2017 - Catania



This project has received funding from the European Research Council (ERC) under the European Union's Horizon 2020 research and innovation programme (grant agreement No 681647).

The problem of flux uncertainty

Indirect technique to estimate neutrino flux (current generation cross-section experiment):

- Monitoring of protons on target (pot), horn currents, muons after the beam dump
- Hadro-production data
- Full simulation of beamline, secondary reinteractions etc.

BUT STILL...

Neutrino experiments affected by an intrinsic limitation:

large uncertainty of the overall neutrino flux ($\sim 7-10\%$) directly reflecting to the cross section measurements.


In addition to the flux uncertainty for $\sigma(\nu_e) \rightarrow$ beam contamination.

$\sigma(\nu_\mu) \leftrightarrow \sigma(\nu_e)$ not simple especially @ low-E (Mc. Farland, 2012)

Poor knowledge of $\sigma(\nu_e)$ can spoil :
the CPV discovery potential
the insight on the underlying physics (standard vs exotic)

Monitored neutrino beams

Kaon-based monitored neutrino beams (A. Longhin, L. Ludovici, F. Terranova, EPJ C75 (2015) 155) are a very appealing candidate since provide a pure and precise source of ν_e



Traditional


- Passive decay region
- ν_e flux relies on ab-initio simulations of the full chain
- large uncertainties

Monitored

- Fully instrumented
- ν_e flux prediction = e⁺ counting ($K^+ \rightarrow e^+ \nu_e \pi^0$)
- “By-pass” hadro-production, PoT, beam-line efficiency uncertainties

ENUBET, ERC Project (Consolidator Grant, PI A.Longhin, Host Institution: INFN) aims to **enable the technology of monitored neutrino beams** for the next generation of experiments (technical challenges / physics reach)

Challenges and Requirements



CHALLENGES:

The decay tunnel is a **harsh environment**:

- **particle rates: > 200 kHz/cm²**
- **backgrounds:** pions from K^+ decays
→ **need to veto 98-99 % of them**
- **instrument region: ~ 50 m**
- grazing incidence
- significant spread in the initial direction

REQUIREMENTS:

e^+ tagger key points:

- longitudinal sampling
- perfect homogeneity
→ integrated light-readout



Photon veto key points:

- photon identification capabilities
- precise timing of the particles
- Exploit 1 mip – 2 mip separation



Neutrino fluxes in the reference design

The **ENUBET design is optimized** to reach a 1% systematic error on the ν_e flux and a <1% statistical error for a **500 ton neutrino detector located ~100 m from the hadron dump.**

Proton Energy	Pot for $10^4 \nu_e$ CC	Run nominal duration
30 GeV [JPARC]	$1.0 \cdot 10^{20}$	~ 3 months at nominal JPARC intensity
120 GeV [Fermilab]	$0.24 \cdot 10^{20}$	~2 months at nominal NuMI intensity
400 GeV [CERN]	$0.11 \cdot 10^{20}$	~3 months at nominal CNGS intensity




PID – Tagger technology




(1) Compact shashlik calorimeter (UCM) with longitudinal ($4 X_0$) segmentation.

- $3 \times 3 \times 10 \text{ cm}^3$ Fe + scint. modules
- SiPM embedded in the bulk of the calorimeter



Separate e^+ , π^+ , μ



(2) Photon Veto Rings of $3 \times 3 \text{ cm}^2$ pads of plastic scintillator



Separate e^+ , γ

1) Hadronic + e.m. calorimeter prototype




Test Beam @ T9 - CERN 2016



56 (e.m) + 18 (had) UCM
modules → 666 SiPM (FBK)



Prototypes: resolution and e/π separation



The obtained results also validate the GEANT4 ENUBET simulation

testBeam @ T9 CERN 2017

Setup shashlik calorimeter (1) :

Scintillator: EJ204 scintillator (double thickness)

WLS Fiber: BCF92 MC

14 X_0 shashlik calorimeter using plastic

Scintillators: new configuration promising a higher light yield and fast response

Goal:

Study calorimeter response (light collection efficiency, linearity response, energy resolution...)



Setup Photon Veto (2):

Scintillator: 3x3x0.5 cm³ EJ200/EJ204

WLS Fiber: Kuraray Y11 MC / BCF92 MC

SiPM: SenSL

Goal:


Study light collection efficiency

First measure of time resolution

First trial of 1 mip / 2mip separation





Photon veto@ CERN-PS T9 2017



1 mip signal is ~ 20 p.e

Testing **1 mip/2mip** separation, exploiting a **Delrin cylinder** on the beam **to enhance the π^0 production** and an **iron γ -converter** ($\sim 0.8 X_0$) for pair production



Ongoing activities (1)

Irradiation studies

ENUBET works after a transfer line (narrow band beam) and the instrumentation is located only at large angles. BUT still the doses are significant and will drive the final detector choice.

- Neutron and ionizing doses have been studied for a tagger radius of 40, 80 and 100 cm with FLUKA and crosschecked with GEANT4.
- Doses at 1 m radius for 10^4 ν_e CC 0.05 kGy (ionizing dose) $2 \cdot 10^{11}$ neutrons /cm² (1 MeV equivalent).
- Test irradiation with 1-3 MeV neutrons performed at INFN-LNL CN Van de Graaff on 12-27 June 2017.
- Characterise rad-hard SiPM with 12-15-20 μ m cell size (FBK, SensL) up to 10^{11-12} 1 MeV-eq n/cm².
- Test viability of self-calibration with m.i.p.






Ongoing activities (2)

Tests:

- Response of irradiated SiPM (FBK, SenSL)
- Custom digitizers electronics
- photon veto prototypes with plastic scintillators
- recovery time (to cope with pile-up)

Scalable/reproducible technological solutions under study:

- Molded scintillators, water-jet holes machining for absorbers
- Polysiloxane scintillators/powder absorbers




Ongoing activities (3)


Simulation of the decay tunnel

Particles are identified by the energy deposit pattern in the calorimeter modules and in the photon veto using a multivariate analysis.

The clustering of energy deposits (“event builder”) is based on position and timing of the signal waveforms in the modules. **Pile up is now fully included.**



composition of the reconstructed sample







Pile-up effect on Ke3 efficiency seen at nominal rates. Mitigation enlarging the radius: ~ 25 % (~ 50 % purity).

Ongoing Activities (4)

Hadron beamline studies

- A realistic implementation of the beam-line/focusing layout.
- Site-independent. We are considering existing proton driver energies.
- FLUKA/G4Beamline simulations in progress. Support early estimates.
- Assess beam-related backgrounds.
- Machine studies of multi-Hz slow resonant extraction at CERN-SPS



Conclusions

- At **GeV scale** the limited **knowledge on the initial flux** is the **dominant contribution to cross section uncertainties** → exploiting the $K^+ \rightarrow \pi^0 e^+ \nu_e$ channel (Ke3)
- **ENUBET is investigating this approach** and its application to a new generation of neutrino experiments.: enabling a technology to directly **monitor neutrino production at source** → **major breakthrough in experimental neutrino physics.**
- The **results** obtained in the first year of the project are **very promising**:
 - The Reference Design has been established
 - The detector technology was studied with dedicated prototypes and testbeams, and performance fulfills the expectations
 - The simulation of the decay tunnel is now complete and include particle identification, pile up and assessment of ionizing and non-ionizing doses
 - The work on the beamline simulation and systematics assessment has started