

# DESCRIPTION OF THE STRIPPING TEST @ DAYA BAY

Michele Montuschi, INFN Ferrara  
on behalf of the Liquid Scintillator Group


# SUMMARY

- **Motivation** of the Test
  - Stripping column **efficiency**
  - **Radon** problem
- **Stripping** Column
  - Nominal and Operational **Conditions**
- **Operations** done at DayaBay
- **Results**
- **Discussion**
- Distillation and stripping pilot plants **paper**
- **Conclusion**

# TEST MOTIVATION

## STRIPPING COLUMN EFFICIENCY


- **Volatile compounds** (as Rn, Ar, Kr) can be removed from a solution by stripping the liquid stream with a gas flow in a stripping tower. The towers serve to breakup the water into droplets and allow contact between the solution and the gas with subsequent transfer of volatile components to air phase.
- The transfer rate of a compound from the gas to the liquid phase depends on the **equilibrium conditions**, basically on T and p



# TEST MOTIVATION


## STRIPPING COLUMN EFFICIENCY

- In order to determine the stripping efficiency is necessary to calculate the **column height** imposing the equilibrium in each stage
- The solubility can be extracted from the **Henry Law**
- It is very hard to find the Henry Coefficient for LAB in literature
- Need a specific experiment to prove the capability and the efficiency of the stripping process of the LAB on removing the volatile radioactive impurities



# TEST MOTIVATION

## RADON PROBLEM




From Yu Boxiang talk  
docDB 3014-v1

- **<sup>222</sup>Rn Pollution** after the insertion of LAB and PPO
- We suspected leakage from
  - Cover-gas pipeline connector and plastic pipe
  - Replacement system

# TEST MOTIVATION

## RADON PROBLEM




From Yu Boxiang talk  
docDB 3014-v1

- Upgrade of the **Replacement system**
  - Replacement system covered with **N<sub>2</sub> blanket acrylic house**;
  - Pipeline connector encapsulated in **boxes purged with N<sub>2</sub>**;
  - Painted the ground with a **radon resistive panting** and covered with HDPE foils;

# TEST MOTIVATION

## RADON PROBLEM




After two 12 hours loop run, one with high Rn content in the acrylic housing, another with very low Rn content, there were no obvious difference in the concentration of the  $^{222}\text{Rn}$  inside the ADI-LS. **The Replacement system is not the source of  $^{222}\text{Rn}$**

# TEST MOTIVATION

## RADON PROBLEM

From Yu Boxiang talk  
docDB 3014-v1



- Upgrade of the **ADI cover-gas**
  - Replaced the normal Nitrogen with HP Nitrogen (from  $0.19 \pm 0.025$  Bq/m<sup>3</sup> to  $0.039 \pm 0.009$  Bq/m<sup>3</sup> )
  - Changed the inlet of ADI cover-gas
  - Pipeline connector encapsulated in boxes with N<sub>2</sub> purging;


# STRIPPING PILOT PLANT

- Stripping plant is based is used to remove the impurities that are more volatile than LAB: Ar, Kr and Rn. Water steam in order to avoid to use huge quantity of nitrogen in underground (safety). Stripping is carried out with counter-current flow of the liquid LAB and water super heated steam and/or nitrogen in a column containing non structured packing (Pall Rings 13 x 0.3 mm and 430 m2/m2).
- High temperature (100 °C) for higher column efficiency (low LAB viscosity)
- Partial vacuum (around 300 mbar)
- Both steam and nitrogen stripping could be tested in the plant
- Electrical Power ~ 10 kW
- Cooling Power ~ 5 kW
- Pure water from Daya Bay water plant (approx. 50 l)
- All the plant is kept under continues nitrogen blanket either to avoid oxidation/contamination but also for safety reason (LAB temperature < flash point)
- Vapour condenser before water vapour/nitrogen exhaust for safety
- Rupture disks for pressure safety

## Nominal Process Parameter

| Stripping | Height(m) | Diameter (mm) | # of Trays             | Pressure (mbar) | Temperature (°C) | Scint. flow (l/h) | Steam Flux (g/h) | Gas Flow (g/h) |
|-----------|-----------|---------------|------------------------|-----------------|------------------|-------------------|------------------|----------------|
|           | 7         | 75            | Non-Structured Packing | 300             | 100              | 100               | 250              | 250            |

# OPERATING CONDITION OF THE STRIPPING PILOT PLANT




- Column Pressure around 300 mbar regulated with a very small nitrogen flow and partially closing the valve between the vacuum pump and the column
- Output flow between 80 and 140 kg/h
- Temperature of the steam around 80 °C
- Temperature of the LAB flow to the column around 90 °C to avoid condensation of the steam in the LAB
- Filters at 0,05 µm are effective and don't get clogged
- Main issue is to keep constant the steam flow to the column, maybe the orifice is clogged with some LAB

# STRIPPING TEST @ DAYA BAY SITE IN NOVEMBER


1. **Blank test** (without stripping) to check the amount of  $^{222}\text{Rn}$  added during the recirculation
2. **Tested** if the Stripping Pilot Plant **introduce  $^{222}\text{Rn}$**  in the liquid scintillator during the operations
3. **Added  $^{222}\text{Rn}$  in the Liquid Scintillator** using water with an high content of  $^{222}\text{Rn}$  in the water extraction plant
4. Processed 10498 l of the Liquid Scintillator at a flow rate of 113 l/h on average with the **Stripping Pilot Plant** using a 1,5 Nm<sup>3</sup>/h N<sub>2</sub> flow

# STRIPPING TEST @ DAYA BAY SITE IN NOVEMBER



# RESULTS


## LS AFTER A BLANK RECIRCULATION



**From Xiaofeng Zhang  
analysis**

# RESULTS

## LS AFTER WATER EXTRACTION WITH NORMAL WATER



# RESULTS

## MODEL

- The count of  $^{222}\text{Rn}$  decay at each hour could be obtained by the count a hour before:

$$N_t = N_{t-1} \cdot \left[ e^{-\lambda \Delta T} - 115 \cdot \eta \cdot \frac{\Delta T}{FV} \right] + leak$$

- $N_t$ : the **count of  $^{222}\text{Rn}$**  decay at the time  $t$
- $\lambda$ : the **decay constant** of  $^{222}\text{Rn}$
- $\eta$ : stripping **efficiency**
- leak: the contribution of leakage.
- $\Delta T = 1\text{h}$
- Both  $N_t$  and leak are in the unit of decay/h.

From Xiaofeng Zhang  
analysis  
docDB 3048-v1

# RESULTS

## FIT PARAMETRI

- The has been done minimising the  $\chi^2$  defined as follow


$$\chi^2 = \sum_t \frac{(y_t - N_t)^2}{N_t}$$

From Xiaofeng Zhang  
analysis  
docDB 3048-v1

- where  $y_t$  and  $N_t$  are the observed and expected counts of  $^{222}\text{Rn}$  decay at time  $t$  respectively.
- The free parameters in the equation above are  $N_0$ ,  $\eta$ , leak.
- The fit range of the three free parameters:
  - $N_0$ :  $y_0 - 125 \leq N_0 \leq y_0 + 124$ , step length = 1, total 250 values;  
 $y_0$  is the observed counts of  $^{222}\text{Rn}$  decay at the starting time
  - $\eta$ :  $0.85 \leq \eta \leq 1.24$ , step length = 0.01, total 400 values;
  - leak:  $0 \leq \text{leak} \leq 4.9$ , step length = 0.1, total 50 values;

# RESULTS

## BEST FIT RESULT



- $N_0$ :  $4905 \pm 11$  decay/h
- $\eta$ :  $95.8\%^{+1.1\%}_{-0.9\%}$
- leak: 0.2 decay/h

# DISCUSSIONS

- From the graph shown in the slide 11 the leak can be calculated as 200 Atoms/h

for a small  $\Delta T$

$$\frac{\text{Atoms}}{h} \approx \frac{\text{decay}}{h} \cdot \lambda \quad \text{where} \quad \lambda = \frac{\ln 2}{T^{1/2}} \sim \frac{1}{132}$$

The 0.2 decay/h was not consistent with the recontamination of 200 Atoms/h  $\sim$  1.5 decay/h.

- if the average flux rate was 113 L/h, then the best fit for efficiency should be  $95.8 \cdot 115 / 112.9 = \mathbf{97.6\%}$ , bringing the purification factor from 25 to 41
- From the minimum  $\chi^2$  analysis it can be seen that there is a strong correlation between leak and efficiency. One possible reason should be that the influence of variation of efficiency is comparable with leak.
- If there was some radon in the stripping nitrogen, then the actual efficiency should be higher than the best fit. where the parameter  $c$  represents the contamination of radon in stripping nitrogen

$$N_t = N_{t-1} \cdot \left[ e^{(-\lambda \cdot t)} - 115 \cdot \eta \cdot \frac{t}{FV} \right] + 115 \cdot c + \text{leak}$$


- that the precise value of  $c$  is unknown.

# DISTILLATION AND STRIPPING PILOT PLANTS PAPER

- Scientific **Motivation**
  - Check the effectiveness of removing the radioactive impurities from the LS
  - Check the optical purity of the LS after the purification stages
  - Check the reliability of the equipments
- Distillation and Stripping process **theories**
- **Characterisation** of the distillation and of the stripping plants (focus on P&Id and the peculiar features of the plant)
- **Results**


# CONCLUSION

- The Rn main source in the ADI is from Nitrogen cover-gas maybe due to a leak in the connectors and in the plastic tubes;
- The stripping test has been done from 20/11 to 30/11 processing more than 10000 l of LS.
- Stripping efficiency calculated from the fit is  
 **$\eta=95.8\%$**   
giving a purification factor of 25.
- Taking into account the value of the Coriolis flow rate the efficiency increase to the value of  
 **$\eta=97.6\%$**   
with a purification factor of 41, that should be taken into account while estimating the systematic error.
- The leak factor need has to be better understood and probably is underestimated. An higher value of the leak factor could bring to an higher value of the efficiency.
- Also the  $^{222}\text{Rn}$  content of the nitrogen can influence the total efficiency of the stripping.



“Thanks!!!”.

–Michele Montuschi



# BACKUP SLIDES



**Acrylic house cover the RP system  
and blanket with N<sub>2</sub>**

**After this process, the Rn count in acrylic  
house is still high;**



**LS connector purged by nitrogen**




**Nitrogen control the valve**




- RAD7 Rn detector was sealed in a Acrylic tank on Hall 1 ground (near replacement system), test the Rn level change with the change of time;

# Radon resistive paint experiment



Beihang paint

With Beihang paint




**Add paint and a HDPE foil on the ground;  
Purge with N2 in high flux rate;  
Rn level of cover house :  
Reducing from 55 Bq/m<sup>3</sup> to 1Bq/m<sup>3</sup> (RAD7 detection limit);**


**HDPE foil (Black foil)**



# AD1 Cover-gas pipeline @DYB Hall1#



# Dependency of $\chi^2$ on $\eta$ , $N_0$ , leak



- Best fit result given by minimizing  $\chi^2$ :  $\eta = 95.8\%$ ,  $N_0 = 4905$ , leak = 0.2.