



Contribution ID: 296

Type: **Poster**

Transformer-Coupled TES Frequency Domain Readout Prototype

Thursday, July 25, 2019 6:45 PM (15 minutes)

Frequency domain multiplexing (fMUX) is a mature readout scheme for TES detectors in the millimetre and sub-millimetre bands. It is implemented at MHz carrier frequencies for the South Pole Telescope, POLAR-BEAR, and Simons Array, and is planned for deployment on the LiteBIRD space polarimeter. Existing implementations couple to the detectors with low-noise, low-input impedance SQUID transimpedance amplifiers, and complex arrangements are in place to handle the inherent SQUID non-linearity and tuning requirements. We introduce a new cryogenic amplification scheme that couples the multiplexed TES devices to a traditional FET amplifier using a high turns-ratio, wide-band, cryogenic transformer that steps up the TES impedance to the noise match of the amplifier. We characterize the bandwidth, transimpedance, input impedance, and noise of the transformer-coupled fMUX system to demonstrate that it is a promising candidate for SQUIDless MHz frequency domain multiplexing.

Less than 5 years of experience since completion of Ph.D

Y

Student (Ph.D., M.Sc. or B.Sc.)

Y

Primary author: ROUBLE, Maclean

Co-authors: Prof. DOBBS, Matt (McGill University); GILBERT, Adam (McGill University); MONTGOMERY, Joshua (McGill University); NOBLE, Gavin (McGill University); VERGÈS, Clara

Presenter: ROUBLE, Maclean

Session Classification: Poster session

Track Classification: Detector readout, signal processing, and related technologies