



Contribution ID: 39

Type: **Poster**

## Design Optimization of a 10 Kilopixel Optical Band Microwave Kinetic Inductance Detector

*Thursday, July 25, 2019 6:45 PM (15 minutes)*

In order to make improved spectral imaging measurements in the ultraviolet, visible and near infrared bands, we investigated the design of a 10 kilopixel Microwave Kinetic Inductance Detector (MKID) sensitive in these bands. We evaluate design parameters and different geometries for MKIDs arrays with equally spaced resonant frequencies and high intrinsic and coupling quality factors. Resonance frequencies were chosen in the range of 2.8-4.8 GHz with an average of 2 MHz intervals. We describe the optimization of our design, including reduced cross-coupling. Through simulations, we find the average intrinsic and coupling quality factors to be on the order of 107 and  $3 \times 10^4$  respectively, which are good enough for our purposes.

### Less than 5 years of experience since completion of Ph.D

N

### Student (Ph.D., M.Sc. or B.Sc.)

N

**Primary author:** Dr SHAFIEE, Mehdi (Energetic Cosmos Laboratory, Nazarbayev University)

**Co-authors:** Prof. SMOOT, George (UC Berkeley University ); Dr GROSSAN, Bruce (UC Berkeley Space Science Laboratory); Dr COLANTONI, Ivan (Consiglio Nazionale delle Ricerche, Istituto di Nanotecnologica, Rome, Italy); Dr HU, Jie (3Université Sorbonne Paris Cité Laboratoire APC-PCCP Université Paris Diderot, Paris, France)

**Presenters:** Dr SHAFIEE, Mehdi (Energetic Cosmos Laboratory, Nazarbayev University); SHAFIEE, Mehdi (Nazarbayev University)

**Session Classification:** Poster session

**Track Classification:** Low Temperature Detector fabrication techniques and materials