

# thinfilms and NEW IDEAS for SRF

Contribution ID: 22

Type: **not specified**

## Cryogenic RF performances of Nb<sub>3</sub>Sn films on Copper

*Tuesday, 9 October 2018 13:10 (25 minutes)*

Superconducting radio frequency (SRF) cavities, made of niobium films on copper (Nb/Cu), are currently employed for a large variety of particle accelerators. At the same time, the Nb/Cu technology, being very cost effective, also represents one of the main options for upcoming machines like the future circular collider (FCC).

While research and development continue on the Nb/Cu technology, there is still a performance gap with respect to the best results that can be obtained with bulk Nb.

Alternative superconducting materials, with larger critical temperature  $T_c$  and superheating field  $H_{sh}$ , might pave the way towards higher performance. In this respect, materials in the A15 family, like Nb<sub>3</sub>Sn, are among the most promising. At CERN, a reliable coating procedure for Nb<sub>3</sub>Sn films on copper, using niobium or tantalum as intermediate layer, has been developed. The films are reproducible and show excellent DC transport properties ( $T_c$  up to 17 K), morphological and structural characteristics. A comprehensive RF characterization of these films was still missing though.

In this work, we report the results of a Nb<sub>3</sub>Sn film coated on a copper sample, measured in the CERN quadrupole resonator (QPR). The QPR enables the characterization of small samples at different temperatures, RF frequencies and field values.

The main results are compared with those from Nb bulk and Nb/Cu samples, measured with the same technique.

**Primary author:** Dr ARZEO, Marco (CERN)

**Co-authors:** Dr ROSAZ, Guillaume (CERN); Dr ILYINA, Katsiaryna (CERN); Dr VENTURINI DELSOLARO, Walter (CERN)

**Presenter:** Dr ARZEO, Marco (CERN)

**Session Classification:** Other SC Materials beyond Niobium: Nb<sub>3</sub>Sn

**Track Classification:** Other superconducting materials beyond niobium