

The KIT accelerator test facilities: Karlsrhe Research Accelerator KARA, short-pulse linac FLUTE and magnet characterizaton facilities

Akira Mochihashi, On behalf of IBPT test facilities Karlsruhe Institute of Technology (KIT)

INSTITUTE FOR BEAM PHYSICS AND TECHNOLOGY (IBPT), KIT





Contents




- Introduction
 - Overview of Test Facilities in KIT
 - Karlsruhe Research Accelerator KARA
 - Magnet Characterization Facilities MCF
 - Short-pulse linac FLUTE
- Present status and ongoing projects
 - KARA & FLUTE
 - ATHENA & cSTART
 - ARIES
- Future plan of the Karlsruhe accelerator test facilities
- Summary

Karlsruhe Research Accelerator KARA



- From ANKA "users facility" to KARA "accelerator test facility"
 - Misson: research & development of beam physics and technology
 - Additionally, KARA can be operated as a synchrotron radiation light source
- Key parameters of KARA
 - Beam energy: 0.5 2.5 GeV
 - Beam current: up to 200 mA
 - Circumference: 110 m
 - 500 MHz RF system
 - RMS bunch length: 50 to few ps
- Outstanding features
 - Superconducting undulators




MCF: Magnet Characterization Facilities




SCU20: First commercial product worldwide



- Installation in December 2017
- Successfully operating in the KIT synchrotron since January 2018 without quenches
- First X-rays 10.1.2018



S. Casalbuoni et al., SRI2018



Courtesy of Dr. S.Casalbuoni

Infrastructure at KIT for SCU technology




To advance SCU technology unique infrastructure to characterize the magnetic field (MCF) of the superconducting coils (quality assurance) and to measure input parameters necessary for the design have been developed.

CASPER I



CASPER II



COLDDIAG



- A. Grau et al., IEEE Trans. Appl. Supercon. 26-4 410804 (2016)
- R. Voutta et al., PRSTAB, 19, 053201 (2016)

Courtesy of Dr. S.Casalbuoni


FLUTE: short-pulse linac test facility



Linac test facility for femtosecond electron beam


Generaton of THz coherent synchrotron radiation

- R&D topics
 - Test bench for new diagnostic methods in fs-range
 - Synchronization on a femtosecond level
 - Bunch compresson, beam physics









Final electron energy	~ 41 MeV
Electron bunch charge	0.001 - 3 nC
Electron bunch length	1 - 300 fs
Pulse repetition rate	10 Hz
THz E-Field strength	up to 1.2 GV/m



Solenoid


E-Gun


KARA storage ring: accelerator operation Today



- Machine physics (588 hrs.)
 - 1week per month (in average)
 - Test for new diagnostic device
 - Beam physics & development
 - Low alpha operation etc.
- User-operation (1194 hrs.)
 - From Tuesday to Friday
 - Injection: once per a day (150 mA)
 - Energy ramping: 0.5 to 2.5 GeV
 - 70 mA at next injection
 - Beam injection by 1-2 operators
 - Stable beam delivery
- Start-up
 - Monday afternoon
 - Accelerator tuning

We have good activities for machine physics experiment.






An example of activities: THz CSR&beam physics



Bursting THz CSR observation: time-resolved phase space tomography

- Low alpha 1.3 GeV
- MHz line camera KALYPSO
- Picosecond sampling systemKAPTURE
- EO sampling in KARA



Long. bunch profile

Hor. bunch profile

Intensity of THz rad.

Turn-by-turn resolution


Detector systems

ASIC design

Si microstrip sensor design


High-density interconnections

DAFNE-TF Workshop 2018



Microbunching instability

- Vlasov-Focker-Planck Solver "Inovesa"
- Physics of microbunching instability



Longer than 70000 turn(26 ms)


Longitudinal bunch profile

Intensity of THz radiation

An example of activities: ARIES and EuroCirCol



- ARIES (Accelerator Research and Innovation for European Science and Society)
 - KIT as a member of "Rings with Ultra-Low Emittance (RULE)" in ARIES-WP7
 - Beam dynamics in low and negative momentum compaction factor
 - Transnational Access Scheme (TNA) in ARIES
 - KARA & FLUTE: as facilities offering TNA for "Electron and proton beam testing" in ARIES-TNA-WP11




Negtive momentm compaction beam in KARA

- **EuroCirCol** (The **Euro**pean **Cir**cular Energy-Frontier Collider Study)
 - "Measurements of cryogenic beam vacuum system prototype (KIT, INFN, CERN)" in WP4 Task4.6










FLUTE short-pulse linac facility: present status




Commissioning of RF photo injector

RF photo-injector parameters				
Frequency	2.998	GHz		
Cells	2.5			
Peak E-field	100	MV/m		
Peak power	20	MW		
Output energy	7	MeV		

Input power to RF gun: 4 MW



- To go proceed RF commissioning:
 - Replacement of Circulator on April 2019
 - Commissioning of different RF components can be possible after the replacement



Courtesy of FLUTE comissioning team


screen

First beam on YAG

800 1000 1200

FLUTE short-pulse linac facility: ongoing plan





Ultra-short bunch diagnostics

Split ring resonator SRR: femtoseconds beam streaking with THz high intense EM field
 Driven by follows for the RE photosethode

Driven by fs laser for the RF photocathode

Table: SRR parameters		fs laser LiNbO ₃ THz 20 μm detector	RF gun
Gap size in x	20 µm	pulse split ring resonator	
Gap size in y	20 µm	UV pulse	
Gap width in z	10 µm	1	
Resonant frequency	300 GHz	cathode	
Peak electric field	500 MV/m	streak field	
Integrated field	10kV	$V\sin(2\pi f t + \varphi)$	

chamber

Distributed accelerator test facility: ATHENA



- ATHENA: Accelerator Technology Helmholz Infrastructure
 - Distributed accelerator test facility in Germany
 - Collaboration and Synergy of 6 Helmholz centers
 - DESY, GSI with HI Jena, HZB, HZDR, FZJ, and KIT
 - Funded on 2018 with 30 million Euro



ATHENA at KIT

- Real-world applications of LWFA electron beams
- Enable multi-user access for materials and life sciences applications
- Example: MHz-repetition rate terahertz medical imaging facility (TMED)
- Benefits from cSTART and sensor technologies

From acceleration towards accelerators and user-readiness


Compact storage ring test facility: cSTART




<u>cSTART:</u> compact Storage Ring for Accelerator Research and Technology



- Storage of ultra-short (fs) electron bunches
- 1st study¹⁾: laser wakefield accelerator(LWFA) injection in ring-based light sources
- Unique design²⁾: non-equilibrium ring with very large momentum acceptance
- Goal: world-wide 1st injection & storage of a LWFA beam in a storage ring





Akira Mochihashi

¹⁾S. Hillenbrand (RU5) *et al.*, NIM A 740, 153 (2014); S. Hillenbrand, Ph.D. thesis (2013). ²⁾A. Papash, E. Bründermann, A.-S. Müller (all RU5), Proc. IPAC2017, TUPAB037 (2017).

As facilities of ARIES Transnational Access



KARA & FLUTE

- Transnational Access Scheme (TNA) in ARIES
- As facilities offering TNA for "Electron and proton beam testing" in ARIES-TNA-WP11
- New experiments and projects in the framework ARIES-TNA has been planned <u>JUST NOW.</u>

Please contact to ARIES-TNA if you have some new ideas of interesting experiments in KARA and FLUTE.

We are looking forward to seeing you at KIT with good collaboration!



https://aries.web.cern.ch/ta


Future KARA: Beam Physics Test Facility



- As a platform of beam physics experiment
 - Installation of "universal device section" into KARA storage ring
 - Users perform "Plug & Play" experiment with 0.5 2.5 GeV beam
- Examples of the Plug & Play experiment
 - Vacuum chamber with variable aperture & coating: <u>impedance</u>
 - Beam test for insertion devices & magnets: <u>light source development</u>
 - Beam instrumentation devices: <u>beam dynamics & diagnostics</u>
 - RF devices : <u>RF acceleration & beam manipulation</u> and more...

So many world-wide contributions to the accelerator physics and technology can be expected

- Advangates of experiment at KARA
 - Systematic beam diagnostic measurement is possible now
 - Flexibility of beam condition: bunch length, beam energy
- R&D topics for Plug&Play experiments
 - Science: improvement of beam tuning knobs, diagnostics etc.
 - Technology: vacuum system design, alignment method etc.




Future FLUTE: Short-pulse Beam Facility



- Beam physics experiment with <u>real short-pulse electron beam</u>
 - Preparation for experimental station beamline
 - Users perform experiments with their own instrumentation
- Examples of the experiment with short-pulse beam in FLUTE
 - R&D of beam diagnostics and instrumentation: <u>beam dynamics &</u> <u>diagnostics</u>
 - Generation of THz radiation: <u>light source</u>
 - Short-pulse electron beam application: <u>material science & chemistry</u>

So many contributions to both the accelerator physics and matter science can be expected



Summary: Present status



- Karlsruhe Research Accelerator KARA
 - Accelerator test facility with 0.5-2.5 GeV electron storage ring
 - Activities for machine physics
 - THz CSR generation, microbunching instability etc.
 - ARIES, EuroCirCol project
- FLUTE short-pulse linac test facility
 - First beam confirmed and further commissioning now
 - Ultra-short pulse generation
 - Bunch compression
 - Femtosecond beam diagnostics: splitting ring resonator
- Distrubuted accelerator test facility: ATHETA
 - Funded and ongoing now
- Compact storage ring test facility: cSTART
 - Funded and ongoing now

Summary: Future plan



Future KARA

- Platform of beam physics experiment
- "Plug & Play" experiment in "universal device section" at KARA storage ring
- To keep flexibility of experimental condition and beam operation

Future FLUTE

- Beam physics experiment station with short-pulse electron beam
- Users can bring their own instrumentation and perform their experiment
- Accelerator physics, material science, chemistry etc.

So many contributions to the accelerator physics and related sciences can be expected

Thank you very much for your attention!

Backups



Future plan: KARA storage ring




- Control & manipulation of accelerators and beams
 - Control: optimization of operating parameters by machine learning
 - Optimization of injectors (booster, microtron, beam transport line)
 - Optimization of storage ring for various kind of operating modes
 - Control: accelerator operation with <u>saving energy consumption</u>
 - Optimization of booster operation: pattern control
 - Optimization of warm-up process in storage ring: start-up/shut-off sequence control
 - Cooling water, air conditioning control

Manipulation: 3-dimensional beam manipulation

- RF gymnastics and modulation
- Alpha (and lattice) manipulation
- Expansion of dynamic aperture
- Improvement of tuning knobs

Akira Mochihashi

Control of THz CSR generation



Future plan: FLUTE short-pulse linac facility



- Control & application of ultra-short pulse beam
 - Control: bunch compression to ultra-short pulse
 - Beam diagnostics of THz-CSR from bunch compressor section
 - Feedback to linac/laser parameters with machine learning by THz-CSR diagnostics
 - Application: <u>ultra-short pulse beam source</u>
 - R&D for new detectors and beam diagnostics devices
 - Electron beam & THz-CSR beam

- Application: an injector for cSTART ultra-short pulse storage ring
 - Optimization of injection condition for ultra-short pulse beam

... And more!

IBPT: Institute for Beam Physics and Technology



- Director: Prof. Dr. Anke-Sussane Müller
 - Coodination & project team
 - Safety & radiation protection team
 - Administration team
 - Operation-1 & Accelerator R&D Gr.
 - Device team
 - Theory & beam dynamics team
 - Control & instrumentation team
 - THz/IR application team
 - Operation-2 & Accelerator R&D Gr.
 - Diagnostics R&D team
 - New accelerator concept team
 - IT team
 - Insertion device team
 - Technical Gr.
 - Workshop team
 - Construction team
 - Vacuum, water & cooling team
 - Electricity & electronics team



http://www.ibpt.kit.edu/

