



Contribution ID: 255

Type: talk

High gradient ultra-high brightness C-band photoinjector

Thursday, September 19, 2019 6:40 PM (20 minutes)

Recent studies and investigations show the possibility to increase the cathode peak field, using normal conducting structures with a reduced RF pulse duration or using copper structures operated at cryogenic temperatures. In this context we studied the beam dynamics advantages using a 1.6 cells C-band gun operated at the gradient of 240 MV/m, in order to set the photo-injector layout for the XLS design study. The higher gradient combined with a shorter RF gun structure, pushes the beam to a relativistic energies faster and in less space compared to the 1.6 cells S-band case operated at 120 MV/m. In order to use only one frequency in the entire injector and to save longitudinal space, we used in the simulations two TW C-band structures operated at the accelerating gradient of 40 MV/m. Scaling the beam parameters from the S-band scenario and re-optimizing the solenoid magnetic field and all the device positions, it is possible to increase the beam brightness at least of an order of magnitude. The beam exiting the C-band gun completely match the requests of the XLS design study, also saving a factor two in the longitudinal photo-injector size compared to the S-band scenario.

Primary authors: VANNOZZI, Alessandro (ROMA1); GIRIBONO, Anna (LNF); VACCAREZZA, Cristina (LNF); ALESINI, David (LNF); CARDELLI, Fabio (LNF); DIOMEDE, Marco (LNF); FERRARIO, Massimo (LNF); CROIA, Michele (INFN / LNF)

Presenter: CROIA, Michele (INFN / LNF)

Session Classification: WG3 - High Gradient RF Technology

Track Classification: WG3 - Electron beams from electromagnetic structures, including dielectric and laser-driven structures