

New Vulcan PetaWatt Beamline: Ultra-broadband, picosecond OPCPA FrontEnd

- EAAC 2019 Workshop -

Mario Galletti^{1,2}

G. Archipovaite¹, P. Oliveira¹, M. Ahmad¹, M. Galimberti¹,
I. Musgrave¹, C. Hernandez-Gomez¹

¹Central Laser Facility, STFC, RAL, Chilton, Didcot, Oxfordshire, OX11 0QX, UK

²GoLP / Instituto de Plasmas e Fusão Nuclear, Instituto Superior Técnico, Lisbon, Portugal



Vulcan laser facility

Motivation for the new PW beamline

VOPEL: Fully OPCPA, PW beamline


Overview and its design

Ultra-broadband, ps Front End

Current status of the research

Summary & future plans

Nd:Glass laser system delivering 8 beams.
It is Based on the CPA technique with an OPCPA Front End.



TAW

Long Pulse:

6 beams, 250J, 0.5-6ns

Short Pulse:

~70J, 1ps or 200J, 10ps

TAP

Long Pulse:


250J, 1ns

Short Pulse:

~500J, 500fs


Combining two PW beamlines will allow us:


- **Pump-probe** experiments
 - Combining e^- and p^+
 - Space Radiation
 - Reproduction
- New **imaging** capability
 - Betatron/ X-ray Imaging



Adopting only the auxiliary PW beam line will allow us:

- Betatron imaging
- X-ray imaging
- Acceleration experiments: e^- , p^+ and light ions





Vulcan laser facility

Motivation for the new PW beamline



VOPEL: Fully OPCPA, PW beamline


Overview and its design

Ultra-broadband, ps Front End

Current status of the research

Summary & future plans





High energy amplification stage 1

Seed 3 ns, ~1 J

Pump Nd:glass rods

5 min rep. rate, 30 J, 1053 nm, 3 ns

SHG pump in KDP 60% eff, 18 J.

Amplified signal 7 J


High energy amplification stage 2

Seed 3 ns, ~7 J

Pump Nd:glass disk (108 mm)

20 min rep. rate, 220 J, 1053 nm, 3 ns


Upgraded to **air cooled disk** amplifier.




SHG pump in KDP 65%, 140 J

Amplified signal 50 J

Sketch of the new PW beamline



High energy Ns Compressor





1% of the beam
dedicated to the
diagnostic

Compressor Parameters

- Gold gratings
- 1100 Grooves/mm
- Transmission 60%.

Sketch of the new PW beamline



**New interaction Chamber:
Betatron Imaging Setup**

Vulcan laser facility

Motivation for the new PW beamline

VOPEL: Fully OPCPA, PW beamline


Overview and its design

Ultra-broadband, ps Front End

Current status of the research


Summary & future plans

Ultra-broadband ps FrontEnd




New Fully OPCPA TAP

Rep. Rate: 100 Hz
Wavelength: 880nm
Pulse energy: ~1.5 mJ
Pulse duration: 10 ps





Goal: sub-30 fs, 1 mJ, 160 nm @880 nm.



The ps NOPA4 stage deliver pulses:
up to **1.5 mJ**, down to **15 fs**, **> 160 nm**.
The NOPA4 efficiency is ~15%.

Goal: sub-30 fs, 1 mJ, 160 nm @880 nm.



- The temporal jitter influences the first two NOPA stages, which could be corrected by minor adjustment of the delay between signal and pump.

- **Active stabilisation** on going.

- The non-compensation of the 3rd order spectral phase, visible with **pre-post pulses**, creates these instabilities in the temporal length.

- **Dazzler** implemented but not a feedback loop

We presented **VOPEL: a fully OPCPA, PW beamline**
for the Vulcan laser facility.

The full beamline will be ready mid-2021.

The ps Front End is on commissioning:

~1.5 mJ, 100 Hz, compressed to 18 fs, BW~170 nm centred @880nm.

On time of the project plan schedule

Compressor fully designed, large crystal on order.

Laser

Munadi Ahmad
Giedre Archipovaite
Andrew Frackiewicz
Mario Galletti*
Steve Hawkes
Ian Musgrave
Pedro Oliveira
Dave Pepler
Waseem Shaikh
Trevor Winstone

Mechanical

Paul Johnson
Andrew Stallwood
Jonathan Saa
Steve Blake
Brian Wyborn

Target Area

Nicola Booth
Rob Clarke
Rob Heathcote
Dave Neely
Margaret Notley

Electrical

Paul Amos
Rich Bickerton
Mark Dearing
Jorge Suarez Merchan
Adrian Thomas
Tinesimba Zata
Alan Stevens

Sponsor

Cristina Hernandez-Gomez
John Collier