

O3.203 High-efficiency rugby-shaped hohlraum designs for driving large gas-filled capsules on the NIF

Wednesday, 10 July 2019 12:10 (15 minutes)

See the full abstract here <http://ocs.ciemat.es/EPS2019ABS/pdf/O3.203.pdf>

In indirect-drive inertial confinement fusion (ICF) a high-Z enclosure (or “hohlraum”) surrounds a low-Z capsule containing DT fuel inside a low-Z spherical shell. Laser beams irradiate the interior of the hohlraum through a pair of laser entrance holes, in turn creating an x-ray radiation “bath” that compresses the fuel to ignition conditions. The coupling of laser light to the capsule is typically ~10%, resulting in ~200 kJ absorbed energy for the ~2 MJ-scale laser at the National Ignition Facility (NIF). A 7 mm-wide rugby-shaped Au hohlraum design is found that can accommodate ~50% larger (DT) gas-filled capsules for up to 500 kJ capsule absorbed energy and ~30% coupling efficiency. This new integrated design is made possible by using a high-density gas fill (6-8 mg/cc) that limits the fuel convergence ratio (C) to <14. The low C greatly limits the degrading effects of hohlraum drive asymmetry and hydro-dynamic instability from surface roughness and target-fielding fixtures, e.g., capsule tent supports and the DT fuel-delivery fill tube. Integrated hohlraum simulations in 2-D show good implosion symmetry with peak radiation temperatures reaching 295 eV at <1.8 MJ of laser energy and 440 TW peak power while delivering nearly 100 kJ of energy (compared with ~60 kJ in DT-layered implosions). The hohlraum design is made possible by employing a shaped two-shock laser power history for compressed energy delivery and desired margin to late-time hohlraum filling (and loss of symmetry control). Confidence in this design is supported by a recently reported campaign on the NIF using a reverse-ramp pulse shape to drive a similar rugby-shaped hohlraum and a ~ 3.5 mm-scale Al shell filled with 7 mg/cc DT gas [1]. The high fuel-adiabat ($\alpha \sim 6-7$) character of the 2-shock design is tolerated due to the higher performance margin from the large-capsule design. This platform can be extended to include varying thicknesses of DT solid-fuel layering for increased yield (> 1 MJ), while benefitting from the favorably low C (<20). Further inroads into understanding ignition thresholds and the transition from volume-dominated (-PdV) ignition to higher-C hot-spot ignition could result from initially leveraging an optimized low-C gas-fill design.

[1] Y. Ping, V. Smalyuk, P. Amendt et al., Nature Phys. (<https://doi.org/10.1038/s41567-018-0331-5>).

Work performed under the auspices of U.S. Department of Energy by LLNL under Contract DE-AC52-07NA27344 and supported by LDRD-17-ERD-119

pppo

Presenter: AMENDT, P.A. (EPS 2019)

Session Classification: BPIF

Track Classification: BPIF