



Contribution ID: 52

Type: **Oral Contribution**

Design and construction of the mechanical structure for thin-gap RPC triplets for the upgrade of the ATLAS muon spectrometer

Wednesday, 12 February 2020 09:10 (20 minutes)

The advent of thin-gap RPCs with 1 mm gas gaps instead of 2 mm in the present RPCs opened the possibility to instrument the inner barrel layer of the ATLAS muon spectrometer where there is very limited amount of space in radial direction from the beam line. The environment is particularly dense in the barrel end-cap transition region. A compact mechanical structure coping with the expected thickness variations of the assembled RPCs is needed to fit into the limited available space. At the same time the mechanical structure must be sufficiently rigid to keep the deformations of the RPC packages within the allowed envelopes. The tight space constraint makes it impossible to achieve the required rigidity with thick paper honeycomb plates as used in the present ATLAS RPCs. For the phase I upgrade of the barrel end-cap transition region of the ATLAS muon spectrometer three 1 mm gap RPCs are put into an aluminium frame. In this frame the RPC triplet is compressed with pre-bent 2-mm thick aluminium plates. The rigidity of the frame is achieved by stiffening rods connecting the lateral structure of the frame. The same concept can be used for the phase II upgrade of the inner layer of the muon spectrometer.

Primary author: KORTNER , Oliver (ATLAS Collaboration)**Presenter:** KORTNER , Oliver (ATLAS Collaboration)**Session Classification:** Large systems and Upgrades