

# The dual Ring Imaging Cherenkov detector for the Electron-Ion Collider

Simone Vallarino

May 10, 2022

EIC\_NET




INFN – Sezione di Ferrara

Università degli Studi di Ferrara

# The Electron-Ion Collider



- Highly polarized electron (~70%) and proton (~70%) beams
- Availability of ion beam from deuterons to heavy nuclei
- $e+p$  center-of-mass energy up to 100 GeV
- High luminosity (up to  $10^{34}$   $\text{cm}^{-2}\text{s}^{-1}$ )




dRICH for EIC

May 10, 2022


# The dRICH at EIC

## Challenges:


- cover wide momentum range 3-60 GeV
- work in high (~1 T) magnetic field




Effective solutions, part of EIC reference detector  
 Radiators: aerogel ( $n_{\text{aero}} \sim 1.02$ ) + gas C<sub>2</sub>F<sub>6</sub> ( $n_{\text{gas}} \sim 1.0008$ )  
 Detector: 0.5 m<sup>2</sup>/sector, 3x3 mm<sup>2</sup> pixel, SiPM option




# The dRICH prototype 2021 test beams




Test	Cherenkov medium	Energy [GeV]	Beam	Photon detector and DAQ
September at SPS	Aerogel	40÷120	$\pi^+$ $\pi^-$	SiPM and ALCOR
October parasitic runs at SPS	Aerogel	120	$\mu^-$ $\pi^-$	MPPC and MAROC
October at PS	Aerogel and Gas ( $C_2F_6$ )	4÷12	$\rho$ and $\pi^+$ $\pi^-$	MAPMT and MAROC




The dRICH setup at PS



SiPM  
dRICH for EIC




MPPC  
May 10, 2022



MAPMT





# The dRICH prototype components



Frontal view



Support




MAPMT detector box

# SiPM study




A study of radiation effects on SiPM and recover by annealing is ongoing. We developed custom carriers for SiPMs of several producers, which can bear the high temperature (up to 170°C) of the annealing process.



Some carriers were irradiated in May at TIFPA (Trento) and in the following months underwent annealing at Bologna and Ferrara



dRICH for EIC



In just one week of annealing the SiPMs recovered one order of magnitude in dark current (or neutron dose).

May 10, 2022








# September tests at SPS

The september test main goal was to implement the readout chain based on ALCOR (with not irradiated SiPMs)

The ALCOR chip and ARCADIA DAQ are INFN developments designed to readout SiPM with precise time resolution (50 ps time binning) and at high rate (up to 500 kHz per channel).

The plot shows the coincidence peak between the SiPM signal of dRICH and the timing and trigger scintillators.



# October test at PS


## Goals:

- To operate the dual RICH by using both aerogel and gas;
- preliminary study the performance of the dRICH.

## Difficulties:

- Sensors came late due to an overlap with another test beam;
- the renovated beam line was not completely commissioned;
- most of the time was parasitic.

Time distribution of hit




Distribution of hit time, the coincidence with the trigger time is clearly visible.

The right plot shows one event measured at PS.

## Legend:


- Little red square, a pixel of the MAPMTs turned on by a photon.
- Red line, edge of MAPMTs.
- Green, geometrical cut applied to distinguish gas (inner) and aerogel (outer) photon.
- Blue, gas and aerogel rings reconstructed.






# dRICH alignment & data corrections

Particle position on upstream GEM




Particle position at aerogel




A tracking system based on two GEM detectors was used during the test beams to track the beam particles for misalignment and beam divergence, The combination of the dRICH optical information and GEM track information allows to correct data on a event by event data.


Particle position on downstream GEM




Particle slope



$\pi^-$  rings before corrections




$\pi^-$  rings




# Preliminary results

Radius of single particle



Radius of ring produced from 12 GeV  $\pi^-$  by crossing the gas

Radius of single particle



Radius of ring produced from 12 GeV  $\pi^-$  by crossing the aerogel


# Result: Gas resolution

Fitting function: 
$$y = \sqrt{\frac{p_0^2}{x} + p_1^2}$$


$p_0$  = single photon resolution  
 $p_1$  = single particle resolution constant term

$p_1$  is not compatible with zero, so there is some residual systematic effect

RMS of radius as function of photon number - Gas




Distribution of the number of photon per particle - Gas




# Simulation: Gas resolution

RMS of radius as function of photon number - Gas - Simulation



Gas	Data	Simulation
$p_0$ [mm]	1.5	1.1
$p_1$ [mm]	0.22	0.07
Avg photon	12.8	11.3

Distribution of the number of photon per particle - Gas - Simulation






# Result: Aerogel resolution

Fitting function: 
$$y = \sqrt{\frac{p_0^2}{x} + p_1^2}$$


$p_0$  = single photon resolution  
 $p_1$  = single particle resolution constant term

$p_1$  is not compatible with zero, so there is some residual systematic effect

RMS of radius as function of photon number - Aerogel




Distribution of the number of photon per particle - Aerogel




# Simulation: Aerogel resolution

RMS of radius as function of photon number - Aerogel - Simulation



Gas	Data	Simulation
$p_0$ [mm]	1.9	0.8
$p_1$ [mm]	0.53	0.26
Avg photon	3.5	3.5

Distribution of the number of photon per particle - Aerogel - Simulation



# Conclusions and future perspectives

- We develop a dRICH prototype and SiPM program to address the challenges of PID at the future EIC.
- We operated the dRICH prototype and all its subsystems, collecting a good set of data to compare with simulations.
- The obtained results are promising, but the expected resolution is not yet achieved.
- A larger amount of data will be acquired in the new test beams in fall 2022, making it possible to carry out systematic studies on the dRICH performance towards the design resolution.
- A new version of the reconstruction and analysis software is under development, which will allow an improved resolution and online monitoring.
- An improvement of the simulations is on going, based on the ongoing optical characterization of the dRICH components.

# The end


Thanks for your attention




# Backup slides

# October parasitic runs at SPS


The MPPC detectors were used.  
Data analysis is ongoing, but the different geometry requires a partially new data analysis which is under development.




### Rings without correction



### Outer mean radius - North and South




### Outer mean radius - Corrected - North and South




# GEMs tracking


Particle position on upstream GEM




Particle position at aerogel



Particle position on downstream GEM




Particle slope



The GEMs provide the track of each event. In this run, only the GEMs and the frontal scintillator were used as trigger. We found a correlation between the semi-difference of the radius measured from two opposite MAPMTs and the particle slope provided by GEMs.

Semi difference of north-south PMT vs Aerogel  $\theta_y$  - Inner ring



# Computing the dRICH alignment

We define the coordinate of the dRICH-optical center as the mean value of the semi-difference between the radius measured in two opposite PMTs, evaluated by using only small angle events ( slope < 1 mRad). This is a dRICH optical property, and the values are the same for each run (unless change on the mirrors orientation).

The coordinates of the single event center are provided by the sum of the optical center and the product of particle slope and length of path inside dRICH.

