

Managed by Fermi Research Alliance, LLC for the U.S. Department of Energy Office of Science

Considerations for Fermilab Multi-MW Proton Facility in the DUNE/LBNF era

S. Nagaitsev, J. Eldred, V. Shiltsev, A. Valishev, R. Zwaska

ICHEP 2022 July 7, 2022

Fermilab at present





Record Booster power 89 kW (8 GeV, 15 Hz)



Fermilab Upcoming Upgrades: PIP-II 1.2MW

Fermilab Accelerator Complex



New SRF linac raises Booster injection energy, new LBNF beamline.

7/7/2022

🛟 Fermilab

PIP-II Linac & Upgrades (1.2 MW power on target)



Project started in 2016 (CD0) First beam in Booster: 2028 (plan) MI 1.2 MW beam on target: 2032 (projection)

800 MeV H- linac

- Warm Front End
- SRF section

Linac-to-Booster transfer line

• 3-way beam split

Upgraded Booster

- 20 Hz, 800 MeV injection
- New injection area

Upgraded Recycler & Main Injector

• RF in both rings

Conventional facilities

- Site preparation
- Cryoplant Building
- Linac Complex
- Booster Connection



PIP-II Booster Power

	PIP	PIP-II
MI Beamline	NuMI	LBNF
RR/MI Intensity	$54 \cdot 10^{12} \text{ protons}$	$65 \cdot 10^{12} \text{ protons}$
RR/MI Rep. Time	$1.333 \mathrm{\ s}$	1.2 s
MI Power	0.7 MW	1.2 MW
Booster Intensity	$4.5 \cdot 10^{12} \text{ protons}$	$6.5 \cdot 10^{12} \text{ protons}$
Booster Rep. Rate	$15 \mathrm{~Hz}$	$20 \mathrm{~Hz}$
Booster Ext. Power	$85 \mathrm{kW}$	$165 \mathrm{kW}$
Injection Energy	$0.4 \mathrm{GeV}$	$0.8 { m GeV}$
Efficiency	95%	98%

The primary purpose of the PIP-II is to inject into the Booster, and in turn power the high-energy proton complex including DUNE/LBNF program.

However, the PIP-II Linac is also designed to be CW-capable and the Booster only uses ~1.2% of the CW beam power!

- Two proposed "near-term" programs are discussed.

🛠 Fermilab

DUNE physics program



- Unambiguous, high precision measurements of Δm_{32}^2 , δ_{CP} , $\sin^2\theta_{23}$, $\sin^22\theta_{13}$ in a single experiment
- Discovery sensitivity to CP violation, mass ordering, θ_{23} octant over a wide range of parameter values
- Sensitivity to MeV-scale neutrinos, such as from a galactic supernova burst
- Low backgrounds for sensitivity to BSM physics including baryon number violation



Proton Intensity Upgrade after PIP-II (construction complete ~2036)



7 S. Nagaitsev | Fermilab Multi-MW proton facility

Fermilab Upcoming Upgrades Future 2.4MW



Booster prevents x2 PIP-II power, injection energy and transition-crossing limits

7/7/2022

🛟 Fermilab

Rapid-Cycling Synchrotron (RCS) Option



8 GeV Linac Option



Upgrade Design History & Process

In 2008, Project X: 8 GeV SRF Linac, directly into Main Injector.

In 2010, Project X ICD-2: 2 GeV Linac, New 2-8 GeV RCS.

In 2018, <u>S. Nagaitsev and V. Lebedev</u>: updated version of ICD-2, DOI: 10.1142/S1793626818001450

In 2019, J. Eldred, V. Lebedev, A. Valishev: parametric study of RCS design.

In 2021, Science Working Group

<u>"Physics Opportunities for the Fermilab Booster Replacement"</u> arXiv:2203.03925

Snowmass whitepapers

- S. Nagaitsev, V. Lebedev , "A Cost-Effective Upgrade Path for the Fermilab Accelerator Complex", arXiv:2111.06932
- R. Ainsworth, J. Dey, J. Eldred, R. Harnik, J. Jarvis, et al. "An Upgrade Path for the Fermilab Accelerator Complex", arXiv:2106.02133
- S. Belomestnykh, M. Checchin, D. Johnson, D. Neuffer, S. Posen, E. Pozdeyev, V. Pronskikh, N. Solyak, V. Yakovlev. "An 8 GeV Linac as the Booster Replacement in the Fermilab Power Upgrade", arXiv:2203.05052

🗖 🛟 Fermilab

Possible experiments in addition to DUNE-Phase II

Experiment	Dark Sectors	V Physics	CLFV	Precision tests	R&D	
Lepton flavor violation: µ-to-e conversion						
Lepton flavor violation: µ decay						Rep
PIP2-BD: ~GeV Proton beam dump						lace
SBN-BD: ~10 GeV Proton beam dump						eme Op
High energy proton fixed target						nt,
Electron missing momentum						202
Nucleon form factor w/ lepton scattering						1 1 Itles
Electron beam dumps						to
Muon Missing Momentum						r the
Muon beam dump						
Physics with muonium						inni
Muon collider R&D and neutrino factory						lab
Rare decays of light mesons						В О С
Ultra-cold neutrons						Oste
Proton storage ring for EDM and axions						۔ ۲
Tau neutrinos						
Proton irradiation facility						
Test-beam facility						
					36.1	ermilab

(electrons)

'Laundry List' of Possible Experiments (RCS Scenario)

2 GeV CW-capable beam, 2mA

- mu2e-II type charged-lepton flavor violation experiment
- Low energy muon experiments (muonium, muon decay)
- REDTOP run-II/run-III program
- neutron-antineutron oscillation experiments
- EDM storage ring (with polarized proton source upgrade)

2 GeV pulsed beam from Storage Ring, ~1 MW

- PIP2-BD stopped pions, GeV-scale dark sector search
- AMF/PRISM charged-lepton flavor violation experiments

8 GeV RCS program, ~1 MW

- SBN-BD kaon decay-at-rest, intermediate energy dark sector search
- any successors to short-baseline neutrino program
- NuSTORM and muon-collider R&D
- proton irradiation facility
- muon beam dump experiment

120 GeV Slow-Extraction program, 8e12 over six second, once per min.

- DarkQuest dark matter spectrometer experiment
- M3 muon missing-momentum experiment
- test beam program

This is everything proposed at Snowmass! Not necessarily planned for Fermilab!

🛠 Fermilab

8-GeV Linac Program (to LBNF/DUNE)

Performance Parameter	PIP	PIP-II	BRL	Unit	
Linac Beam Energy	400	800	8000	MeV	
Linac Beam Current (chopped)	25	2	2	mA	
Linac Pulse Length	0.03	0.54	2.2	ms	Injects at 20Hz
Linac Pulse Repetition Rate	15	20	20	Hz	inte MI ever eix
Linac Upgrade Potential	N/A	CW	CW		into will over Six
8 GeV Protons per Pulse (extracted)	4.2	6.5	27.5	10 ¹²	2.2ms pulses
8 GeV Pulse Repetition Rate	15	20	20	Hz	•
Beam Power @ 8 GeV	80	166	700	kW	
8 GeV Beam Power to MI	50	83-142*	176-300	kW	
Beam Power to 8 GeV Program (pulsed mode)	30	83-24*	500-375	kW	
Main Injector Protons per Pulse (extracted)	4.9	7.5	15.6	10 ¹³	
Main Injector Cycle Time @ 120 GeV	1.33	1.2	1.2	S	
Main Injector Cycle Time @ 60 GeV	N/A	0.7	0.7	S	
Beam Power @ 60 GeV	N/A	1	2.15	MW	
Beam Power @ 120 GeV	0.7	1.2	2.5	MW	

*Total PIP-II with Booster 8 GeV power is 166 kW.

Section	Length	Bending field or RF frequency	Total bending angle or Linac mode	Cavities/magnets/ cryomodules	Cryomodule length
1 GeV transport	40 m	0 277 T	-45°	ci yomounes	iength
$1 \rightarrow 3 \text{ GeV Line}$	240 m	650 MHz	CW	120/20/20	0 02 m
	240 m		ew	120/20/20	9.92 111
3 GeV bend	200 m	0.13 T	105°		
$3 \rightarrow 8 \text{ GeV Linac}$	390 m	1300 MHz	Pulsed, 10 Hz	224/28/28	12.5 m
8 GeV injection		0.055 T			

7/7/2022

‡Fermilab

8-GeV Linac Program (8-GeV experiments)

Performance Parameter	PIP	PIP-II	BRL	Unit	
Linac Beam Energy	400	800	8000	MeV	
Linac Beam Current (chopped)	25	2	2	mA	
Linac Pulse Length	0.03	0.54	2.2	ms	
Linac Pulse Repetition Rate	15	20	20	Hz	
Linac Upgrade Potential	N/A	CW	CW		
8 GeV Protons per Pulse (extracted)	4.2	6.5	27.5	10 ¹²	
8 GeV Pulse Repetition Rate	15	20	20	Hz	0 (
Beam Power @ 8 GeV	80	166	700	kW	0-0
8 GeV Beam Power to MI	50	83-142*	176-300	kW	2µ
Beam Power to 8 GeV Program (pulsed mode)	30	83-24*	500-375	kW	
Main Injector Protons per Pulse (extracted)	4.9	7.5	15.6	10 ¹³	
Main Injector Cycle Time @ 120 GeV	1.33	1.2	1.2	S	
Main Injector Cycle Time @ 60 GeV	N/A	0.7	0.7	S	
Beam Power @ 60 GeV	N/A	1	2.15	MW	
Beam Power @ 120 GeV	0.7	1.2	2.5	MW	

-GeV pulsed us -> 2ms

‡ Fermilab

*Total PIP-II with Booster 8 GeV power is 166 kW.

Section	Length	Bending field or	Total bending angle	Cavities/magnets/	Cryomodule
		RF frequency	or Linac mode	cryomodules	length
1 GeV transport	40 m	0.277 T	-45°		
$1 \rightarrow 3 \text{ GeV Linac}$	240 m	650 MHz	CW	120/20/20	9.92 m
3 GeV bend	200 m	0.13 T	105°		
3 → 8 GeV Linac	390 m	1300 MHz	Pulsed, 10 Hz	224/28/28	12.5 m
8 GeV injection		0.055 T			

15 S. Nagaitsev | Fermilab Multi-MW proton facility

RCS Scenarios

"Design Considerations for Fermilab Multi-MW Proton Facility" white paper

Parameter	PIP-II Booster	ICD-2	BSR
Linac Energy	$0.8 { m GeV}$	$2 \mathrm{GeV}$	2 GeV
Minimum Linac Current	2 mA	2 mA	2 mA
GeV-scale Accumulator Ring	Optional	Optional	Required
RCS Energy	8 GeV	8 GeV	8 GeV
RCS Intensity	6.5 e12	26 e12	37 e12
RCS Circumference	474.2 m	553.2 m	570 m
RCS Rep. Rate	20 Hz	10 Hz	20 Hz
Number of Batches	12	6	5
Accumulation Technique	Slip-stacking	Conventional	Conventional
8 GeV Accumulation	Recycler	Recycler	Main Injector
Available RCS Power	80 kW	170 kW	750 kW
Main Injector Intensity	80 e12	156 e12	185 e12
Main Injector Cycle Time	1.2 s	1.2 s	1.4 s
Main Injector Power (120 GeV)	$1.2 \ \mathrm{MW}$	2.4 MW	2.4 MW



RCS Scenarios (ramp rate and 8 GeV program)

"Design Considerations for Fermilab Multi-MW Proton Facility" white paper

Parameter	PIP-II Booster	ICD-2	BSR
Linac Energy	$0.8 { m GeV}$	$2 \mathrm{GeV}$	2 GeV
Minimum Linac Current	2 mA	2 mA	2 mA
GeV-scale Accumulator Ring	Optional	Optional	Required
RCS Energy	8 GeV	8 GeV	8 GeV
RCS Intensity	6.5 e12	26 e12	37 e12
RCS Circumference	474.2 m	$553.2 \mathrm{~m}$	570 m
RCS Rep. Rate	20 Hz	10 Hz	20 Hz
Number of Batches	12	6	5
Accumulation Technique	Slip-stacking	Conventional	Conventional
8 GeV Accumulation	Recycler	Recycler	Main Injector
Available RCS Power	80 kW	170 kW	750 kW
Main Injector Intensity	80 e12	156 e12	185 e12
Main Injector Cycle Time	1.2 s	1.2 s	1.4 s
Main Injector Power (120 GeV)	1.2 MW	$2.4 \mathrm{MW}$	2.4 MW

ICD-2 RCS is more cost-effective, BSR is more ambitious

BSR delivers more for 8 GeV, compatible with a second LBNF target station

🛟 Fermilab



RCS Scenarios (required rings)

"Design Considerations for Fermilab Multi-MW Proton Facility" white paper

Parameter	PIP-II Booster	ICD-2	BSR
Linac Energy	$0.8 { m GeV}$	2 GeV	2 GeV
Minimum Linac Current	2 mA	2 mA	2 mA
GeV-scale Accumulator Ring	Optional	Optional	Required
RCS Energy	8 GeV	$8 { m GeV}$	8 GeV
RCS Intensity	6.5 e12	26 e12	37 e12
RCS Circumference	474.2 m	553.2 m	570 m
RCS Rep. Rate	20 Hz	10 Hz	20 Hz
Number of Batches	12	6	5
Accumulation Technique	Slip-stacking	Conventional	Conventional
8 GeV Accumulation	Recycler	Recycler	Main Injector
Available RCS Power	80 kW	170 kW	750 kW
Main Injector Intensity	80 e12	156 e12	185 e12
Main Injector Cycle Time	1.2 s	1.2 s	1.4 s
Main Injector Power (120 GeV)	1.2 MW	$2.4 \mathrm{MW}$	2.4 MW

ICD-2 scenario require Recycler (or similar), maintains RR experimental program.

🛟 Fermilab

7/7/2022

BSR scenario requires either an Accumulator Ring or 5 mA linac upgrade.

"Design Considerations for Fermilab Multi-MW Proton Facility" white paper

Parameter	PIP-II Booster	Staging?	ICD-2	BSR
Linac Energy	$0.8 \mathrm{GeV}$	$\sim 1.6 { m GeV}$	$2 \mathrm{GeV}$	2 GeV
Minimum Linac Current	2 mA	2 mA	2 mA	2 mA
GeV-scale Accumulator Ring	Optional	Optional	Optional	Required
RCS Energy	8 GeV	8 GeV	8 GeV	8 GeV
RCS Intensity	$6.5 \ e12$	$\sim 20 \text{ e}12$	26 e12	37 e12
RCS Circumference	474.2 m	$\sim 550~{\rm m}$	$553.2 \mathrm{~m}$	570 m
RCS Rep. Rate	20 Hz	10 Hz	10 Hz	20 Hz
Number of Batches	12	6	6	5
Accumulation Technique	Slip-stacking	Conventional	Conventional	Conventional
8 GeV Accumulation	Recycler	Recycler	Recycler	Main Injector
Available RCS Power	80 kW	$\sim 60 \text{ kW}$	170 kW	750 kW
Main Injector Intensity	80 e12	116 e12	156 e12	185 e12
Main Injector Cycle Time	1.2 s	1.2 s	1.2 s	1.4 s
Main Injector Power (120 GeV)	1.2 MW	1.8 MW	$2.4 \mathrm{MW}$	2.4 MW

Possible Staging with 1.8 MW, smaller Linac upgrade, PIP-II era Main Injector RF. Optionally, could be designed to be upgradeable to either of 2.4 MW scenario.

🚰 Fermilab

Summary

PIP-II upgrade, massive potential for GeV-scale experimental program

- Proposed ~100kW mu2e-II program.
- Proposed ~100kW PAR / dark sector program
- A lot of other ideas are out there muons, neutrons, polarized protons.

Longterm planning for a subsequent Proton Intensity Upgrade.

- Engaging Snowmass and the wider physics community.
- Robust planning helps make wise decisions, maintain flexibility.
 ICD-2 RCS: Well-developed proposal, focused on 2.4 MW for LBNF.
 BSR RCS: More challenging injection/linac, much more 8-GeV power.
 8-Gev Linac: R&D for 8-GeV injection, potential for high CW power.

What will be the **future 0.8-2 GeV** experimental program?

- power, beam structure, timeline.

What will be the **future 8 GeV** experimental program?

- power, beam structure, timeline.
- future role of Recycler Ring and Delivery Ring.

Fermilab