

WIFAI 2024

Workshop Italiano sulla
Fisica ad Alta intensità


Bologna 12-15 Novembre 2024
Palazzo Hercolani, Aula Poeti
Str. Maggiore, 45 - Bologna

THE CGEM INNER TRACKER OF BESIII

G. CIBINETTO (INFN FERRARA)
on behalf of the CGEM-IT group

Outline of the talk


- * The BESIII experiment and its upgrade program
- * The Cylindrical GEM Inner Tracker (CGEM-IT)
- * Simulation studies and expected performance
- * Status of the project
- * Summary and outlook



THE BESIII EXPERIMENT AND ITS UPGRADE PROGRAM


The BESIII experiment @ BEPCII

- $E_{CM} = 2 - 4.95 \text{ GeV}$
- $\mathcal{L}_{peak} = 1.0 \times 10^{33} \text{ cm}^{-2}\text{s}^{-1}$
- Center-of-mass energy spanning the τ -charm sector
- Region below 2 GeV directly accessible (via ISR)
- World's largest sample of
 - $J/\psi \rightarrow 10$ billions
 - $\psi(2S) \rightarrow 3$ billions
 - $\psi(3770) \rightarrow 20 \text{ fb}^{-1}$
- About 22 fb^{-1} of data for Exotic Charmonium Spectroscopy




The BESIII experiment @ BEPCII

- $E_{CM} = 2 - 4.95 \text{ GeV}$
- $\mathcal{L}_{peak} = 1.0 \times 10^{33} \text{ cm}^{-2}\text{s}^{-1}$
- Center-of-mass energy spanning the τ -charm sector
- Region below 2 GeV directly accessible (via ISR)
- World's largest sample of
 - $J/\psi \rightarrow 10 \text{ billions}$
 - $\psi(2S) \rightarrow 3 \text{ billions}$
 - $\psi(3770) \rightarrow 20 \text{ fb}^{-1}$
- About 22 fb^{-1} of data for Exotic Charmonium Spectroscopy



The BESIII upgrade program: physics



$$* e^+e^- \rightarrow \Sigma_c \bar{\Lambda}_c \pi$$

$$* e^+e^- \rightarrow \Sigma_c \bar{\Sigma}_c$$



$$* e^+e^- \rightarrow \Lambda_c^+ \bar{\Lambda}_c^- \text{ and } e^+e^- \rightarrow \Xi_c \bar{\Xi}_c$$

- * Upgrade of the C.M. energy to 4.95 GeV, then up to 5.6 GeV
- * Measurements of the cross sections near threshold to provide insight of the vacuum productions of $c\bar{c}$ and $s\bar{s}$ pairs
- * Study the EM structure of charmed baryons
- * Studies of the absolute BFs of Σ_c and Ξ_c

Competitive with BELLE2

more at arXiv:1912.05983v3

The BESIII upgrade program: machine




- * BEPCII upgrade aims at increasing luminosity by a factor of 3 & increasing beam energy to 2.8 GeV
- * Key technologies: double beam power & optics upgrade & new high gradient of magnets



The BESIII upgrade program: detector

- * MDC performs tracking, momentum and dE/dx measurement for charged particle identification
- * Inner and Outer MDC are two separate chambers sharing the same gas volume




- * The increasing of the luminosity is speeding up the aging of the **Inner Tracker**

NIM A Volume 1063, June 2024, 169276

The Cylindrical GEM Inner Tracker


- * 3 layers of cylindrical triple-GEM detectors to replace the inner MDC
- * Improve rate capability, aging and secondary vertex reconstruction
- * While retaining the current momentum and tracking performance ($\sigma_p/p \sim 0.5\% @ 1 \text{ GeV}$)
- * Main System Requirements
 - * Angular coverage: 93%
 - * Low material budget ($\sim 0.5\%$ of X_0 per layer $\rightarrow 1.5\%$ of X_0 in total)
 - * High azimuthal spatial resolution $\rightarrow 130\text{-}150 \mu\text{m}$ with charge and time readout
 - * Substantial improvements in **rad hard** and **secondary vertex** reconstruction ($\sim 300 \mu\text{m}$ in z)



Detector design

Designed to provide mechanical robustness with relatively low material budget

- * Anode strip pitch 650 micron
- * Gas mixture: Ar/Isobutane 90/10
- * Large drift gap for microTPC




Cathode



3 GEMs



Anode




Space and time resolutions defined by optimization of the mechanical design, electronics and operating parameters

more at <https://www.mdpi.com/2073-8994/14/5/905>

Electronics design


more at JINST 16 P08065

- * 64 channels, up to 60 kHz/ch rates
- * ENC noise below 2000 e⁻ rms for strip capacitance < 100pF Max. strip C ~300 pF
- * Analog charge measurement up to 50 fC
- * Possibility to extend the dynamic range with Time-over-Threshold
- * T and Q branch of every channel
- * 12 mW/ch power
- * SEU tolerant digital part




Tested also on microRWELL

CGEM-IT system implementation




more at JINST 16 P08065

SIMULATION STUDIES AND EXPECTED PERFORMANCE




Track finding

- * Global method with Hough Transform
- * The procedure includes two steps:
 - * Circle finding
 - * V-view hits association






- * Both steps use Hough transform to get track candidates and initial track parameters
- * A global fitting with Least-Square method is done after each step



X-view hits: DC axial wire hits and CGEM X-clusters


V-view hits : DC stereo wire hits and CGEM V-clusters

Expected performance




- * No difference between different multiplicities
- * CGEM XY resolutions slightly worse at low p_t
- * CGEM Z resolution much better
- * Momentum resolution worse only at very low p_t

Tracking efficiency with CGEM



- Particle type and momentum dependent
- Worse for low p_T proton as expected
- Comparable in most p_T

Impact on vertex reconstruction



- * Expected impact on vertex reconstruction
- * Better separation for complex topologies and improvements on secondary vertexes, both crucial for charmed baryon decays

$\Sigma_c(2455)$ DECAY MODES


$\Lambda_c^+ \pi$ is the only strong decay allowed to a Σ_c having this mass.

Mode	Fraction (Γ_i/Γ)
$\Gamma_1 \quad \Lambda_c^+ \pi$	$\approx 100\%$

Ω_c^0 DECAY MODES


No absolute branching fractions have been measured. The following are branching ratios relative to $\Omega^- \pi^+$.

Mode	Fraction (Γ_i/Γ)	Confidence level
$\Gamma_1 \quad \Omega^- \pi^+$	Cabibbo-favored ($S = -3$) decays — relative to $\Omega^- \pi^+$ DEFINED AS 1	




decay topology example

Track finding in a local approach



- * To keep high efficiency for tracks from displaced vertex the assumption (or constraint) of tracks from origin should not be used
- * Track finding with a local method usually use some local constraints to get track seeds (or segments) and then to associate more hits (or combine segments) to get complete track candidates.

- * So track finding with a local approach should be also efficient for tracks from displaced vertex
- * A Track Following (TF) method by selecting adjacent DC hits is implemented





K_S sample
generated with
 $p=0\sim 2$ GeV/c and
all decay to $\pi^+\pi^-$







STATUS OF THE PROJECT

Detector staging

- * Standalone commissioning with cosmics before installation
- * Continuous running for operations and performance evaluation




Noise distributions



Detector operations

Detector currents

layer 1






layer 2







layer 3



Charge per strip distribution




Performance evaluation with cosmics




Alignment and residuals

- * Provides geometry corrections (rotation, offset, ...)
- * Method: track fitting with these corrections as global parameters, which are obtained iteratively using the tool Millepede
- * 5 global parameters for each of the outer layers (relative to the inner layer)


3D event display



Residual comparison





χ^2 comparison




χ^2 distribution is improved significantly after alignment !

Detector performance





- * Double-view efficiency above 95% for all layers
- * HV segmentation clearly visible in the φ view
- * Residual distributions for almost orthogonal tracks $< 200 \mu m$ including contribution from tracking



$r\varphi$ residuals for track with azimuthal incident angles between 0° and 5°

Detector digitization

- * Digitization is the simulation of detector response
- * Processes in digitization of CGEM-IT




- * Ionization --> Heed in Garfield++
- * Drift & avalanche --> parameterized model based on Garfield++ simulation results
- * Induction --> Digitization from Garfield++ simulation results
- * Electronics measurement --> transfer function of TIGER


more at JINST 18 P05027 and
CPC 295 (2024) 109000 (arXiv:2005.04452)

Digitization tuning with cosmic data



- * Data from cosmic runs
 - * 2D cluster reconstruction with c.c. method
 - * Straight line fit
- * Simulation with GEANT4 and CGEM-IT simulation package
- * Consistency between data and MC is good after tuning
- * Paper published: JINST 18 P05027



more at JINST 18 P05027




INSTALLATION AND COMMISSIONING OF THE DETECTOR



DETECTOR INSTALLATION

CGEM-IT REACHING ITS NOMINAL POSITION ON OCTOBER 5, 2024



DETECTOR CABLING

COMPLETED ON OCTOBER 18 - DETECTOR POWERED ON AT NOMINAL VALUES ON OCTOBER 19

Integration and commissioning

- * Installation of the EM shielding in progress
- * Next to do
 - * The endcaps of the EM calorimeter will be placed to their nominal position
 - * Installation of the beam pipe
 - * Installation of the final focus
- * First data acquired in standalone for debugging purpose
- * The integration with BESIII DAQ and Slow Control is in progress

Summary and outlook

- * BESIII is planning to continue taking data up to (at least) 2030 with higher luminosity and higher CM energy
- * The Cylindrical GEM Inner Tracker has been designed to improve rate capability and secondary vertex reconstruction
- * The detector has just been installed and is currently being integrated with the BESIII spectrometer
- * Still quite some time before having some collider data to analyze but the fun part is about to begin



TO BE FILLED
WITH DATA





THANKS FOR YOUR ATTENTION


Energy	Physics motivations	Current data	Expected final data	T_C / T_U
1.8 - 2.0 GeV	R values Nucleon cross-sections	N/A	0.1 fb^{-1} (fine scan)	60/50 days
2.0 - 3.1 GeV	R values Cross-sections	Fine scan (20 energy points)	Complete scan (additional points)	250/180 days
J/ψ peak	Light hadron & Glueball J/ψ decays	3.2 fb^{-1} (10 billion)	3.2 fb^{-1} (10 billion)	N/A
$\psi(3686)$ peak	Light hadron & Glueball Charmonium decays	0.67 fb^{-1} (0.45 billion)	4.5 fb^{-1} (3.0 billion)	150/90 days
$\psi(3770)$ peak	D^0/D^\pm decays	2.9 fb^{-1}	20.0 fb^{-1}	610/360 days
3.8 - 4.6 GeV	R values XYZ /Open charm	Fine scan (105 energy points)	No requirement	N/A
4.180 GeV	D_s decay XYZ /Open charm	3.2 fb^{-1}	6 fb^{-1}	140/50 days
4.0 - 4.6 GeV	XYZ /Open charm Higher charmonia cross-sections	16.0 fb^{-1} at different \sqrt{s}	30 fb^{-1} at different \sqrt{s}	770/310 days
4.6 - 4.9 GeV	Charmed baryon/ XYZ cross-sections	0.56 fb^{-1} at 4.6 GeV	15 fb^{-1} at different \sqrt{s}	1490/600 days
4.74 GeV	$\Sigma_c^+ \bar{\Lambda}_c^-$ cross-section	N/A	1.0 fb^{-1}	100/40 days
4.91 GeV	$\Sigma_c \bar{\Sigma}_c$ cross-section	N/A	1.0 fb^{-1}	120/50 days
4.95 GeV	Ξ_c decays	N/A	1.0 fb^{-1}	130/50 days

	KLOE-2	BESIII	action
Number of detector layers	4	3	→ 5 mm drift gap
Drift gap	3 mm	5 mm	for mTPC
Material budget per layer	0.5% X ₀	0.5% X ₀	
Momentum resolution @ 1 GeV	not used	$\sigma_{pt}/P_t \approx 0.5\%$	
Rate capability	< 10 kHz/cm ²	few 10 kHz/cm ²	
Spatial resolution f	250-350 mm (B=0.5T)	100-150 mm (B=1T)	mTPC
Spatial resolution Z	~1 mm	<500 mm	mTPC
Magnetic field	B = 0.52 T	B = 1 T	mTPC
Internal/external diameter	244/440 mm	156/356 mm	higher rate
Readout	digital	charge + time	TIGER chip

R&D and detector design



- * Combining CC and microTPC stable spatial resolution over a large range of incident angle
- * Possibility to perform 3D track reconstruction with only one layer
- * A large (5 mm) drift gap is needed for the microTPC readout



Performance evaluation with cosmics

