













NEFERTARI project: a network of Research Infrastructures for Magnetic Confinement Fusion Research



DIAGNOSTICS FOR FUSION REACTORS: THE BURNING PLASMA ERA
VIIIa Monastero, Varenna, Italy

Simone Peruzzo

Research Infrastructure Manager CNR-ISTP & Consorzio RFX

on behalf of the NEFERTARI project Team













Nefertari Meritmut 13th century BC Egyptian queen "The one for whom the sun shines"



New Equipment for Fusion Experimental Research and Technological Advancement with Rfx Infrastructure

• Funding institution: Italian Ministry of University and Research



• Framework program: National Recovery and Resilience Plan



• Objective: Strengthening of high priority Research Infrastructures

Project aim: Innovation of experimental equipment and diagnostic systems for

PEX and diagnostic systems for the property of DTT LTER. DEMO.

RFX-mod2 and linked laboratories, in support of DTT, ITER, DEMO

• Allocated funds: 18 M€ (70% dedicated to hardware investment)

(27 new positions: 19 researchers, 8 PhD)

• Duration: 30 months (2022 – 2025)

Partnership:
 Consiglio Nazionale


delle Ricerche





Nefertari










ICFRD2025, Varenna, Italy September 1 - 5, 2025







Distribution of experimental facilities enhanced or newly realized with NEFERTARI























RFX experiment at a glance:

• 1992 - 99: **RFX**

experimental phases 2004 - 16: RFX-mod

• 2018 - 23: modification of the vessel complex

• 2023 - 25: new experimental plants & diagnostics

• 2026 - ...: **RFX-mod2**

✓ High Priority Research Infrastructure included in the Italian «Research Infrastructure National Plan 2021-27» - ENERGY sector (ESFRI)

 PNRR-NEFERTARI investment: 10 M€

• pre-existing investment:

110 M€







Neutral Beam Test Facility

Funded in the framework of international agreements ITER – F4E – MUR up to 2030 (in prospect up to 2040)







, Varenna, Italy







ICFRD2025, Varenna, Italy

September 1 - 5, 2025







Nefertari

Involved Operating Units

NEFERTARI project - Work Packages	CI	NR-IST	Р	UniPD	Uı	niNA
(1) RFX-mod2 <u>Technological Plants</u>	Pd			CRF	DII	
(2) Electromagnetic measurements and feedback control in fusion devices	Pd			CRF		DIETI
(3) Innovative <u>diagnostics for edge fusion plasmas</u>	Pd					
(4) Enhancement of RFX-mod2 main plasma diagnostics	Pd		CRF			
(5) Neutral beams injectors in RFX-mod2	Pd					
(6) <u>Laboratory of High Voltage insulation</u> in fusion devices				CRF		
(7) Laboratory for the study of fusion relevant high-density plasmas and materials interaction		Mi				
(8) Laboratory for innovative diagnostics for imaging of soft X-rays and neutrons	Mi		Mi			
(9) Research and Development of optical plasma diagnostics and modelling for fusion		Ва				


















- ✓ new RH system for RFX-mod2 first wall maintenance
- Self-consistent Training Facility @Napoli
- Main system @Padova



Vacuum and Gas Injection System

- Glow & Pulsed Discharge Cleaning Systems
- Remote Handling system for first wall maintenance

Main procurements:

- Robotic arm (serial robot with 7 DoF)
- 1:1 vessel complex mockup (30°)
- RH robot Control systems
- Server for RH Virtual Reality and accessories






BECKHOFF New Automation Technology

Project update:


- ✓ Factory Acceptance Tests in progress
- Commissioning by Oct 2025





ref.: G.A. Fontanelli, et al., Fusion Engineering and Design 206 (2024) 114586 https://doi.org/10.1016/j.fusengdes.2024.114586




















√ Complete refurbishment of:


- In-Vessel Electro-Magnetic sensors
- signal acquisition and preprocessing system



Layout of new in-vessel sensors (tot. n. 2216):

- 1736 magnetic
- 480 electrical


- Development and prototyping of machine protection and plasma control software
- EMC laboratory (new anechoic chamber for em compatibility tests < 18GHz)
- EM sensors and acquisition systems for plasma control and machine protection






Modular system

- 20 bit ADC 1 MSample/s
- · 250 kHz analog bandwidth.
- Galvanic isolation < 2.5 kV AC rms
- · Numerical signal integration in FPGA - 10 sec
- Based on Xilinx Zyng 7020 architecture





- ✓ derived from RFX-mod experience
- ✓ proposed for DTT with minor adaptations





Project update:

- ✓ Acceptance Tests completed
- installation on RFX-mod2 planned by Dec 2025

ref.: R. Cavazzana, et al., SOFE 2025, https://plasmafusion.eventsair.com/sofe2025, submitted to IEEE Transactions on Plasma Science



Politecnica ceroi














(3) plasma edge diagnostics for RFX-mod2

- ✓ New manipulator for rapid insertion in the plasma edge region of electro-magnetic probes for detection of plasma parameters (n, T, V, B)
- reflectometric system for real time plasma position control (proposed also for DTT and DEMO)
- light impurity tomography (LIT)
- spectroscopic diagnostics system based on the use of polychromator (MANTIS)
- movable system of probes with FAst Reciprocating Manipulator (FARM)



(ins / dwell / ext)

Reciprocating probe head Higher 5-pin triple probe Mach probes at four different radial positions External case (Boron Nitride) Internal frame (stainless steel) 50 mm

Technical solutions:

✓ Used also on W7X



✓ Ready for installation



Main procurements:

- Manipulator
- Probe heads
- Power supply & data acquisition system

ref.: P. Agostinetti, et al., SOFE 2025, https://plasmafusion.eventsair.com/sofe2025, submitted to IEEE Transactions on Plasma Science





ICFRD2025, Varenna, Italy September 1 - 5, 2025 T.E.E.S.













(4) Enhancement of RFX-mod2 main plasma diagnostics: • Soft X Rays and bolometry tomography

Requirement	Specification	
Wavelength	1064 nm	
Pulse Energy	4 J per pulse	
Operation mode	Single shot, 0.3, 1, 2, 3 kHz	
Pulse Duration (FWHM)	10 ns	
Max pulse-to-pulse jitter	< 100 ns	
1 st pulse-trigger jitter	10 μs	
Trigger delay	10 μs	
Beam Divergence	≤ 0.5 µrad (full angle)	
Pointing Stability	≤ 50 μrad	
Burst Operation	≥ 10 pulses per burst	

OS Nd-YAG lase

Innolas Nd-YAG

SLHy-VIII laser

Compact Neutral Particle Analyzer

• Thomson Scattering for radial Te and ne profiles measurement

Scattered light detectors

new Nd:Yag laser 0.3 ÷ 3 Khz coupled to existing 4Joule 100 Hz LOS Nd:Yag laser

Main procurements:

- Laser
- Manipulator and support structure
- Acquisition system
- **Optical** components







Laser input window

> Manipulator for dump/mirror installation without breaking vacuum

Beam dump or mirror

Project update:

- Site Acceptance Tests of laser accomplished 2025
 - installation on RFX-mod2 planned for 2026

ref.: L. Carraro, et al., Nucl. Fusion 64 (2024) 076032 https://doi.org/10.1088/1741-4326/ad490a

Nefertari














in collaboration with:



(5) Neutral beams injectors in RFX-mod2: Complete refurbishment of the 50 keV, 100 kW Diagnostic Neutral Beam Injector (DNBI) for core measurements of Ti, ion flow, impurity content, \vec{B}



Main activities and procurements:





Redesign of High Voltage Deck and related power units and control system



Replacement of open-cycle **cryopumps** with closed-cycle ones



- Redesign of DNBI-RFX-mod2 duct to reduce beam losses
- New **spectrometer** and **EMCCD cameras** for
 - CHarge Exchange Recombination Spectroscopy (CHERS)
 - Motional Stark Effect (MSE) polarimetry




Project update:

- ✓ Acceptance Tests of spectrometer and cameras accomplished 2025
- Completion of electrical and vacuum components planned by Dec 2025

ref.: M. Barbisan, et al., Fusion Engineering and Design 220 (2025) 115320 https://doi.org/10.1016/j.fusengdes.2025.115320



















(6) Laboratory of High Voltage insulation in fusion devices

• Refurbishment and upgrade of the facilities of the High Voltage Padova Test Facility (HVPTF)

ICFRD2025, Varenna, Italy September 1 - 5, 2025

Facility of the HVPTF for the study of pressurized gas insulation in high voltage systems

This conference:

Study of in-vacuum discharges with X-rays at the High Voltage Padova Test Facility

Speaker: Federico Caruggi

3 Sept 2025, **16:15**

















(7) Laboratory for the study of fusion relevant high-density plasmas and materials interaction

			_	
	GyM	BiGyM		
Plasma density [m -³]	10 ¹⁵ - 10 ¹⁷	10 ¹⁸ - 10 ¹⁹	ALLY	
d r 2 13	1021	10 ²² – 10 ²³		
Ion flux [m -² s -¹]	ITER first-wall relevant	ITER divertor relevant		
Source type	2 Magnetrons	2 RF birdcage antennas		
Total power [kW]	4.5	20	New sample	Sample temperature up to 1500 K
13.56 MHz Dirdcage antennas Helicon wave plasma			exposure system	High-resolution monochromator $\lambda = 200 - 1000 \text{ nm}$ $\Delta \lambda = 0.06 \text{ nm}$
	dura • Max	second pulse tion energy per e > 50 mJ	1/2	nduced breakdown ctroscopy (LIBS)

✓ Upgrading linear plasma device GyM to BiGyM:

- BiGyM helicon wave plasma sources
- BiGyM sample exposure system
- Upgrade of BiGyM diagnostic system











Project update:

- ✓ procurements almost completed
- Commissioning planned by end 2025

ref.: A. Uccello, et al., Front. Phys. 11, 1108175 (2023) https://doi.org/10.3389/fphy.2023.1108175

ICFRD2025, Varenna, Italy September 1 - 5, 2025















(8) Laboratory for innovative diagnostics for imaging of soft X-rays and neutrons:

- Realization of a Detector Assembly Unit (DAU)
- Test Irradiation Area
- Realization of an advanced X-ray imaging diagnostic for high time and space resolution of RFX-mod2
- Realization of a multiple lines of sight system with spectroscopic information for imaging of neutron

ICFRD2025, Varenna, Italy September 1 - 5, 2025

This conference:

Neutron diagnostics for RFX-mod2

Speaker: Andrea Dal Molin

3 Sept 2025, **15:45**

The GEM soft x-ray diagnostics on RFX-mod2

Speaker: Oscar Putignano

3 Sept 2025, **16:00**


















(9) Research and Development of optical plasma diagnostics:

Laser Induced Breakdown Spectroscopy (LIBS)

Main procurements:

- 400 fs-10 ps laser for LIBS
- Spectrograph for high-speed LIBS spectroscopy
- Vacuum chamber with 2-cathode reflex discharge
- Optical microscope and profilometer



Optical Spectroscopy: emission (OES) and laser (LIF)

Main procurements:

- 4 ns tunable OPO laser for LIF spectroscopy
- 30 ps tunable OPO laser for kinetic studies by laser spectroscopy
- Spectrograph with, 500 ps minimum gate for optical spectroscopy
- 8-cathode reflex discharge systems







Project update:


✓ Acceptance Tests of instrumentation accomplished 2025

> Set up of a new laboratory space (civil works and technical systems) almost completed



ref.: S.F. Cipelli, et al., 2025, submitted to Journal of Nuclear Materials

Nefertori



O OPTOPRIM















Time schedule for RFXmod2 restart and forthcoming experimental phase



>10 years of operation
(obligation due to NRRP funding)

	20	25	20	26	2027-2036
NEFERTARI project (RFX-mod2 new plant & diagnostics)					
Re-installation of RFX-mod2					
Commissioning					
Experimental Phase					
Further investments (*)					

(*)

Italian Nuclear Research Plan





Research and Development of technologies for innovative and sustainable nuclear power















Take-home message:

✓ NEFERTARI = great opportunity of investment in

equipment human resources

Ready for scientific exploitation with present or prospective stakeholders





