


NUSDAF 2025 - 1st Collaboration Meeting on NUclear Structure, Dynamics and Astrophysics at FRIB













SYnergic Strategy for fuTure ElectRonics and Streaming rEadout solutions

SYSTERSE: an overview

M.Battaglieri (INFN-GE), M.Bondì (INFN-CT)



















From signals to physics



DAQ chain








Signals in HEP and NP physics: analog vs. digital

Particle

- Position: x, y, z
- Momentum: px, py, pz
- Energy: $E^2 = (M^2 + p_x^2 + p_y^2 + p_z^2)$
- Electric charge




Detector

- Position
- Time
- Energy

HEP/NP detector

- **★** Interaction TIME
- **★** Interaction POSITION
- **★** Deposited ENERGY


Analog



- "OVERSHOOT"
 "RINGING"
 "TILT"

 UNDERSHOOT
- ★ The Front End Electronics (FEE) produces analog signals. The information is coded into the signal shape
- PROS
 - coded info: height, length, shape ...
- CONS
 - distortions imply a loss

Digital



- ★ Coding the info in a conventional 'pulse' provides a simpler and effective manipulation of signals
- PROS
 - distortion is not an issue
- CONS
 - coding requires a more complex elaboration and (often) a loss of information






Signals in HEP and NP physics: analog vs. digital

Particle

- Position: x, y, z
- Momentum: px, py, pz
- Energy: $E^2 = (M^2 + p_x^2 + p_y^2 + p_z^2)$
- Electric charge




Detector


- Position
- Time
- Energy

HEP/NP detector

- **★** Interaction TIME
- **★** Interaction POSITION
- ★ Deposited ENERGY



- ★ Full waveform contains information about the shape of the signal
- * Modern digitizers sample the waveform at a high rate and high definition (bits)



- **★** Interaction ENERGY ⇔ Q
- **★** Interaction TIME ⇔ Threshold

Digitizers provide 'numbers' at the front end SRO DAQ leverages modern FEE & data manipulation





Triggered DAQ


Traditional (triggered) DAQ

Traditional triggered

* (few) trigger Channels participating send (partial) information to trigger logic

trigger condition is satisfied:

· a new 'event' is defined




* All channels continuously measured, hits stored in short term memory

Traditional triggered DAQ

- Pros
- we know it works reliably!
- Drawbacks:
- · only few information forms the trigger
- Trigger logic (FPGA) difficult to implement and debug
- not easy to change and adapt to different conditions

Trigger logic

- ★ decides if/when to collect detector information
- ★ Select 'events' over 'background'
- ★ Save data on disk for further processing
- ★ Different levels
 - LI: threshold on FEE
 - L2: combine information from different sub-detect components
 - L3: requires info processing





Streaming RO

Streaming read out (SRO)


Streaming

* A HIT MANAGER receives hits

from FEE, order them and ship

to the software defined trigger

- * Software defined trigger re-aligns in time the whole detector hits applying a selection algorithm to the time-slice
 - the concept of 'event' is lost
 - time-stamp is provided by a synchronous common clock distributed to each FEE



* All channels continuously measured and hits streamed to a HIT manager (minimal local processing) with a time-stamp

SRO DAQ

- Pros
 - All channels can be part of the trigger
 - · Sophisticated tagging/filtering algorithms
 - · high-level programming languages
 - scalability
- Drawbacks:
- we do not have the same experience as for TRIGGERED DAQ

Why SRO is so important?

- * High luminosity experiments
 - Write out the full DAQ bandwidth
 - Reduce stored data size in a smart way (reducing time for off-line processing)
- * Shifting data tagging/filtering from the front-end (hw) to the back-end (sw)
 - Optimize real-time rare/exclusive channel selection
 - Use of high-level programming languages
 - Use of existing/ad-hoc CPU/GPU farms
 - Use of available AI/ML tools
 - (future) use of quantum-computing
- * Scaling
 - Easier to add new detectors in the DAQ pipeline
 - Easier to scale
 - Easier to upgrade


Many NP and HEP experiments adopt a SRO DAQ

- CERN: LHCb, ALICE, AMBER
- FAIR: CBM
- DESY:TPEX
- FRIBS: GRETA
- BNL: sPHENIX
- JLAB: SOLID, BDX, CLAS12, ...






Streaming RO



- FEE optimised for SRO
 - ASICS (cheap) or fADC (multiplexing) at (O(\$10/ch)
 - TDC if necessary to replace fADC
 - Zero-suppression mode
 - Fast readout (optical link)
- Signal pre-processing with fast hw (dedicated FPGA)
 - de-multiplexing fADC info
 - Charge, time, amplitude
 - Data compression
 - Data monitoring
 - Add other information (e.g. ch_ID eTimeStamp)
- CPU/GPU/TPU sub-detector analysis (single stream)
 - Local clusters, track segments, PID, ...
 - Time-frame building
 - If necessary only store high-level data dumping raw
- TF-Router Time frame construction
 - Use time stamps to reorganise data from all streams in time frames



• Full reconstruction CPU analysis (for each time frame)

Data center

Subtle border between hard-wired and software data processing



Al-supported algorithms for SRO

Real Time data analysis

- In the SRO scheme, data analysis is performed online [this does not prevent to save unbiased frames for further analysis!]
- A sw trigger is released based on real-time data analysis
- SRO and real-time data processing shall use Al:
 - to adapt data analysis to the changed conditions of the run (e.g. thresholds)
 - to identify data features in real-time (e.g.clusters)
 - to extract calibration constants from a data sub-set
 - to define algorithms to run (fast!) in real time on heterogeneous systems (e.g. CPU+GPU+FPGA)

Partial Real-Time data reconstruction: clustering

- Look at all detector information (hit: x, y, t, E) to learn correlations: clusters of objects share common features
- Define a metric in a space and identify cluster features
- Tests on minimum bias trigger data before real-time
- Hyperparameters optimization based on data

Fast inference

- Fast algorithms to extract data features to be used in data selections (and reduction)
- Mimicking a smart 'trigger'
- provide partial reconstructed quantity quickly

Calibration

- Use smart algorithms to extract data features and correct detector parameters varying over time
- toward a self-calibrating detector

Data reduction


• reduce data volume to a manageable level with minimum bias





SYnergic Strategy for fuTure ElectRonics and Streaming rEadout solutions

SYSTERSE



Common development of:

- Front end electronics (FEE)
 - ASICs for gaseous detector RO (APV25,VMM3, SALSA)
 - Data Concentrators (FELIX)
- Streaming readout framework
 - Prototyping
 - Off/on-beam tests
- Distributed Real-Time data analysis
 - ESNET
 - HPC nodes (CNAF, CINECA, HPDF)
- Collaborations
 - CERN
 - Japan: SPADI Alliance (JPARC, RIKEN, RIBF)
 - Germany: PRISMA clusters (GSI/FAIR, Mainz, Bonn)
- Training and education
 - Fast electronics, DAQ systems
 - Al on FPGAs, distributed HPC




















SYnergic Strategy for fuTure ElectRonics and Streaming rEadout solutions

SYSTERSE



Common development of:

- Front end electronics (FEE)
 - ASICs for gaseous detector RO (APV25, VMM3, SALSA)
- Giordano's Data Concentrators (FELIX)
 - Streaming readout framework
 - Prototyping
 - Off/on-beam tests
 - Distributed Real-Time data analysis
 - ESNET
 - HPC nodes (CNAF, CINECA, HPDF)
 - Collaborations
 - CERN
 - Japan: SPADI Alliance (JPARC, RIKEN, RIBF)
 - Germany: PRISMA clusters (GSI/FAIR, Mainz, Bonn)
 rand Salta Meach
 - - Fast electronics, DAQ systems
 - Al on FPGAs, distributed HPC




















Jefferson Lab









- *Primary Beam: Electrons
- * Beam Energy: 12 GeV
 10 > λ > 0.1 fm

 - nucleon → quark transition
 - baryon and meson excited states
- *100% Duty Factor (cw) Beam
 - coincidence experiments
 - Four simultaneous beams
 - Independent E and I

- * Polarization
 - spin degrees of freedom
 - weak neutral currents

Luminosity $> 10^7 - 10^8 \times SLAC$ at the time of the original DIS experiments!











DAQ in Hall-B: CLAS and CLAS 12





CLAS (1997-2012) TRIGGERED system limited by:

- Available technology
- Low latency (~100ns) defined by FASTBUS ADCs
- Level-I trigger: calorimeter/TOF/Cherenkov/StartCounter/Tagger (time coincidence of 'fast' detectors discriminators)
- Level-2 trigger: drift chamber (no tracking, just multiplicity)
- Hardware: since 1997: JLAB-made; since 2008: CAEN v1495's (Cyclone I first experience with FPGAs)



CLAS12 (2017 - present) TRIGGERED system improved by:

- Advanced FPGA technology
- high latency (~8 us) defined by fADCs
- Level 1 trigger: clusters in 3 calorimeters and hodoscope (FADC pulse integrals) + hits in 2 TOFs and 2 Cherenkovs (FADC pulse integrals) + tracks in Drift Chamber (discriminators/TDCs)
- Hardware: JLAB-made VTP (VXS Trigger Processor) boards (Virtex7 FPGA)
- Trigger algorithms: energy, position, and timing of the clusters in calorimeters; energy, position, and timing of TOFs and Cherenkov hits + drift chamber track finding (dictionary-based) + timing and position matching between clusters, hits and track

Credit: Sergey Boiarinov






Streaming RO at Jlab: the proof of principle



M.Battaglieri - INFN



FrontEnd

D.Abbott, F.Ameli, C.Cuevas, P. Musico, B.Raydo

* JLab fADC250 + VTP bord

- JLab 250 MHz flash ADC digitizer currently used in many experiments
- Overcome VXS limitations (<24 Gb/s) using JLab VTP board (<40 Gb/s)
- Not optimised but reuse of existing boards: ready-to-go solution while waiting for fADC250.v2



SRO concept validation

- I) Assemble SRO components
- 2) Test SRO DAQ in lab
- 3) Test SRO DAQ on-beam

Jana2 + reconstruction

N.Brei, D.Lawrence, M.Bondi', A.Celentano, C.Fanelli, S.Vallarino


* JANA2 + TriDAS

- Integration between On-line and off-line
- Real-time tagging/filtering data
- Offline algorithm development immediately available for use in Software Trigger
- Level I"minimum-bias": at least one crystal with E> 2 GeV
- Level 2 plugins (tagging and filtering)
- "standard" FT-CAL clustering (N_{cluster}≥1, 2, 3)
- cosmic tracking
- Al clustering algorithm: at least two cluster in the FT-CAL

BackEnd

L.Cappelli, T.Chiarusi, F.Giacomini, C.Pellegrino

- * TRIggerless Data Acquisition System (TriDAS)
 - Developed for KM_3NET
 - Installed on Hall-B DAQ cluster
 - Multi CPUs, rate up to 20-30 MHz



Cebaf Online Data Acquisition (CODA)

D.Abbott, S.Boyarinov, B.Raydo, G.Heyes

- Originally designed for trigger-based readout systems
- Controllers (ROCs) and VXS Trigger Boards (VTPs)
- TheTrigger Supervisor (TS) synchronizes components using clock, sync, trigger and busy signals.-time tagging/filtering data
- CODA adapeted to the SRO
- Replaced EB to use timestamp)
- ROC communication via VTP (not VXS bus)






13

Streaming RO at Jlab: pioneering tests

Streaming Readout for Next Generation Electron Scattering Experiments https://link.springer.com/article/10.1140/epjp/s13360-022-03146-z



SRO concept validation

- I) Assemble SRO components
- 2) Test SRO DAQ in lab
- 3) Test SRO DAQ on-beam

Nuclear Physics » A Trial Run for Smart Streaming Readouts



Scientists tested streaming readout systems during nuclear physics experiments that collected data in Jefferson Experimental Halls B and D.


The Science

Nuclear physics experiments are data intensive. Particle accelerators probe collisions of subatomic particles such as protons, neutrons, and quarks to reveal details of the bits that make up matter. Instruments that measure the particles in these experiments generate torrents o raw data. To get a better handle on the data, nuclear physicists are turning to artificial intelligence and machine learning methods. Recent tests of two streaming readout systems that use such methods found that the systems were able to perform real-time processing of raw experimental data. The tests also demonstrated that each system performed well in comparison with traditional systems.

JLab SRO validation

* CLASI2 Forward Tagger

- Complete system that include calorimetry, PiD, Traking in a simpler (than CLASI2) set up
- FT-ECAL: 332 PbWO crystals, APD readout
- FT-HODO: 224 plastic scintillator tiles, SiPM readout
- FT-TRK: ~3000 channels, MicroMegas
- fADC250 digitizers + DREAMs for MM



The FT in CLAS I 2

*CLASI2 Forward Tagger


- Inclusive pi0 electroproduction
- Two gammas detected into FT-CAL
- EM clusters identification, anti coincidence with FT-Hc
- Self-calibration reaction (pi0 mass)

On-beam tests:


10.4 GeV e- beam on thin Pb/Al target

Inclusive pi0 production

e + Pb/Al -> Xeπ⁰ -> (X)eγγ



target




X - not detected





Streaming RO at Jlab: pioneering tests






• Two pi0 peaks corresponding to two vertices (and a wrong assumption on the vertex position)






Al to analyze data in real time, and extract features (e.g. number of peaks and position)

- Al clustering inspired by Hierarchical Density-Based
 Spatial Clustering of Applications with Noise (HDBSCAN)
 - It is not cut-based
 - o it is able to cope with a large number of hits
- Compared γγ-invariant mass spectrum obtained utilizing both the standard and the HDBSCAN clustering algorithm
 - \circ Al significantly improves signal-to-background ratio in the $\pi 0$ region
 - A longer runtime of ~30% relative to the standard clustering algorithm
- Al clustering approach promising alternative to traditional cut-based approaches









Streaming RO in Hall-B




Credit: Sergey Boiarinov

CLASI2 (Future)


Streaming ReadOut

- Alternative use of the VXS Trigger Processor (VTP) board
- Up to 4×10 Gbit/s
- More than 50 crates (VME/VXS) can be reused



Status of SRO in Hall-B

- VTP firmware updates
- Beam tests with local resources (Hall-B counting house)
- Tests with remote resources (Computer Center) using Arista smart switch
- Planned test to stream ~half CLASI2 data to CC
- Final goal (~5y): x2-3 CLASI2 Luminosity (~50GB/s)








Streaming RO at Jlab: the current effort






• Integration of different components in an optimised SRO framework


ERSAP

- Reactive, event-driven data-stream processing framework that implements micro-services architecture
- Provides basic stream handling services (stream aggregators, stream splitters, etc.)
- Adopts design choices and lessons learned from TRIDAS, JANA, CODA and CLARA


ERSAP: Environment for Real-time Streaming, Acquisition, and Processing Framework



Development of SRO DAQ pipeline tools



• Development of JLAB CLAS 12 Remote data-stream processing over a distance



Inaugural demonstration of remote data-stream workflow deployment and processing over a distance

- Captured CLAS12 data, streamed across the Jlab campus using a 100Gbps high-speed NIC featuring hardware timestamps
- Captured data using synchronized streams from multiple network sources


Credit: Vardan Gyurjyan & Ayan Roy






JLab SRO R&D: networking and data transfer





• Re-utilize the existing data transfer infrastructures developed at Jefferson Lab



Networking test for JLab SRO framework just started






JLab SRO R&D: GEANT simulations



Credit: Maurizio Ungaro



GEMC: solving the geant4 event-centric framework GRunAction handles creation, filling and flushing (GStreaming) GFrameDataCollection 1 geant4 event is (for example) 1 µs long time **GEMC Streaming Hits** • Hits from a geant4 event can end on different buffers (propagation time, etc) slot 2 • Pile-ups are intrinsic in hit 1, hit 2, hit 3, hit 1, hit 2, hit 3, this scenario

Continuous DATA Stream

GOAL: Having simulated data stream on network indistinguishable from real data

Define and address challenges on hardware, communications and


software issues

Streaming Simulations Scope

• Development of a MC GEANT-based toolkit to implement SRO in detector simulations

Frame Buffer 31 Frame Buffer 32 Frame Buffer 33

- Transform event-based to stream-based G4 logic
- Develop libraries share same on-line data format
- Emulate TCP output to feed to ERSAP
- Milestone Nov 2021, FT Calorimeter streaming








Maurizio Ungaro


EIC @ Brookhaven National Lab (BNL)






 $\eta = 0$ $\theta = 90^{\circ}$

Barrel



- spanning a wide kinematical range
 - ECM: 20 141 GeV
- High luminosity
 - up to 10³⁴ cm⁻² s⁻¹
- highly polarized e (~ 70%) beams
- highly polarized light A (~70%) beams
- wide variety of ions: from H to U
- Number of interaction regions: up to 2










 $\eta = 4 \\ \theta = 2^{\circ}$

EIC @ Brookhaven National Lab (BNL)











SRO@ePIC



Compute-Detector Integration to Maximize and Accelerate Science

- Maximize Science Capture every collision signal, including background.
 - Event selection using all available detector data for holistic reconstruction:
 - Eliminate trigger bias and provide accurate estimation of uncertainties during event selection.
 - Streaming background estimates ideal to reduce background and related systematic uncertainties.
- Accelerate Science Rapid turnaround of 2-3 weeks for data for physics analyses.
 - Timeline driven by alignment and calibration.
 - · Preliminary information from DSCs indicates that 2-3 weeks are realistic.
- Technologies Compute-detector integration using:


Streaming readout for continuous data flow of the full detector information. Al for autonomous alignment and calibration as well as autonomous validation for rapid processing.

computing for acceleration (CPU, GPU).

ePI


ePIC Collaboration Meeting, January 20, 2025.

11



Why SRO is important for ePIC?

- * Expedite ePIC Science outcome
 - Computing/detector integration for a rapid turnaround
- * SRO breaks barriers between DAQ and computing
 - Data collected at Echelon0 and processed at BNL and JLab
 - Important role of Echelon2 and Echelon3








22

ePIC Streaming Computing






- Rates at ePICS not comparable to LHC HI-LUMI but the advantages of SRO remain:
 - multiple channels to trigger on
 - Holy Graal: to manage (storage) an unbiased (un-triggered) data set for further analysis
 - on/off-line event selection with full detector information





ePIC Streaming Computing








Key components: FE aggregator





Data Aggregation Module (DAM)

Computing

Common

Large FPGA / SoC COTS

High Level Trigger Data Reduction Processing

Data Reduction

Data Reduction

Data Reduction

Global Timing Unit (GTU)

Interfaces to Collider

Run Control & DAM

Config & Control

Clock & Timing

Echelon 1 Computing

(BNL)

(JLAB)

Common

COTS

DAM Board - FLX-155

- FELIX (Front-End Link Exchange) hardware for future ATLAS experiments at HL-LHC is being developed at BNL (Omega Group)
- First boards under evaluation at BNL by Omega group





Key components: data reduction



General Principles

- I. Don't remove any information unless required by throughput / storage requirements
- 2. If any information is removed, write out a fraction of data without removing the information (in conjunction with the reduced data)
- 3. Any filtering / data reduction code needs to be documented and available for access by the collaboration


Non-destructive reduction techniques:

- Compression (Standard or ML techniques)
- Reduction of ASIC data inefficiencies
- Aggregation of headers


Techniques that drop information:

- (I-d) cluster finding for ADC data
- (2-d) cluster finding
- Feature finding
- High Level Noise Rejection

- Averages / Histograms
- Simple Analysis
- Arbitrary Deadtime



• Real-time data processing using an autoencoder to compress the digitised waveform








Key components: data reduction






Test Setup at INFN-Genova

- Sample signals from JLAB-CLAS12 detector (similar to PbWO ECal crystal + PMT signals)
- fADC 250MHz, I6bits, discrite
- dedicated (heterogeneous) hardware for data reduction
- GPU:Tesla VI00
- FPGA: Alveo V70
- CPU: Dell C6400

Results

Best performance achieved with a CPU-based server





SRO: training and education










STREAM-AI Streaming Readout Educational Assistant for modern AI DAQ

Two-channels SRO DAQ demonstrator


- CsI(TI) crystals, I0 MHz 12 bit digitizer, Raspberry, Al-data reduction, Frame routing, high level data analysis
- Full SRO DAQ pipeline e functionality (at low rates)
- Signals and data flow visible at each step

Data

reduction




Real-time data rate (L0, L1, Time-coincidence)




Credit: Stefano Grazzi, Fabio Rossi





Data reduction performance





FEE Data

reduction Fr

router D

Data analysis & storage





Detector

Detecto

SRO: training and education










Two-channels SRO DAQ demonstrator

- CsI(TI) crystaFull SRO DAC
- Signals and da
- FEE: digitized dat



Data reduction

SNRI 2025

24 Nov 2025, 08:30 → 28 Nov 2025, 18:30 Europe/Rome


Claudia Gemme (Istituto Nazionale di Fisica Nucleare), Marco Ripani (Istituto Nazionale di Fisica Nucleare), Monica Sisti (Istituto Nazionale di Fisica Nucleare)

The VIII National Seminar on Innovative detectors (SNRI-VIII) is an INFN Educational Program for researchers and technologists aiming at improving awareness and knowledge on the "state of the art" in novel detection techniques. The course will investigate current limits and future developments as well as various related aspects such as simulation, signal acquisition, tracking, particle identification, and much more. Although intended for INFN personnel, the course is also opened to a limited number of external participants, so-called "auditors". SNRI-VIII is organized by INFN Genova and will be hosted by the Physics Department.


While filling the registration form the applicants will be prompted to upload a short CV. Please have the file ready in advance. The applicants will receive notification about their acceptance by October 17th.


The Seminar is part of the INFN Educational Program for the INFN personnel; nevertheless a limited number of external auditors is welcome.






e data rate (L0, L1, incidence)







storage

Credit: Fabio Rossi







Summary and Outlook

- Modern technologies (high rate digitisers, ASICs, FPGAs) are changing g the DAQ paradigm
- Streaming RO is needed for high-luminosity experiments to explore increasingly rare reactions
- Streaming RO is 'THE' option for future electron beam experiments running at high luminosity (JLab, EIC, ...)
- Take advantage of the full detector's information for optimal (smart) tagging/filtering
- Pioneering SRO chain (FE + SRO sw + ON-LINE REC) tested with existing hardware at Jefferson Lab
- Deployment of JLab SRO framework based on micro-services architecture (ERSAP)
- Development of ancillary components such as G4 MC (GEMC3), real-time calibrations, ...
- Developing solutions applicable to ePIC eperiment at the future Electron Ion Collider
- SYSTERSE promotes synergies between low/medium energy NP/HEP experiments leveraging existing tools
- Built a working SRO prototype and a work team!

Many thanks to the whole SRO team:

D.Abbott (JLab), F.Ameli (INFN), MB (JLab/INFN), V.Berdnikov (CUA), S.Boyarinov (JLab) M.Bondí (INFN), N.Brei (JLab), L.Cappelli (INFN) A.Celentano (INFN), T.Chiarusi (INFN), C.Cuevas (JLab), R. De Vita (INFN), M.Diefenthaler (JLab), J. Landgraf (BNL), W. Gu (JLab), C.Fanelli (MIT), R. Fang (ODU), A. Farhat (ODU), S.Furletov (JLab), F.Giacomini (INFN), V.Gyurjyan(JLab), W.Gu (JLab), G.Heyes (JLab), T.Horn (CUA), J.Huang (BNL), E. Jastrzembski (JLab), D.Lawrence (JLab), L.Marsicano (INFN), X.Mei (JLab), P.Moran (MIT), P.Musico (INFN), C.Pellegrino (INFN), E. Pooser (JLab), B.Raydo (JLab), F.Rossi (INFN), H. Szumila-Vance (JLab), C.Trimmer (JLab), M.Ungaro (JLab), S.Vallarino (INFN), J-Y Tsai (JLab), Y. Xu (ODU).



