



KM3NeT: power distribution and control for a star-like sea-floor network

R. Cocimano

for KM3NeT PPM work package H

KM3NeT General Meeting 20-23 February 2012, Catania




Talk Outline

- KM3NeT Seabed Star-like Network for a building block:
 - Input Data and Main Components
 - Electro-Optical Cable Specifications
 - Power System and Calculation Results
- Primary and Secondary Junction Boxes: Block Diagrams & Power scheme
- Medium Voltage Converter
- KM3NeT - IT



Star Detector Layout: Main Components




Main figures:

- 104 Detection Units
- 8 DUs per Secondary Junction Box
- 13 Secondary Junction Boxes
- 1 Associated Science Node (ASN)
- 1 Primary Junction Box



Star Detector Layout: Power System



✓ ON SHORE :

◆ Power Feeding Equipment (PFE) :

- delivers power to the submarine apparatus
- Voltage Converter: 400Vac 3 phase / 10 kVdc

✓ OFF SHORE :

◆ Main Electro Optical Cable (MEOC):

- transmits power and communication

◆ Primary Junction Box (PJB):

- steps down the voltage from 10 kVdc to 400 Vdc
- distribute power and communication to the secondary nodes

✓ OFF SHORE :

◆ Secondary Junction Boxes (SJB):

- distribute power and communication to 8 DUs

◆ Cables (HEOC & IL):

- connects electro-optically the PJB to the SJB and each JB to 8 DUs



Star-like Network Layout: Power System

✓ **DC POWER NETWORK:**


- ♦ **Transmission** Power System (from the shore station to the PJB) : **DC monopolar @ 10 kV**
 - the MEOC copper conductor is energized at -10 KV
 - positive electrode on shore
 - negative electrode off-shore
- ♦ **Distribution** Power System (from the PJB to the DU) : **DC bipolar @ 400 V**

POWER INVENTORY for a BUILDING BLOCK (104 DUs)

COMPONENT	POWER / COMPONENT	POWER/ BUILDING BLOCK
DU local control	360 W	37,44 kW
SJB internal load	100 W	1,3 kW
PJB internal load	300 W	0,3 kW
Associated Science	10 kW	10 kW
		49,04 kW

Star Detector Layout: cable specifications

CABLE	ROUTE	LENGHT	COPPER WIRES	QTY	QTY/km
MEOC MAIN ELECTRO OPTICAL CABLE	shore - PJB	100 km	1 copper conductor 1,5 Ω /km	1	100 km
HEOC HORIZONTAL ELECTRO OPTICAL CABLE	PJB - SJB	1000-2000 m	2 x 16 mm ²	14	20 km
IL INTERLINK CABLE	SJB - DU	100-350 m	2 x 16 mm ²	104	25 km
VEOC VERTICAL ELECTRO OPTICAL CABLE	DU backbone (2 VEOC per DU)	880 m	2 x 18 AWG	208	200 km




Alcatel-Lucent

exans


Draka

HEOC & IL



exans


VEOC



NIKHEF




Star-like Network Layout: Calculation Results



POWER BUDGET	
Power per DU	360 W
DUs total power	37,4 kW
Associated Science (EMSO)	10 kW
HEOC+IL Joule losses (~6%)	3 kW
Internal loads PJB+SJBs	1,6 kW
MVC joule losses ($\eta = 85\%$)	9,2 kW
MEOC losses	6,2 kW
TOTAL POWER LOSSES	27%
POWER ON SHORE	67,4 kW




Primary Junction Box: block scheme




R. Cocimano INFN-LNS for WPH - KM3NeT General Meeting, 20-23 February 2012, Catania

Secondary Junction Box: block scheme






PJB - Power System Box



R. Cocimano INFN-LNS for WPH - KM3NeT General Meeting, 20-23 February 2012, Catania



SJB - Power System Box



R. Cocimano INFN-LNS for WPH - KM3NeT General Meeting, 20-23 February 2012, Catania

Medium Voltage Converter:

Alcatel produced a 10 kW, 10kV / 400 V Medium Voltage Converter for submarine application for two projects :

- NEMO: 2 pieces, 1 deployed and working
- NEPTUNE: 6 pieces, 5 deployed and working

As per Alcatel communication they have discontinued MVC product line.

The Alcatel MVC main features:

DC Input Voltage : 5,7kV - 10 kV

DC Output Voltage: 375 V

Power: 10 kW

Input shut down voltage: 5,2 kV

Efficiency @ 10 kV, full load : 87%

Voltage undershoot (10% to 90% step up) @ 10kV: 40 V

Voltage overshoot (90% to 10% step down) @ 10kV: 43 V

Output Ripple Voltage (rms @ 100 kHz) < 1,5 V





Medium Voltage Converter

An activity of market inquiry finalized to find a new supplier it is on going.

Companies contacted:

✓ PBF, OceanWorks, Bruker, Heinzinger, L-3 MariPro


- **PFB** is a power supply producer, it is interested and It did a feasibility study of a 10 kW/400V
- **OceanWorks** worked for NEPTUNE and VENUS (Node) and has an experience with subsea cabled network. It is "interested in the development of a 10 kW - 10kV/400V solution in a single stage with firm fixed price and performance guarantees".
- **L-3 MariPro** has experience with subsea cabled network, worked for NEPTUNE. It is working for the Regional Scale Nodes (RSN) of the Ocean Observatories Initiative (OOI). It is producing seven MVC, 10 kW unit (10kV/375V) for the RSN.

KM3NeT-IT: Network Capacity

Present Status


PFE: 50 kW
MVC: 10 kW (85% eff.)
MEOC: 20 optical fibers

DU power: 360 W
JB power: 200 W
Cable Joule losses: 4%



20 DUs

(DU number only limited by MVC)



MVC upgrade to remove power limitation


PFE: 50 kW
MVC: 2 x 10 kW (85% eff.)
MEOC: 20 optical fibers

DU power: 360 W
JB power: 200 W
Cable Joule losses: 4%



32 DUs

(DU number limited by fibers
2 DUs per readout fiber)



DU power increase scenario


PFE: 50 kW
MVC: 2 x 10 kW (85% eff.)
MEOC: 20 optical fibers

DU power: 450 W
JB power: 200 W
Cable Joule losses: 10%



32 DUs

(DU number limited by MVC
and by fibers:
2 DUs per readout fiber)



Improved fiber capacity scenario
(50 % - 3 DUs per readout fiber)

PFE: 50 kW
MVC: 3 x 10 kW (85% eff.)
MEOC: 20 optical fibers


DU power: 450 W
JB power: 200 W
Cable Joule losses: 10%



48 DUs




KM3NeT-IT: Seabed Network



Main figures:

- 32 Detection Units
- 8 DU per Secondary Junction Box
- 4 Secondary Junction Boxes
- 1 Primary Junction Box

KM3NeT-IT: Calculation Results



POWER BUDGET	
Power per DU	360 W
DUs total power	11,52 kW
HEOC+IL Joule losses (~4%)	0,5 kW
Internal loads PJB+SJBs	1 kW
MVC joule losses ($\eta = 85\%$)	2,3 kW
MEOC losses	0,4 kW
TOTAL POWER LOSSES	27%
POWER ON SHORE	15,7 kW



Conclusions

- Achievements:
 - Preliminary power inventory and power calculation results
 - Preliminary design of power distribution and its slow control data routing
 - Cables specifications - defined
 - Contacts with cable suppliers (Alcatel, Nexans, Draka, JDR) and cable terminations - on going
 - MVC specification - defined
 - Contacts with MVC development companies - on going

As soon as the final DU power inventory will be available

- Next Steps:
 - Network final power consumption,
 - Network final power distribution design (included cables and electrical connectors)
 - MVC procurement



Thank you for your attention

R. Cocimano, for KM3NeT Consortium - VLVnTII 12-14 October 2011, Erlangen