


GravNet A Global Network for the Search of High Frequency Gravitational Waves



- 3 high frequency RF cavities per site
- One RF cavity at 100 MHz
- Multi-mode readout










SUPAX





Goal: Extend the network to more sites and technologies (BAW, Levitated Sensors ...)





FLASH

FLASH Collaboration

Bylaws of the FLASH Collaboration

September 2025

Contents

1	Ger	eneral considerations			
	1.1	The FLASH Collaboration			
	1.2 The GravNet Collaboration				
	1.3 Participation in the FLASH Project				
	1.4	Participation in GravNet			
	1.5 Organization of the collaboration				
	1.6	Decision-making procedures in the FLASH Collaboration			
	1.7	7 FLASH elections			
	1.8	FLASH documentation			
	1.9 FLASH data				
	1.10 FLASH software				
	1.11 FLASH Prior Inventions and Intellectual Property				
2	FL	ASH Organisation			
	2.1	Institutions			
	2.2	Members			
		2.2.1 Definition, rights and duties of Members			
		2.2.2 List of members			
		2.2.3 Losing the member status			
	2.3	FLASH Authors			
	2.4 Collaboration Board				
		2.4.1 Collaboration Board Institutional Representation			
		2.4.2 Chair of the Collaboration Board			
		2.4.3 Collaboration Board meetings, minutes and reports to the			
		collaboration $\dots \dots \dots$			
	2.5	Technical Board			
	2.6 Spokesperson and Deputy Spokesperson				
	2.7	Technical Manager			
	2.8	Working Groups			

Technical Board F. Bossi (Chair), S. Gazzana (Technical Manager), C. Ligi (Cryogenics), G. Mazzitelli (Computing), C. Gatti (PI)





UNIVERSITY OF LIVERPOOL

























WP1 Physics Reach


(L. Visinelli and F. Mescia)

- The theoretical work currently focuses on:
- Detecting axion mini-clusters with FLASH
- Relativistic axions and DP
- Coupling to HFGW (within GravNet)
- Concerning future applications and detector upgrades:
- Investigating dilaton detection with Bulk Acoustic Wave (BAW) resonators
- Searching for millicharged particles with FLASH

Frascati National Laboratories



Detecting axion miniclusters in FLASH?



Visinelli arxiv:2011.05377

WP2: Cryostat Mechanical Design and Cryogenics (C. Ligi)

- Signed by CERN and LNF a Collaboration Agreement for the cryogenic design of the FLASH experiment.
- A PhD student in engineering from La Sapienza University is now working with the Cryogenic Service at CERN.
- A report on FLASH cryogenics is expected in summer 2026 and the final report on its mechanical design before summer 2027.

ADDENDUM No. KN6519 /TE

to


FRAMEWORK COLLABORATION AGREEMENT KN3083 between THE EUROPEAN ORGANIZATION FOR NUCLEAR RESEARCH (CERN) and THE ISTITUTO NAZIONALE DI FISICA NUCLEARE ("INFN")

concerning

Collaboration in cryogenic design for the FLASH experiment at LNF

BETWEEN: THE EUROPEAN ORGANIZATION FOR NUCLEAR RESEARCH ("CERN"), an Intergovernmental Organization having its seat in Geneva, Switzerland, duly represented by José Miguel Jiménez, Head of Technology Department,

AND: ISTITUTO NAZIONALE DI FISICA NUCLEARE - LABORATORI NAZIONALI DI FRASCATI LNF ("INFN-LNF") established at Frascati, Italy, duly represented by Paola Gianotti, Director of INFN-LNF




Ongoing Work

- Definition of the RF cavity cryostat general layout details
- Cryostat cryo/mechanical design of
 - RF cavity
 - vacuum shield
 - 70 K radiation shield
- Cryogenic turret cryo/mechanical design
- Cryogenic transfer lines design


Carpentry Structure

for the access to the experimental and technical area and for hosting the new cryogenic turret




Credit F. Rosatelli









FINUDA Control System

- Reconstructed the operating diagram for the magnet control and cooling system and the various components involved.
- A new architecture was designed to replace the old control system, the instruments were identified, and the purchase process ongoing.



NI-9375 Digital Input/Output

WP3: RF Cavity


(S. Tocci and A. Diaz)


Electromagnetic design ongoing and proceeding in synergy with mechanical design:

- **Electromagnetic design** is in its final phases. The main parts of the FLASH detector have been defined
- New mechanical designs for the cavity and tuners have been developed and electromagnetically simulated.
- The dimensions and mechanics of the FLASH prototype have been defined and electromagnetic simulations to extract the main parameters have begun

CURRENT STATUS SIMULATIONS ACTIVITY FOR FLASH	STATUS
Simulate the coupling effect between two orthogonal TE modes induced by the loop antenna	In progress
Study capacitive tuning	To be started
Study the effect of mechanical vibrations produced on the antennas (monopole and loop)	In progress
Perform an EM analysis to find the optimal monopole configuration for all TM modes of interest	In progress
Define the exactly position of the loop antenna on cavity end caps	In progress
Develop an algorithm for optimal monopole length	To be started
Calculate the maximum effective tuning sensitivity with optimal β (e.g., $\beta \text{=-}2)$	In progress
Fine tuning with dielectric rod	In progress
Analyze the effect of losses from the mechanical moving parts of the tuners on the Q factor for all modes	To be started


Mechanical Design FLASH cavity and prototype






Credit S. Tomassini

Tuning System



Credit S.Tocci

Mechanical Design: Tuners sliding contacts



Analysis of Mechanical Vibrations

Vibrations, especially from the tuners, degrade the stability of the resonant frequency


- Study the dynamic of the oscillating structures
- Determine the impact on the RF modes
- Determine the damping of oscillations due to the presence of 1.1 T magnetic field




PhD student in engineering in La Sapienza University

Ente finanziatore: ISTITUTO NAZIONALE DI FISICA NUCLEARE (INFN)


<u>Tematica</u>: Dinamica di strutture oscillanti sotto l'azione di campi elettromagnetici e in stato di coazione termica nell'esperimento FLASH ai Laboratori Nazionali di Frascati






Surface Roughness

A Hernandez et al 1986 J. Phys. E: Sci. Instrum. 19 222



For cryogenic copper at 100 MHz we expect a skin depth delta=1 micron (RRR=50 in the CDR) and no less than 0.6 micron (in the anomalous limit for very high RRR).




The target is roughness below 0.4 microns:


- 1) 1 micron mechanical
- 2) 0.5 micron chemical surface treatment


700MHz Prototype

- 4K cryostat (Ligi, lungo, Beatrici, Tocci)
- Cavity mechanical design(Tomassini)
- Manufactoring (Uni Bonn)
- Surface treatment (LNL)

Galactic dark photons as decay products from scalar dark matter










WP4: Signal Amplification and Acquisition

(P. Falferi and G. Lamanna)





PostAmp Gain (200 MHz) ≈ 15 dB

MSA #425-1 Gain (200 MHz) \cong 15 dB MSA #425-1 Bandwidth \cong 80 MHz

Further tests in preparation:


- in B field at Camerino Uni.
 Shielding under study in Liverpool Uni.
- 2. Multiplexing to more SQUIDS in Pisa Uni.

WP5: Data Analysis and Computing

(K. Schmieden and G. Mazzitelli)

GravNet Computing Model

- MIDAS Triumf based **DAQ**; fast (test with QUAX ongoing with 70MB/s on disk) and slow control drivers under development
- online data filtering for axion/HFGW search under study
- local data buffer (3TB NVMe) and metadata (SQL)
- streaming server for online data monitoring, preanalysis and alert on events
- remote storage and tape backend @CNAF with RUCIO data management
- data access and analysis facility (notebooks, batch system, experiment software/CVMFS) open to all the members of the collaboration



WP6: FINUDA Decommissioning and FLASH Commissioning (S. Gazzana)

We found the option of outsourcing the dismantling work to an external company too expensive.


A new disassembly procedure was agreed with the Safety and Protection Service (S. Vescovi).


Some delay in the operations inevitable.


- Refurbishing and certification of the original FINUDA assembly tools.
- Extraction of the FINUDA Clepsydra
- Dismounting of Scintillators and Phototubes

Ongoing activities:

- Maintenance and testing of hydraulic and endcap handling systems.
- Certification of the DAFNE cryogenic plant.







TROLLEY

RAIL SUPPORT

TOWER

3700

MAGNET

EXTRACTION: THE "CLESSIDRA", PULLED BY WINCHES, TRANSLATE FOLLOWING RAILS LEAVING THE MAGNET


2500

RAIL SUPPORT

SHORT TOWER


TROLLEY







QUAX@LNF






New QUAX@LNL results in PRL https://doi.org/10.1103/4dv9-72t5

Improvements in LNF haloscope:

- Quantum limited TWPA amplifier
- Improved cavity tuner
- Calibration Noise source
- Multi-mode acquisition for HFGW
- GPS time acqusition
- New digitizer
- MIDAS DAQ

Technical stop of two months for a leak in the new thermal switch. Sending it back for repairs.



Phys. Rev. D 110, 022008 (2024)

Multi-Mode Detection for HFGW


Acquisition setup for the next QUAX@LNF data take

Mode	Resonant	Q factor	
QUAX@LNF	Frequency [GHz]	(@4°K)	
TM010	8.67	1e5	
TM011	8.69	1e5	
TM012	8.75	1e5	


TM 010 Mode


TM 011 Mode

TM 012 Mode TM 013 Mode





Credit Y. Kim





Daily Modulation






Credit Y. Kim

Coupling to GW from different directions


Characterization of TWPA Amplifier





Rettaroli) in October for the TWPA characterization.




Coherent Oscillations in Weakly Anharmonic NbSe2 Qubit









New NbSe₂ Qubit with large anharmonicity





- Frequency ~10.8 GHz
- Anharmonicity ~400 MHz
- Full Rabi, Ramsey and Echo characterization
- New paper in preparation!




2 Qubits Photon-Counter

The resonant cavity was fabricated at INFN-LNL and the qubits at CNR-IFN (not the final qubit design).

COLD Lab expansion works





In summary

- GravNet Collaboration expanding.
- FLASH Collaboration is taking shape; Collaboration with CERN started; Periodic FLASH meetings; Engineering PhD students from La Sapienza etc.
- WP teams formed and work is progressing.
- Test of FLASH prototype foreseen in summer 2026: investigating the possibility of doing relativistic-DP searches.
- Preparing QUAX@LNF/GravNet multimode run; TWPA amplifier characterized; 2
 months technical stop for a leak in the thermal switch
- Submitted paper on first NbSe2 qubit! New paper in preparation with results on new more anharmonic samples.
- LNL sent the triple cavity for the 2-qubits photon counter. We are now commissioning a foundry to produce the qubits.