MEGII, Mu3e and HiMB status at PSI


Andreas Knecht and Angela Papa PROBES meeting 27-28 November 2025 Pisa, Italy

Content

- Muon physics cases
- Muon beams
- Muon experiments

The role of the low energy precision physics

• The Standard Model of particle physics: A great triumph of the modern physics but not the ultimate theory




 Low energy precision physics: Rare/forbidden decay searches, symmetry tests, precision measurements very sensitive tool for unveiling new physics and probing very high energy scale

Charged lepton flavour violation search: Motivation

- · Neutrino oscillations: Evidence of physics Behind Standard Model (BSM). Neutral lepton flavour violation
- Charged lepton flavour violation: NOT yet observed
- An experimental evidence of cLFV at the current sensitivities will be a clear signature of New Physics








too small to access experimentally

a clear signature of New Physics NP

(SM background FREE)




Content

- Muon physics cases
- Muon beams
- Muon experiments


Muon beams

 Dedicated beam lines for high precision and high sensitive SM test/BSM probe at the world's highest beam intensities, proper (DC or pulsed) time structure, w/o polarization, optimal phase space




- DC beam for coincidence experiments
 - $\mu \rightarrow e \gamma$, $\mu \rightarrow e e e$


- Pulse beam for noncoincidence experiments
 - μ-e conversion



PSI's muon beams





• PSI delivers the most intense continuous (DC) low momentum (surface) muon beam in the world up to few x 10⁸ mu/s (28 MeV/c, polarised beam (**Intensity Frontiers**)



The HiMB (High Intensity Muon Beam) project at PSI

- Aim: O(10¹⁰ muon/s); Surface (positive) muon beam (p = 28 MeV/c); DC beam
 - Target: alternate materials (B₄C and Be₂C show 10-15% gain) and/or geometry (up to 60% of gain: Graphite **Slanted target**)
 - Beam line: high capture efficiency and large phase space acceptance transport channel
- Slanted target test successfully done and installed as "default" target since 2020
 - Increase surface muon rates (30-60% increase depending of the beamline)
 - · Increase safety margin for "missing" target with the proton beam
- PSI Long shut-down: 2027-28. HiMB from end of 2028






Content

- Muon physics cases
- Muon beams
- Muon experiments

The MEGII experiment at PSI


- Best upper limit on the BR ($\mu^+ \rightarrow e^+ \gamma$) set by the MEG experiment (4.2 10-13 @90% C.L.)
- Searching for $\mu^+ \rightarrow e^+ \gamma$ with a sensitivity of $\sim 6 \ 10^{-14}$
- Five observables (E_g, E_e, t_{eg}, 9_{eg}, ϕ_{eg}) to identify $\mu^+ \rightarrow e^+ \gamma$ events




The MEGII experiment at work

After a major upgrade, the MEGII detector started data taking in 2021


Eur. Phys. J. C84 (2024) 190



• Up to 5 x 10^7 stopped μ +




- •LXe 900L (~2.7ton)
- Highly granular
 scintillation readout
 with SiPM(×4092) +
 PMT(×668)



(CDCH)

Radiative decay counter

(RDC)




- ×512 fast plastic scintillator plates
- 40ps time resolution averaged over multiple hits



• ~9000ch waveform readout

- New in MEG II
- BG-γ suppression by identifying associated low mom. positron






- Ultra-low-mass with single gas-volume
- Drift cells with stereo wires

Physics Run: Data collection

- 2021: first physics run with the full detector first result of MEGII published (Eur. Phys. J. C84 (2024) 216)
- · 2022: long and stable run in optimal conditions: discussed in this talk and published recently (Eur. Phys. J. C85 (2025) 1177)
- 2023: largest statistics ever acquired data analysis ongoing
- 2024: ~5 months in standby due to technical problem at PSI
- · 2025: Ongoing since beginning of July



µ⁺ → e⁺ γ Analysis Strategy

•Observables to characterise $\mu^+ \rightarrow e^+ \gamma$ signal

$$t_{e\gamma}, E_{\gamma}, E_{e}, \theta_{e\gamma}, \phi_{e\gamma}$$

Blinding signal region

- Blind box: $48 < E_{\gamma} < 58 \,\mathrm{MeV}, \; |t_{e\gamma}| < 1 \,\mathrm{ns}$
- BG study at sidebands
 - Accidental BG at time sidebands
 - RMD at energy sidebands

ullet Maximum likelihood analysis to estimate $N_{ m sig}$


• Likelihood fit to analysis window:

$$48 < E_{\gamma} < 58 \text{ MeV},52.2 < E_{e} < 53.5 \text{ MeV}$$

$$|t_{e\gamma}| < 0.5 \text{ ns}, |\phi_{e\gamma}| < 40 \text{ mrad}, |\theta_{e\gamma}| < 40 \text{ mrad}$$

Two independent analyses


- ullet Per-event PDFs with two angular observables $heta_{e\gamma}$, $\phi_{e\gamma}$ (\leftarrow reference)
- ullet Constant PDFs with single angular observable $\Theta_{e\gamma}$ (\leftarrow crosschecking)



$$\mathcal{L}(N_{\text{sig}}, N_{\text{RMD}}, N_{\text{ACC}}, x_{\text{T}}) = \frac{e^{-(N_{\text{sig}} + N_{\text{RMD}} + N_{\text{ACC}})}}{N_{\text{obs}}!} C(N_{\text{RMD}}, N_{\text{ACC}}, x_{\text{T}}) \times \prod_{i=1}^{N_{\text{obs}}} (N_{\text{sig}} S(\vec{x_i}) + N_{\text{RMD}} R(\vec{x_i}) + N_{\text{ACC}} A(\vec{x_i})),$$


Detector performance highlights

Positron tracking




- Energy resolution: 90 keV
- $(\leftrightarrow 320\,keV$ @MEG)
- Efficiency: **67** % @ $3 \times 10^7 \mu/s$ ($\leftrightarrow 30$ % @MEG)

Photon energy



- High-granularity and uniform readout by MPPCs
- Energy resolution: 2.0%/1.8% for (conv. depth: <2cm/>2cm)
- Pielup BG reduction by 35% at 48-58MeV (5 imes $10^7 \, \mu/\mathrm{s}$)

Relative timing




• Overall resolution: **84** ps

 $(\leftrightarrow 122 \text{ ps@MEG})$

Significant improvement over MEG


Likelihood fit and result



15

Where we are aiming at...

MEG II expected sensitivity



The beryllium anomaly

• Hint for the production of a neutral, 17 MeV boson, potential mediator of a fifth force: X17 (ATOMKI collaboration) Phys. Rev. Lett. 116, 042501 • Observed in the ⁷Li(p, e+e-)⁸Be reaction at 1030 keV (not at 440 keV) arXiv:2205.07744 • Observed in the ${}^{3}H(p,e+e-){}^{4}He$ and ${}^{11}B(p,e+e-){}^{12}C$ Phys. Rev. C 104, 044003 Q=17.6 MeV Q=18.1 MeV Phys. Rev. D 95, 035017 log(S) [eV barn] **10** 1st excited E_p [MeV] Ground o state Excess consistent with

- Light boson mass = 16.95 MeV/c²
- Branching ratio (X17/gamma) = 6 x 10-6

Collected data sample

• Pivotal run 2022: Proton beam tuning, Mechanical/integration test of the new parts, LiF and LiPON target test, Different trigger settings, Optimised Data Taking and Reconstruction Algorithms

25

- Physics run 2023: 4 weeks producing mainly the 17.6 MeV gamma-line
 - Proton energy at 1080 keV
 - Beam composition: H+ (~75%) and H2+(~25%)
 - Thick LiPON (~7 um)
 - Both 440 keV and 1030 keV excited simultaneously

1 target for 4 weeks, good stability 1 target for 4 weeks, good stability

Gamma rate in BGO per current unit [Hz/µA]


Date and time

- Statistics:
 - ~75 M Events
 - ~500 K Events Reconstructed pairs
- On full range of the Esum and Angular Opening angle observables:
 - ~60% EPC (Dominant at low angle), ~40% IPC (Dominant in the signal region)

Results from the ML fit


Best fit

- Sample of 17.6 MeV [78.4%] and 18.1
 MeV [21.6%]
- 10+-92 signal events at Q = 18.1 MeV for a mX17 = 16.5 MeV, O(100) expected based on ATOMKI
- 0+-68 signal event at Q = 17.6 MeV for a mX17 = 16.5 MeV, O(300) expected based on ATOMKI/Feng et al.
- IPC: **12.6**(9)% Q = 18.1 MeV and **45.8**(13)% Q = 17.6 MeV
- Goodness-of-fit: p-value = 10%



90% Confidence Limits

· Systematic effects (energy scale, resolution, mass dependence, relative acceptance) are all included as nuisance parameters



 $R_{17.6.} < 1.8 \times 10^{-6}$

corresponding to Nsig (17.6) < 200


 $R_{18.1.} < 1.2 \times 10^{-5}$

corresponding to Nsig (18.1) < 230


 MEGII plans to continue X17 data taking during the next HIPA shutdown 2026, Exploiting further the only 1030 keV resonance (assuming NO conflicts with the main MEG data taking)

Axion-like particle (ALP) searches with MEGII

- The muon decay to ALP should just look like a radiative muon decay (RMD)
- It features different topology from MEG decay → 3 body instead of 2 in the final state
 - different trigger selections to maximize signal acceptance
 - low photon energy cut → Eg > 10 MeV
 - no back to back topology
 - need for lower beam rate to keep the trigger under 50 Hz
- Use calibration data taken for a few days with low photon energy (>18MeV) at low beam rate (~106/sec)





Conditional Normalization Function



Axion-like particle (ALP) searches with MEGII

- The muon decay to ALP should just look like a radiative muon decay (RMD)
- It features different topology from MEG decay → 3 body instead of 2 in the final state
 - different trigger selections to maximize signal acceptance
 - low photon energy cut → Eg > 10 MeV
 - no back to back topology
 - need for lower beam rate to keep the trigger under 50
 Hz
- Use calibration data taken for a few days with low photon energy (>18MeV) at low beam rate (~106/sec)
- The ongoing analysis indicates that we can exceed the TWIST limit





The Mu3e experiment at PSI

- The Mu3e experiment aims to search for $\mu^+ \to e^+ e^+ e^-$ with a sensitivity of ~10⁻¹⁵ (Phase I) up to down ~10⁻¹⁶ (Phase II). Previous upper limit BR($\mu^+ \to e^+ e^+ e^-$) $\leq 1 \times 10^{-12}$ @90 C.L. by SINDRUM experiment)
- Observables (E_e, t_e, vertex) to characterize μ→ eee events



Mu3e: Latest news and currents status


Key points:


- First integration Run 2021
- Inner MuPix layer
- SciFi ribbons
- Sub-detector services
- Full beam line commissioning 2022 and fine tuning 2023
- Very successful: TDR promised values matched!
 - 2.49e108 mu/s @2.4 mA (at the collimator): The highest beam rate in pie5 at the collimator
 - 1.02e10⁸ mu/s @2.4 mA (Mu3e magnet): Several beam configurations studied, some of them connected with possible Mu3e magnetic field intensity optimisation

Time line phase I (exploiting current beam-line intensity)

- Engineering run: 2025
- First physics run: 2026


Phase II: It requires 109 mu/s —> HiMB









Full analysis performed on Simulated data




Beam commissioning





The Engineering run: 2025




- First all services have to be installed and tested
- Vertex comes with flex connections installed which connect to the uTP cables
- DAQ fibre optical cables
- · LV, HV, gasus helium system, etc.










General service area




- First all services have to be installed and tested
- Vertex comes with flex connections installed which connect to the uTP cables
- DAQ fibre optical cables
- · LV, HV, gasus helium system, etc.
- Vertex detector installation





- First all services have to be installed and tested
- Vertex comes with flex connections installed which connect to the uTP cables
- DAQ fibre optical cables
- · LV, HV, gasus helium system, etc.
- Vertex detector installation
- Installation of the SciFi detector





- First all services have to be installed and tested
- Vertex comes with flex connections installed which connect to the uTP cables
- DAQ fibre optical cables
- · LV, HV, gasus helium system, etc.
- Vertex detector installation
- Installation of the SciFi detector
- Installation of the Tile detector















- First data
 - Beam intensity 10⁶ mu/s








Towards the Run 2026



Towards the Run 2026

- Single Event Sensitivity Projections for the detector planed in 2026
- Surpass the SINDRUM limit in less than two weeks
- Still a lot of MC studies needs to be performed
- Detector efficiencies has to be studied




Outlook

- Impressive progresses have been done in all MEGII, Mu3e and HiMB
- MEGII released three major physics results (MEG data taking and X17 search)
 and a new one related to the ALPs search will be published soon
- HiMB has been fully approved and started the work into the experimental area in view of the long shutdown 2027-28
- Mu3e achieved the first important milestone of collecting some data with/out beam with part of the apparatus in view of a first physics data taking in 2026

Back up

HV-MAPS

High Voltage Monolithic Active Pixel Sensors (HV-MAPS)



- High Voltage Monolithic Active Pixel Sensors
- Thinned down to 50 μm
- Fast charge collection via drift


- Time resoluton of a few ns
- Digitalization and zero suppression on the chip

good vertex resolution and momentum measurment

Timing detectors


Timing Detectors

Fibre < 250 ps time resolution



- 128 fibres per ribbon
- 3 layers of fibres
- Readout via SiPMs arrays

Tiles < 70 ps time resolution



- $6.3 \times 6.2 \times 5.0 \text{ mm}^3$ tiles
- 4 x 4 tiles per matrix
- One SiPM per tile

good time resolution