


NEMO AND KM3NET

Carla Distefano – INFN, LNS

The giant-scale detector KM3NeT

2

Faintness of neutrino fluxes and small interaction probabilities oblige to use large natural target such as sea-water: a volume of 5 km³ of seawater will be instrumented with optical detectors.



5 building blocks
115 Detection Units (DU)
750 m DU height
180m DU distance
5 km³ volume
Budget 250 M€


KM3NeT-Italia is funded by INFN since 1999 (NEMO)
In 2010 the project was awarded with a PON grant of 20.8 M€



KM3NeT is a EU funded ESFRI Infrastructure since 2006.
INFN led the Preparatory Phase

The Capo Passero Site infrastructure

3



Shore Laboratory:

Electronics Labs

Data Acquisition Room

Control Room

Guest House 4 rooms

Power Feeding Equipment (UPS protected)

1Gb/s (upto 10) Optical-fibre link GARR-X

Submarine cable and infrastructure:

96 km

20 fibres ITU655-NZDSF

Single conductor with DC-sea return

Cable Termination Frame:

Medium Voltage Converter: 10kV to 375V

3 ROV-mate e.o. output connectors


Off-shore Laboratory:

NEMO Phase-2 tower since 23 March 2013

Depth=3458 m

The NEMO Phase-2 tower: main components

4



- 8 floors
- 8 m bars, vertical dist. = 40 m, $H_{\text{tot}} = 450$ m
- 32 OM, 14 hydrophones
- oceanographic instrumentation

The OM: 10" Hamamatsu R7081, Front End Module, Time Calibration, LED beacons




Hydrophones: acoustic positioning and bioacoustics



The deep-sea field

5





NEMO-Phase2 under test in Malta before boarding on “Nautical Tide”




The tower on the “Nautical Tide”

Deployment of the NEMO-Phase2 Tower from the “Nautical Tide”





The "Nautical Tide" ROV and its launching system



The tower touches the sea-bottom at 3500m depth

INFN

NEMO Project : Tower 2000



Inspecting the tower with the ROV

3/23/2013 12:22:39 PM

H-216.37G

D-3,109.1m



Brief summary of the status

13

- In operation since the deployment date (23 March 2013)
- All Optical transmission parameters OK
- Optical Modules
 - 31 out of 32 OMs are sending data (1 OM internal electrical malfunction)
- Acoustics (in coll. with France: CPPM, Spain: UPV, Germany: ECAP)
 - No hydrophones on floor 5
 - 2 Piezo on floor 8
 - All hydrophones are sending data
 - LBL: 2 external beacons (autonomous) and 1 tower base beacon (autonomous clock) working, 1 tower base beacon (triggered) under commissioning
- Time calibration (in coll. with Spain: IFIC)
 - Led-beacon on floors 1-4, working
 - Tower base laser-beacon under commissioning
- Environmental instrumentation
 - 2 CTD probes working and sending data
 - 1 Current metre working and sending data
 - 8 Compasses working and sending data
- DAQ and TRIGGER system working
- Slow Control working

PMT Rate Monitoring

- The rate is sampled once per second by the PMT Front-End electronics;
- Rate is measured in a time window $\Delta t=10\text{ms}$;




- Baseline values are quite constant for over 8 months;
- There is a small burst percentage.

CTD probes


15

- Two CTD probes: Conductivity, Temperature, Pressure and Depth, Density, Salinity, Sound Velocity;
- Both working;
- Sampling every 10 min;
- Depths and sound velocity used as input for positioning algorithm.



DCS probe and Compasses

16



Inertial currents are evident at the same time in b.f., current intensity and heading variations

Acoustic detection: status

17

Distance differences derived from TOA differences using sound velocity measured by CTDs. Distances between hydrophones on the same floor are known.


~500 m

Beacon signal

Amplitude: 180 dB re 1 μ Pa @1 m
Frequency : 32 kHz
Pulse length: 5 ms



~400 m

4 m



Reconstruction with acoustics pos.

18




07/05/2013
00:00 UTC

Reconstruction possible with accuracy $O(1\text{m})$


Muon Triggers

19

L1 triggers



Trigger rates



- Event trigger rate: ~100 Hz
- Muon purity: $\sim 10^{-3}$
- More selective trigger strategies under study


Data taking and Shifts

20

- The tower takes data continuously (h24). It's controlled by automatic systems and monitored by a shift crew during the daytime.
- The shift crew is composed of two persons, responsible of the operation, calibration and monitoring of the detector for a period of 1 week.
- All INFN sections participating to the experiment (Bari, Bologna, Catania, Genova, LNF, LNS, Napoli, Pisa, Roma, Salerno) contribute to the shifts.
- Up to August: only local shifts. Since September: 50% of shifts in remote.

Live time and accumulated events

21




Live time and total number of events accumulated since April 16 2013


Atmospheric muon analysis: first results

22

Single PT files reconstruction rates




Track reconstruction level



- Post Trigger files selected between 2013-06-22 and 2013-07-17.
- Reconstruction rate stable in time. Mean value of 0.0065 Hz (consistent with Depth=3500m).
- Agreement with MC but excess in simulations: under investigation.
- In progress: analysis of the whole data set


The future

23



IceCube Neutrino Observatory reports first evidence for extraterrestrial high-energy neutrinos.


28 neutrino candidate events, substantially more than the expected from atmospheric backgrounds (4σ level).



KM3NeT Phase-1 at Capo Passero Site


24

- 8 Towers + 24 Strings
- New CTF with 5 outputs (4 fo, 2 e)
- Up to 5 Secondary JB
 - ▣ 1 SJB x 8 towers
 - ▣ 2 SJBs x 12+12 strings
 - ▣ 1 SJB for EMSO



The NEMO Phase-3

25



- 8 towers
- 14 floors/tower
- 8 m bars, vert. dist. = 20 m, $H_{\text{tot}} \sim 450$ m
- 6 OMs + 2 hydrophones/floor
- oceanographic instrumentation
- towers at ~ 100 m horiz. dist.



Shorter vertical distance and larger number of PMT/floor
→ lower energy threshold

Multi-PMT DOM Strings

26



Digital Optical
Module
31 small, 3" PMTs in
one glass sphere
Photon counting



Detection Unit with 18 storeys
36 m inter-storey distance
Compact deployment

Prototype DOM tested successfully
on ANTARES instrumentation line

Prototype DU with 3 DOMs to be
deployed in Capo Passero in March
2014




Capo Passero Site Future Layout


27

- 8 Detection Units in 2014 (towers)
- PPM Detection Unit in March 2014 (string)
- 24 Detection Units in 2015 (strings)
- A full Building Block before 2020 (≈ 1.5 IceCube)

10.000 light sensors
1000 hydrophones
tens of CTDs, CMs,..



The largest deep-sea
observatory in the world



KM3NeT and EMSO

28

Common efforts with the Earth and Sea Science Community



Real Time Environmental Monitoring

Toulon, Sicily and Hellenic:
sites of common interest for
KM3NeT and EMSO



Oceanography (water circulation, climate change):

Current intensity and direction, Water temperature, Water salinity ,...

Geophysics (geohazard):

Seismic phenomena, low frequency passive acoustics, magnetic field variations,...

Biology (micro-biology, cetaceans,...):

Passive acoustics, Biofouling, Bioluminescence, Water samples analysis,...


The Catania Test Site: a multidisciplinary deep sea-lab

29

LNS-INFN Catania



LNS Test Site – Laboratory
at Catania's harbour



Installation at
2100 m depth

Test Site North (TSN) – **SN1**



North:
4 LBW hydrophones
2 LF hydrophones
CTD, ADCP,
Seismometers
magnetometers
pressure gauges
GPS time stamping

Test Site South (TSS) – **SMO – EMSO**



NEMO
Junction Box



South:
4 LBW hydrophones
Underwater GPS time
stamping

Summary

30

- 8 storey tower deployed on March 23 2013
- Operational since then
- First results and in particular
 - ▣ Very low background rates (compatible with 40K background with few bioluminescence bursts)
 - ▣ Acoustic positioning: still in progress but accuracy $O(1\text{m})$ reachable
 - ▣ First results from muon track reconstruction analysis
- Toward KM3NeT telescope
 - ▣ Nemo Phase-3: an 8 tower detector (2014)
 - ▣ PPM Detection Unit (March 2014)
 - ▣ KM3NeT Phase-1: 8 towers plus 24 strings equipped with Multi-PMTs (2015)
 - ▣ km^3 -scale detector before 2020