The 6th International Conference - Channeling 2014 Charged & Neutral Particles Channeling Phenomena October 5th-10th, 2014, Capri (Naples), Italy

Goals and Plans for the Crystal Collimation Test at the Large Hadron Collider

Stefano Redaelli, CERN, BE-ABP on behalf of the Collimation Project and the UA9 teams











Outline



- **Introduction**
- **W** LHC beam collimation
- **Crystal collimation**
- **M** Layouts for beam tests
- **Plans for 2015**
- **Conclusions**





Acknowledgements



This talk is given on behalf of the members of the LHC collimation team the UA9 collaboration

Special thanks to Walter Scandale Daniele Mirarchi













Halo cleaning: reduce the risk of magnet quenches





- Halo cleaning: reduce the risk of magnet quenches
- Passive machine protection

Collimators are the first line of defense in case of accidental failures.





- Halo cleaning: reduce the risk of magnet quenches
- Passive machine protection
 Collimators are the first line of defense in case of accidental failures.
- Concentration of losses/activation in controlled areas
 Avoid many hot locations around the 27km-long tunnel





- Halo cleaning: reduce the risk of magnet quenches
- Passive machine protection
 Collimators are the first line of defense in case of accidental failures.
- Concentration of losses/activation in controlled areas
 Avoid many hot locations around the 27km-long tunnel
- Reduction total doses on accelerator equipment
 Provide local protection to equipment exposed to high doses (like the warm magnets in cleaning insertions)





- Halo cleaning: reduce the risk of magnet quenches
- Passive machine protection
 Collimators are the first line of defense in case of accidental failures.
- Concentration of losses/activation in controlled areas
 Avoid many hot locations around the 27km-long tunnel
- Reduction total doses on accelerator equipment
 Provide local protection to equipment exposed to high doses (like the warm magnets in cleaning insertions)
- Cleaning of physics debris (collision products)

 Avoid SC magnet quenches close to the high-luminosity experiments





- Halo cleaning: reduce the risk of magnet quenches
- Passive machine protection
 Collimators are the first line of defense in case of accidental failures.
- Concentration of losses/activation in controlled areas
 Avoid many hot locations around the 27km-long tunnel
- Reduction total doses on accelerator equipment
 Provide local protection to equipment exposed to high doses (like the warm magnets in cleaning insertions)
- Cleaning of physics debris (collision products)
 Avoid SC magnet quenches close to the high-luminosity experiments
- Optimize background in the experiments
 Minimize the impact of halo losses on
 (no big issue for the LHC)






- Halo cleaning: reduce the risk of magnet quenches
- Passive machine protection
 Collimators are the first line of defense in case of accidental failures.
- Concentration of losses/activation in controlled areas
 Avoid many hot locations around the 27km-long tunnel
- Reduction total doses on accelerator equipment
 Provide local protection to equipment exposed to high doses (like the warm magnets in cleaning insertions)
- Cleaning of physics debris (collision products)

 Avoid SC magnet quenches close to the high-luminosity experiments
- Optimize background in the experiments
 Minimize the impact of halo losses on
 (no big issue for the LHC)
- Beam tail/halo scraping, halo diagnostics
 Control and probe the transverse or longitudinal shape of the beam




























Including protection devices, a 5-stage cleaning in required!

The system performance relies on achieving the well-defined hierarchy between collimator families and machine aperture.



Collimation layout for the LHC Run II



Two warm cleaning insertions, 3 collimation planes

IR3: Momentum cleaning

1 primary (H)

4 secondary (H)

4 shower abs. (H,V)

IR7: Betatron cleaning

3 primary (H,V,S)

11 secondary (H,V,S)

5 shower abs. (H,V)

Local cleaning at triplets


8 tertiary (2 per IP)

Passive absorbers for warm magnets

Physics debris absorbers

Transfer lines (13 collimators)
Injection and dump protection (10)


Total of 118 collimators (108 movable). Two jaws (4 motors) per collimator!





Collimator gaps in 2012










Collimator gaps in 2012








2012: achieved the our design 7 TeV primary collimator setting!
Secondary collimator retraction still above nominal (~2.5 σ retraction instead than 1 σ).
Possible limitations: impedance and OP efficiency (more frequent alignments).




Collimator gaps in 2012








2012: achieved the our design 7 TeV primary collimator setting! Secondary collimator retraction still above nominal (~2.5σ retraction instead than 1σ). Possible limitations: impedance and OP efficiency (more frequent alignments).





Collimator movements in operation








Collimator movements in operation








Collimation cleaning at 4 TeV (β*=60cm)








Collimation cleaning at 4 TeV (β*=60cm)






Highest COLD loss location: efficiency of > 99.99%!
Most of the ring actually > 99.999%



Collimation cleaning in IR7






<u>Critical locations</u> (both beams): losses in the dispersion suppressors around (Q8) from <u>single diffractive</u> interactions with the primary collimators.

No other major cleaning limitations observed around the ring with present optics.



Collimation cleaning in IR7







No other major cleaning li



Betatron cleaning for Pb ion beams







Betatron cleaning of a few percent: **factor ~100 worst** than for protons.


Limiting location still the **dispersion suppressor**, but different loss distribution than for protons: ion beams from dissociation and fragmentation at the primary collimators are lost at specific locations.



Betatron cleaning for Pb ion beams



Local cleaning inefficency



Betatron cleaning of a few percent: **factor ~100 worst** than for protons.

Limiting location still the **dispersion suppressor**, but different loss distribution than for protons: ion beams from dissociation and fragmentation at the primary collimators are lost at specific locations.



Outline




- **Introduction**
- **TLHC** beam collimation
- **Crystal collimation**
- Layouts for beam tests
- Plans for 2015
- **Conclusions**



Concept of crystal collimation (i)






Bent crystals allow bending high-energy particles trapped between lattice planes.



Concept of crystal collimation (i)





Bent crystals allow bending high-energy particles trapped between lattice planes.

Application for **hadron beam collimation**:

Crystals might be used as primary collimators to **exploit large angles** (~50µrad) and the **reduced change of beam rigidity** (diffractive events and ion dissociation/fragmentation).


Challenges for the LHC:

- small angular acceptance;
- localization of large losses (0.5-1.0MJ) in one single collimator.



Concept of crystal collimation (i)





Bent crystals allow bending high-energy particles trapped between lattice planes.

Application for **hadron beam collimation**:

Crystals might be used as primary collimators to **exploit large angles** (~50µrad) and the **reduced change of beam rigidity** (diffractive events and ion dissociation/fragmentation).

Challenges for the LHC:

- small angular acceptance;
- localization of large losses (0.5-1.0MJ) in one single collimator.

Solid experimental validation at the SPS from UA9 experiment (starting in 2009), at beam energies up to 270 GeV (proton and ion beams). (less positive results in other machines like RHIC and Tevatron...)



Crystals for LHC collimation



- Halo cleaning: reduce the risk of magnet quenches
- Passive machine protection
 Collimators are the first line of defense in case of accidental failures.
- Concentration of losses/activation in controlled areas
 Avoid many hot locations around the 27km-long tunnel
- Reduction total doses on accelerator equipment
 Provide local protection to equipment exposed to high doses (like the warm magnets in cleaning insertions)
- Cleaning of physics debris (collision products)

 Avoid SC magnet quenches close to the high-luminosity experiments
- Optimize background in the experiments
 Minimize the impact of halo losses on
 (no big issue for the LHC)
- Beam tail/halo scraping, halo diagnostics
 Control and probe the transverse or longitudinal shape of the beam



Crystals for LHC collimation



- Halo cleaning: reduce the risk of magnet quenches
- Passive machine protection
 Collimators are the first line of defense in case of accidental failures.
- Concentration of losses/activation in controlled areas
 Avoid many hot locations around the 27km-long tunnel
- Reduction total doses on accelerator equipment
 Provide local protection to equipment exposed to high doses (like the warm magnets in cleaning insertions)
- Cleaning of physics debris (collision products)

 Avoid SC magnet quenches close to the high-luminosity experiments
- Optimize background in the experiments
 Minimize the impact of halo losses on
 (no big issue for the LHC)
- Beam tail/halo scraping, halo diagnostics
 Control and probe the transverse or longitudinal shape of the beam



Crystals for LHC collimation



- Halo cleaning: reduce the risk of magnet quenches
- Passive machine protection
 Collimators are the first line of defense in case of accidental failures.
- Concentration of losses/activation in controlled areas
 Avoid many hot locations around the 27km-long tunnel
- Reduction total doses on accelerator equipment
 Provide local protection to equipment exposed to high doses (like the warm magnets in cleaning insertions)
- Cleaning of physics debris (collision products)
 Avoid SC magnet quenches close to the high-luminosity experiments
- Optimize background in the experiments
 Minimize the impact of halo losses on
 (no big issue for the LHC)
- Beam tail/halo scraping, halo diagnostics
 Control and probe the transverse or longitudinal shape of the beam



Crystals for LHC collimation




- Halo cleaning: reduce the risk of magnet quenches
- Passive machine protection
 Collimators are the first line of defense in case of accidental failures.
- Concentration of losses/activation in controlled areas
 Avoid many hot locations around the 27km-long tunnel
- Reduction total doses on accelerator equipment
 Provide local protection to equipment exposed to high doses (like the warm magnets in cleaning insertions)
- Cleaning of physics debris (collision products)

 Avoid SC magnet quenches close to the high-luminosity experiments
- Optimize background in the experiments
 Minimize the impact of halo losses on
 (no big issue for the LHC)
- Beam tail/halo scraping, halo diagnostics
 Control and probe the transverse or longitudinal shape of the beam






















<u>Promises</u> of crystal collimation at the LHC:

- 1. Improve **collimation cleaning** achieved with fewer collimators;
- 2. Reduce electro-magnetic perturbations of collimators to the beams (**impedance**);
- 3. Improve significantly the cleaning for **ion beams**.







<u>Promises</u> of crystal collimation at the LHC:

- 1. Improve **collimation cleaning** achieved with fewer collimators;
- 2. Reduce electro-magnetic perturbations of collimators to the beams (**impedance**);
- 3. Improve significantly the cleaning for **ion beams**.

Can this really work at the LHC?



Beam tests deemed necessary before relying on crystal collimation...









Demonstrate hadron beam channeling at larger energies with the required efficiency!

There are uncertainties in the extrapolation to unknown energy territories. Both for protons and for ion beams.





Demonstrate hadron beam channeling at larger energies with the required efficiency!

There are uncertainties in the extrapolation to unknown energy territories. Both for protons and for ion beams.

Demonstrate that crystal collimation can improve the cleaning performance compared to present system!

We have seen that the betatron cleaning worked very well so far!





Demonstrate hadron beam channeling at larger energies with the required efficiency!

There are uncertainties in the extrapolation to unknown energy territories. Both for protons and for ion beams.

Demonstrate that crystal collimation can improve the cleaning performance compared to present system!

We have seen that the betatron cleaning worked very well so far!

Demonstrate the feasibility of crystal alignment at the required angular tolerances





Demonstrate hadron beam channeling at larger energies with the required efficiency!

There are uncertainties in the extrapolation to unknown energy territories. Both for protons and for ion beams.

Demonstrate that crystal collimation can improve the cleaning performance compared to present system!

We have seen that the betatron cleaning worked very well so far!

- Demonstrate the feasibility of crystal alignment at the required angular tolerances
- Demonstrate that crystal collimation can work during all operational phases, as required at the LHC.

Beam tests so far performed with coasting beams.

LHC require a performing cleaning during injection, ramp, squeeze, ...





Demonstrate hadron beam channeling at larger energies with the required efficiency!

There are uncertainties in the extrapolation to unknown energy territories. Both for protons and for ion beams.

Demonstrate that crystal collimation can improve the cleaning performance compared to present system!

We have seen that the betatron cleaning worked very well so far!

- Demonstrate the feasibility of crystal alignment at the required angular tolerances
- Demonstrate that crystal collimation can work during all operational phases, as required at the LHC.

Beam tests so far performed with coasting beams. LHC require a performing cleaning during injection, ramp, squeeze, ...

A crystal collimation test with LHC beams if foreseen to address these open points!

Scope of **first phase**: feasibility demonstration at **low-intensity**!





Demonstrate hadron beam channeling at larger energies with the required efficiency!

There are uncertainties in the extrapolation to unknown energy territories. Both for protons and for ion beams.

Demonstrate that crystal collimation can improve the cleaning performance compared to present system!

We have seen that the betatron cleaning worked very well so far!

- Demonstrate the feasibility of crystal alignment at the required angular tolerances
- Demonstrate that crystal collimation can work during all operational phases, as required at the LHC.

Beam tests so far performed with coasting beams. LHC require a performing cleaning during injection, ramp, squeeze, ...

A crystal collimation test with LHC beams if foreseen to address these open points!

Scope of **first phase**: feasibility demonstration at **low-intensity**!

In parallel: need to address high-energy challenge (0.5-1.0 MW losses in single absorber)



Outline



- **Introduction**
- **TLHC** beam collimation
- **Toleranal** Crystal collimation
- **M** Layouts for beam tests
- Plans for 2015
- **Conclusions**





Recent development, in addition to the years of experience from UA9:


- Improved tools to identify suitable candidate layouts (semi-analytical analysis of channeled beam trajectories).
- Setup complete tracking simulations to predict loss maps
 - Important to address cleaning performance taking into account layout constraints and leakage from collimators used as absorbers.
- Worked on an improved crystal routine for tracking studies.
- Conceived set of setting for the whole collimation system (~50 collimators) to achieve PhD thesis work by D. Mirarchi (see his talk later)



















Ideally: install crystal at location with **zero derivative** of beam envelope

→ same angle versus energy!







Ideally: install crystal at location with **zero derivative** of beam envelope


→ same angle versus energy!

Optics changes are very **costly** in terms of commissioning **time** at the LHC!

- → taken the <u>design choice</u> to use present optics to avoid commissioning overheads.
- → direct comparison of cleaning performance against present collimation.







Ideally: install crystal at location with **zero derivative** of beam envelope

→ same angle versus energy!

Optics changes are very **costly** in terms of commissioning **time** at the LHC!

- → taken the <u>design choice</u> to use present optics to avoid commissioning overheads.
- → direct comparison of cleaning performance against present collimation.

Rely on **existing collimation** system to catch the secondary beams

→ only compatible with lowintensity beams.





Collimation plane	Bending [μrad]	Length [mm]	Material	Bending planes
Hor.	50	4	Si	110
Ver.	50	4	Si	111





- Initial installation (carried out in April 2014):
 - Two goniometers on beam 1 only (horizontal + vertical)
 - Preparation of infrastructure for additional detectors
 - Improved beam instrumentation (fast diamond loss monitors)

Collimation plane	Bending [μrad]	Length [mm]	Material	Bending planes		
Hor.	50	4	Si	110		
Ver.	50	4	Si	111		





- Initial installation (carried out in April 2014):
 - Two goniometers on beam 1 only (horizontal + vertical)
 - Preparation of infrastructure for additional detectors
 - Improved beam instrumentation (fast diamond loss monitors)
- **Crystal angle in both planes: 50 μrad (see table)**

Collimation plane			Material	Bending planes		
Hor.	50	4	Si	110		
Ver.	50	4	Si	111		





- Initial installation (carried out in April 2014):
 - Two goniometers on beam 1 only (horizontal + vertical)
 - Preparation of infrastructure for additional detectors
 - Improved beam instrumentation (fast diamond loss monitors)
- ☑ Crystal angle in both planes: 50 µrad (see table)
- Crystal collimation layout suitable for beam tests from injection energy (450 GeV) to top energy (6.5 TeV in 2015)

Different collimator configurations required to intercept the channeled beam.

Collimation plane	Bending [μrad]	Length [mm]	Material	Bending planes		
Hor.	50	4	Si	110		
Ver.	50	4	Si	111		





- ☑ Initial installation (carried out in April 2014):
 - Two goniometers on beam 1 only (horizontal + vertical)
 - Preparation of infrastructure for additional detectors
 - Improved beam instrumentation (fast diamond loss monitors)
- ☑ Crystal angle in both planes: 50 µrad (see table)
- Crystal collimation layout suitable for beam tests from injection energy (450 GeV) to top energy (6.5 TeV in 2015)

Different collimator configurations required to intercept the channeled beam.

Possibility to improve cleaning relies on 5 other absorber collimators.


A Carbon-based collimator is used to intercept the beam: not enough absorption for cleaning!

Collimation plane	Bending [μrad]	Length [mm]	Material	Bending planes
Hor.	50	4	Si	110
Ver.	50	4	Si	111




Installation status









S. Redaelli, Channeling2014, 10/10/2014



Goniometer design concept



Design derived from some LHC beam instrumentation: with high intensity beams, a 'C' vacuum chamber "hides" the goniometer (only moved in beam for dedicated beam tests).


We designed the hardware with the goal of being "transparent" for the standard LHC operation. This also simplified the design versus impedance and vacuum constraints!

> Courtesy W. Scandale, A. Masi Dedicated talk by A Masi in this session!



Expected crystal collimation cleaning






See talk later by D. Mirarchi for complete simulation setup.

S. Redaelli, Channeling2014, 10/10/2014



Expected crystal collimation cleaning







Outline



- **Introduction**
- **TLHC** beam collimation
- **Tolerande** Crystal collimation
- Layouts for beam tests
- **Plans for 2015**
- **Conclusions**



Baseline 2015 schedule (i)



	Jan				Feb				Mar				
Wk	1	2	3	4	4 5 6		7	8	9	10	11	12	13
Mo	29	5	12	19	26	2	9	16	73	2	9	16	23
Tu										5			
We										9			
Th					HW tests					S C P	Reco	mmissionin	g with
Fr										ž .		beam	
Sa						Sector		Sector		Wac			
Su						test (523)		test (578)					

				Scrubbing for 50 ns Scrubbing for 25 ns operation operation										
	Apr				May						June			
Wk	14	15	16	17	18	19	20	2:	1	22	23	24	25	26
Mo	30	6	13	20	27	4	11		18	25	1		15	♦ 22
Tu								*						
We							LHCf VdM			TS1				
Th		Recom	missioning beam	with			VOIM					ensity ramp th 50 ns be		
Fr			ocum									I		
Sa														
Su														

Commissioning strategy recently discussed at the "Chamonix" LHC Performance Workshop (Sep. 22nd-25th).

Start of beam commissioning: March 2015

M. Lamont, J. Wenninger,

- □ The main strategy for 2015 is to concentrate on 6.5 TeV and 25 ns beam to reduce complexity:
 - Relaxed β^* of 80 cm for the startup
 - Plan a change of β^* later during the run.
- → Necessary beam time to be allocated to understand the LHC after the 2 year stop!


Explore in 2015, produce in 2016!



Baseline 2015 schedule (ii)







MD = Machine Development → beam studies for various purposes (immediate performance improvement, long-term developments, test new concepts, ...)









Assuming that the new hardware is thoroughly tested at the SPS and in the lab (2 goniometers bought for this purpose)...





Assuming that the new hardware is thoroughly tested at the SPS and in the lab (2 goniometers bought for this purpose)...
Assuming that we get 2-3 shifts in the main MD blocks:





Assuming that the new hardware is thoroughly tested at the SPS and in the lab (2 goniometers bought for this purpose)...

Assuming that we get 2-3 shifts in the main MD blocks:

Establish channeling and demonstrate improved cleaning at injection energy.





Assuming that the new hardware is thoroughly tested at the SPS and in the lab (2 goniometers bought for this purpose)...

Assuming that we get 2-3 shifts in the main MD blocks:

- Establish channeling and demonstrate improved cleaning at injection energy.
- Establish channeling and demonstrate improved cleaning at top-energy (6.5 TeV).

This includes verification of angular stability.



Main goals for first studies in 2015



Assuming that the new hardware is thoroughly tested at the SPS and in the lab (2 goniometers bought for this purpose)...

Assuming that we get 2-3 shifts in the main MD blocks:

- Establish channeling and demonstrate improved cleaning at injection energy.
- Establish channeling and demonstrate improved cleaning at top-energy (6.5 TeV).

This includes verification of angular stability.

Check crystal performance with Pb ion beams.



Main goals for first studies in 2015



Assuming that the new hardware is thoroughly tested at the SPS and in the lab (2 goniometers bought for this purpose)...

Assuming that we get 2-3 shifts in the main MD blocks:

- Establish channeling and demonstrate improved cleaning at injection energy.
- Establish channeling and demonstrate improved cleaning at top-energy (6.5 TeV).

This includes verification of angular stability.

- Check crystal performance with Pb ion beams.
- If possible, check crystal collimation in dynamics operational phases like ramp and squeeze.



Main goals for first studies in 2015



Assuming that the new hardware is thoroughly tested at the SPS and in the lab (2 goniometers bought for this purpose)...

Assuming that we get 2-3 shifts in the main MD blocks:

- Establish channeling and demonstrate improved cleaning at injection energy.
- ☑ Establish channeling and demonstrate improved cleaning at top-energy (6.5 TeV).

This includes verification of angular stability.

- Check crystal performance with Pb ion beams.
- If possible, check crystal collimation in dynamics operational phases like ramp and squeeze.

Very ambitious program!

Cannot effort hardware and software debugging during LHC beam time!









The present **LHC collimation system**, and highlight of its main performance achievements, were presented.

We are very happy with the performance up to 4 TeV → legacy for upgrades! We need to monitor carefully the behaviour at higher energies (quenches!)





The present LHC collimation system, and highlight of its main performance achievements, were presented.

We are very happy with the performance up to 4 TeV → legacy for upgrades! We need to monitor carefully the behaviour at higher energies (quenches!)

☑ Scope of a possible crystal collimation at the LHC were introduced.

Beam tests in the LHC deemed necessary before relying on this promising technique for LHC upgrades and for other machines.





- The present LHC collimation system, and highlight of its main performance achievements, were presented.
 - We are very happy with the performance up to 4 TeV → legacy for upgrades! We need to monitor carefully the behaviour at higher energies (quenches!)
- Scope of a possible crystal collimation at the LHC were introduced.
 - Beam tests in the LHC deemed necessary before relying on this promising technique for LHC upgrades and for other machines.
- A setup for crystal collimation studies has been installed in the LHC collimation insertion region for beam tests starting in 2015!
 - We believe that we can learn a lot for a minimum-impact installation setup with goniometers for horizontal and vertical beam tests.
 - Other outstanding open points will follow this "first phase" at low intensities.





The present LHC collimation system, and highlight of its main performance achievements, were presented.

We are very happy with the performance up to 4 TeV → legacy for upgrades! We need to monitor carefully the behaviour at higher energies (quenches!)

- Scope of a possible crystal collimation at the LHC were introduced.
 - Beam tests in the LHC deemed necessary before relying on this promising technique for LHC upgrades and for other machines.
- A setup for crystal collimation studies has been installed in the LHC collimation insertion region for beam tests starting in 2015!

We believe that we can learn a lot for a minimum-impact installation setup with goniometers for horizontal and vertical beam tests.

Other outstanding open points will follow this "first phase" at low intensities.

Goals for beam tests at the LHC and plans for 2015 were discussed

It will be challenging to fit more than a few shifts into the busy LHC schedule

→ more important the in the past to start with a "debugged" setup.





- The present LHC collimation system, and highlight of its main performance achievements, were presented.
 - We are very happy with the performance up to 4 TeV → legacy for upgrades! We need to monitor carefully the behaviour at higher energies (quenches!)
- Scope of a possible crystal collimation at the LHC were introduced.

 Beam tests in the LHC deemed necessary before relying on this promising technique for LHC upgrades and for other machines.
- A setup for crystal collimation studies has been **installed** in the LHC collimation insertion region for **beam tests** starting in **2015**!

 We believe that we can learn a lot for a minimum-impact installation setup with goniometers for horizontal and vertical beam tests.
 - Other outstanding open points will follow this "first phase" at low intensities.
- ☑ Goals for beam tests at the LHC and plans for 2015 were discussed
 It will be challenging to fit more than a few shifts into the busy LHC schedule
 → more important the in the past to start with a "debugged" setup.
- Looking forward to seeing channeled and collimated beam in 2015!






Reserve Slides

S. Redaelli, Channeling2014, 10/10/2014

29





























previous machines by orders of magnitude!

S. Redaelli, Channeling2014, 10/10/2014








Beam cleaning requirements at the LHC exceed previous machines by orders of magnitude!



Stability of cleaning






- Excellent stability achieved with 1 alignment per year in IR3/6/7 (2x30 devices).
- New alignments are only repeated for new physics configurations (it remains crucial to be efficient!)
 - → PhD by G. Valentino: average alignment time < 5 min per collimator using the BLMs.




Stability of cleaning






- Excellent stability achieved with 1 alignment per year in IR3/6/7 (2x30 devices).
- New alignments are only repeated for new physics configurations (it remains crucial to be efficient!)
 - → PhD by G. Valentino: average alignment time < 5 min per collimator using the BLMs.












Controlled beam excitation over several seconds: **Peak>1MW on TCP!**Worsened cleaning by relaxing collimator settings.










Controlled beam excitation over several seconds: **Peak>1MW on TCP!**Worsened cleaning by relaxing collimator settings.










Controlled beam excitation over several seconds: **Peak>1MW on TCP!**Worsened cleaning by relaxing collimator settings.










Understanding of LHC beam losses








Understanding of LHC beam losses








Understanding of LHC beam losses













- Considering a minimum lifetime of 0.2 h based on the 2012 experience
 - Perhaps pessimistic, but ~10% of fills reached $\tau_b < 0.5-1h!$
 - Reviewers felt that it could get worse (25ns vs 50ns, higher E, larger impedance)





- Considering a minimum lifetime of 0.2 h based on the 2012 experience
 - Perhaps pessimistic, but ~10% of fills reached $\tau_b < 0.5-1h!$
 - Reviewers felt that it could get worse (25ns vs 50ns, higher E, larger impedance)
- Different models to scale losses to 6.5 TeV: Intensity reach from proton cleaning in IR7 is 3 to 6 times the nominal LHC (3.2x10¹⁴p). Less margin at 7 TeV (different for 2 available quench models). HL-LHC intensity goal reduce this window by a factor ~2.





- Considering a minimum lifetime of 0.2 h based on the 2012 experience
 - Perhaps pessimistic, but ~10% of fills reached $\tau_b < 0.5-1h!$
 - Reviewers felt that it could get worse (25ns vs 50ns, higher E, larger impedance)
- Different models to scale losses to 6.5 TeV: Intensity reach from proton cleaning in IR7 is 3 to 6 times the nominal LHC (3.2x10¹⁴p).
 Less margin at 7 TeV (different for 2 available quench models).
 HL-LHC intensity goal reduce this window by a factor ~2.
- For more than a factor 2 above LHC design, we have to worry also about collimator robustness!

We might have to set BLM thresholds to protect the collimators!





- Considering a minimum lifetime of 0.2 h based on the 2012 experience
 - Perhaps pessimistic, but ~10% of fills reached τ_b<0.5-1h!
 - Reviewers felt that it could get worse (25ns vs 50ns, higher E, larger impedance)
- Different models to scale losses to 6.5 TeV: Intensity reach from proton cleaning in IR7 is 3 to 6 times the nominal LHC (3.2x10¹⁴p).
 Less margin at 7 TeV (different for 2 available quench models).
 HL-LHC intensity goal reduce this window by a factor ~2.
- For more than a factor 2 above LHC design, we have to worry also about collimator robustness!

We might have to set BLM thresholds to protect the collimators!

Ions: ALICE luminosity upgrade target is at least a factor 2 above quench limits.
 Same limitations apply for IR1 and IR5 that have less priority for ion runs.





- Considering a minimum lifetime of 0.2 h based on the 2012 experience
 - Perhaps pessimistic, but ~10% of fills reached τ_b<0.5-1h!
 - Reviewers felt that it could get worse (25ns vs 50ns, higher E, larger impedance)
- Different models to scale losses to 6.5 TeV: Intensity reach from proton cleaning in IR7 is 3 to 6 times the nominal LHC (3.2x10¹⁴p).
 Less margin at 7 TeV (different for 2 available quench models).
 HL-LHC intensity goal reduce this window by a factor ~2.
- For more than a factor 2 above LHC design, we have to worry also about collimator robustness!

We might have to set BLM thresholds to protect the collimators!

- lons: ALICE luminosity upgrade target is at least a factor 2 above quench limits.
 Same limitations apply for IR1 and IR5 that have less priority for ion runs.
- No additional limitations in IR1/5 until LS3 from physics debris thanks to the use of 3 TCL collimators.
 - Expect the same result for HiLumi, but need to prove this with final IR layouts. Backup slide in case more details are needed. See also talk by L.Esposito.



S. Redaelli, Channeling2014, 10/


LS1 collimation activities



16 Tungsten TCTs in all IRs and the 2 Carbon TCSGs in IR6 will be replaced by new collimators with integrated BPMs.

Gain: can align the collimator jaw without "touching" the beam → no dedicated low-intensity fills.


- → Drastically reduced setup time => more flexibility in IR configurations
- → Reduced orbit margins in cleaning hierarchy => more room to squeeze $β^*$: ≥ ~30 cm (R. Bruce)
- → Improved monitoring of local orbit and interlocking strategy
- Updated TCL layouts in IR1/5 for physics debris absorption
 - → Add 1-2 TCL collimator per beam. Expected to be compatible with HL proton luminosity.
- Improve protection of warm MQW magnets in IR3 by adding passive absorbers





Collimator hierarchy and β^* reach






• Closing down the collimators reduces the (normalized) triplet aperture that we can protect \rightarrow can fit a smaller β^* :

$$eta^* \propto rac{1}{N_{
m mqx}\sigma_{
m mqx}}$$
 $N_{
m mqx} > N_{
m tct} > N_{
m tcdq} > N_{
m tcsg} > N_{
m tcp}$

- Setting hierarchy was tightened after gaining operational experience and confidence in the machine (optics/orbit stability, beam lifetime, cleaning requirements,)
- Started with "relaxed" settings (easier commissioning, less challenging tolerance set), then achieved at 4 TeV gaps in mm equivalent to the design 7TeV goal → β* = 60 cm!
- Improve cleaning performance but reduce lifetime!







Lifetime during OP cycle



Couple of illustrative examples taken randomly from the LHC elogbook...





Will this be a serious issue after LS1?

Detailed analysis of quench tests will provide improved estimates.

Needs of possible scraping methods (hollow e-lens or similar) are being studied.


Can always open the collimators, at the **cost of larger** β^* .



Losses from luminosity debris



- In 2012, we have started using the TCL collimators in IP1 and IP5 that catch **physics debris**.
- Set to 10σ since the start of the run.
- We have performed TCLs scans to understand the impact on reducing the losses and the load to the magnets. At 10σ measured losses at Q8 reduced by a factor of 50!






3.5 TeV losses with Pb-Pb collisions





IBS & Electromagnetic dissociation at IPs, taken up by momentum collimators

Losses from collimation inefficiency, nuclear processes in primary collimators




J. Jowett



Secondary beam at the IR2 DS






Cannot separate BFPP and main beam in warm area (eg by Roman pots a la TOTEM).

J. Jowett



Secondary beam at the IR2 DS








Lifetime analysis (ii)






Beam lifetime 2011



Minimum lifetime per each fill






Lifetime analysis (i)





Beam lifetime 2012 Minimum lifetime per each fill





Collimation Review 2013 - Belen Salvachua

Number of fills with $I_{tot} > 10^{13}$ protons: 384 fills analyzed in 2012



Minimum beam lifetime in 2012




Beam intensity versus time

$$I(t) = I_0 \cdot e^{-\frac{t}{\tau_b}}$$

Beam lifetime gives the loss rate on collimators. Cleaning η gives the peak losses in magnets.

Collimator design: 500 KW!





Minimum beam lifetime in 2012




Beam intensity versus time

$$I(t) = I_0 \cdot e^{-\frac{t}{\tau_b}}$$

Beam lifetime gives the loss rate on collimators. Cleaning η gives the peak losses in magnets.

Collimator design: 500 KW!



2012: Minimum lifetime with gaps equiv. to 7 TeV: 0.2 - 1 hour

