



Contribution ID: 171

Type: talk

## Controlled injection of plasma electrons into a laser-driven wakefield using a variable length gas target

*Thursday, 17 September 2015 16:50 (20 minutes)*

Plasma wakefields can support very high field gradients ( $\sim 100$  GV/m) which makes particle acceleration to ultra-relativistic energies possible within a few millimeters. Precise control over the electron bunch phasespace during the process of injection into the accelerating wakefield is needed for the production of high-quality electron beams. Shaping of the longitudinal plasma-density profile, e.g. through the use of downramps, has been proposed as a possible controlled injection mechanism [1,2, e.g.]. In this report the study of density down-ramp injection into a plasma wakefield using gas target of variable length is presented. Suitable target density profiles, with a short down ramp length, preceded by a high-density peak are of crucial importance. The target is a gas cell with variable length of peak and plateau regions and was operated with a helium.

The goals and first preliminary results of the experiment are presented, including hydrodynamic simulations of the tailored target, performed using OpenFOAM.

[1] S. Bulanov et al., Phys. Rev. E 58, R5257 (1998)

[2] H. Suk et al., Phys. Rev. Lett. 86, 1011–1014 (2001)

**Primary author:** KONONENKO, Olena (Deutsches-Elektronen-Synchrotron (DESY))

**Co-authors:** Dr PALMER, Charlotte (DESY); Mr COLE, Jason (Imperial College London); Dr OSTERHOFF, Jens (Deutsches Elektronen-Synchrotron DESY); Mr CARREIRA-LOPES, Nelson (Imperial College London); Prof. NAJMUDIN, Zulfikar (Imperial College London)

**Presenter:** KONONENKO, Olena (Deutsches-Elektronen-Synchrotron (DESY))

**Session Classification:** WG1 - Electron beams from plasmas

**Track Classification:** WG1 - Electron beams from plasmas