



Contribution ID: 16

Type: Poster

Characterizations of GEM detector prototype

Wednesday, 27 May 2015 09:19 (0 minutes)

Gas Electron Multiplier (GEM) is one of the most important micro-pattern gaseous detectors used in the recent and being considered for future High-Energy Physics (HEP) experiments [1, 2]. For example ALICE at the Large Hadron Collider Facility is upgrading its multi-wire proportional chamber based Time Projection Chamber (TPC) with GEM units. In line with the worldwide efforts, we have also taken an initiative in our experimental high-energy physics detector laboratory build and test of GEM detector prototypes. The GEM foils and other components are obtained from CERN. The detector has been tested with Co60, Cs137 and Sr90 radioactive sources with Ar/CO₂ gas in 70/30 ratios. The temperature and atmospheric pressure has been measured and recorded continuously using a data logger developed in-house. Effect of Temperature and Pressure on count rate has also been measured. Variation of the count rate has also been measured with varying flow rate. The details test results will be presented. The results of long term stability test will also be presented.

Summary

Characterizations of GEM detector prototype

Rajendra Nath Patra³, Amit Nanda¹, Sharmili Rudra⁴, S. Biswas^{1,*}, B. Mohanty¹, T. K. Nayak³, P. K. Sahu², S. Sahu²

¹School of Physical Sciences, National Institute of Science Education and Research, Bhubaneswar - 751005, Odisha, India

²Institute of Physics, Sachivalaya Marg, P.O: Sainik School, Bhubaneswar - 751 005, Odisha, India

³Variable Energy Cyclotron Centre, 1/AF Bidhan Nagar, Kolkata-700 064, West Bengal, India

⁴Department of Applied Physics, CU, 92, APC Road, Kolkata-700 009, West Bengal, India

Email: *s.biswas@niser.ac.in, saikat.ino@gmail.com

Gas Electron Multiplier (GEM) is one of the most important micro-pattern gaseous detectors used in the recent and being considered for future High-Energy Physics (HEP) experiments [1, 2]. For example ALICE at the Large Hadron Collider Facility is upgrading its multi-wire proportional chamber based Time Projection Chamber (TPC) with GEM units. In line with the worldwide efforts, we have also taken an initiative in our experimental high-energy physics detector laboratory build and test of GEM detector prototypes. The GEM foils and other components are obtained from CERN. The detector has been tested with Co60, Cs137 and Sr90 radioactive sources with Ar/CO₂ gas in 70/30 ratios. The temperature and atmospheric pressure has been measured and recorded continuously using a data logger developed in-house. Effect of Temperature and Pressure on count rate has also been measured. Variation of the count rate has also been measured with varying flow rate. The details test results will be presented. The results of long term stability test will also be presented.

[1] F. Sauli, Nucl. Instrum. Meth. A 386 (1997) 531.

[2] Technical Design Report for the Upgrade of the ALICE Time Projection Chamber, ALICE-TDR-016, CERN-LHCC- 2013-020, March 3 2014.

Primary authors: Ms RUDRA, SHARMILI (University of Calcutta); Dr BISWAS, Saikat (National Institute of Science Education and Research)

Co-authors: Mr NANDA, Amit (NISER); Prof. MOHANTY, B. (NISER); Ms BHATTACHARYA, P. (NISER); Prof. SAHU, P. K. (IoP); Mr PATRA, Rajendra Nath (VECC); Mr SAHU, S. (IoP); Dr NAYAK, T. K. (VECC)

Presenters: Ms RUDRA, SHARMILI (University of Calcutta); Dr BISWAS, Saikat (National Institute of Science Education and Research)

Session Classification: Gas Detectors - Poster Session

Track Classification: S7 - Gas detectors