



Contribution ID: 101

Type: **Oral contribution**

Development of μ -PIC with resistive electrodes using sputtered carbon

Thursday, 15 October 2015 17:05 (20 minutes)

Micro-Pixel chamber (μ -PIC) with resistive electrodes has been developed for particle tracking detector in the environment of high rate HIP (Highly Ionizing Particles). One of the target of this development is ATLAS Muon Tagger that is considered to be disposed at phase-2 upgrade. The amplification region of μ -PIC is separated by isolated pixels, so it is expected to separate multi incident tracks with high position resolution. In our previous research resistive μ -PIC has succeeded to get enough gain for observing minimum ionizing particles and to suppress the sparks. As new developments, sputtered carbon is used as resistive cathode strips which are arranged by 400 μ m pitch with 250 μ m diameter hole. Very fine pattern can be formed with lift off process and resistivity is well controlled by varying its thickness (50-500nm) and nitrogen doping. Physical and chemical toughness of the resistive electrodes are realized by its diamond-like carbon structure. The gain measurement and spark tolerant test by fast neutron irradiation will be reported.

Primary author: Mr YAMANE, Fumiya (Kobe Univ.)

Co-authors: Mr OCHI, Atsuhiko (Kobe Univ.); Mr HASEGAWA, Hiroaki (Kobe Univ.); Ms NORIKO, Nagasaka (Kobe Univ.); Mr YAMAUCHI, Satoru (Kobe Univ.); Mr KAWAMOTO, Tatsuo (Tokyo ICEPP); Mr MASUBUCHI, Tatsuya (Tokyo ICEPP); Mr HOMMA, Yasuhiro (Kobe Univ.); Mr KATAOKA, Yousuke (Tokyo ICEPP)

Presenter: Mr YAMANE, Fumiya (Kobe Univ.)

Session Classification: Contributed talks

Track Classification: New Developments in MPDGs