

**PMTs motherboard**

**02.06.12 LaBiodola**

**Massimo B. , Gabriele Simi**



## SuperB FDIRC PMTs MotherBoard baseline



Backplane = 8 Mboards of 6 PMTs each

MBoard: simple structural profile + PCB in order to:

- Support PMTs in precise position ( $\perp$  and  $//$  to quartz window)
- Allow FE boards insertion without forces on connectors and PMTs
- Transmit signals to FEbs, 64 contacts/PMTs or  $<200$  contacts/FEb required

Baseline:




- Samtec SQT on PMT side for both signals and HV+GND
- Connectors on PMTs do not allow elastic mounting then
- Clearance PMTs to Quarz avoids compression on PMTs and interferences with quartz due to: piling up tolerances, FEb insertion, Fbox thermal deformation
- Erni connectors Mboard to Feb
- PMTs type C
- HV daisy chain
- PMTs  $\perp$  position driven by set-screws acting on PMTs corners, secured by the M3 screw



## SuperB FDIRC MBoard to FEb connectors



Baseline: Non-ZIF Erni connectors  
 ERNI SMC-Q 64004 press fit connector  
 50 contacts/pc, 100 contacts/PMT  
 Quoted BW 3 GHz  
 Press fit: only male connector  
 Insertion force 26N each (datasheet)  
 160N/Feb (row of 6 connectors)  
 Best if centering feature e.g. pre-alignment  
 module, to be fit the Mboard... in progress





## SuperB FDIRC PMTs Backplane



Beam structure sag

Deformation of aluminum bar, section 50x20, 3 wings 5-10-5 mm thick, under 160N of distributed load

Sag  $\leq 50 \mu\text{m}$  of alu bar


PCBs deformation depending on thickness and coupling to beam structure

Requires many coupling screws or PCB gluing to structure

Add tolerance, thermal effect ...

suggested clearance of 200 – 300  $\mu\text{m}$

(PMTs built-in average clearance ... 60  $\mu\text{m}$ ?)





## SuperB FDIRC

### Why not AMP ZIF connectors



Rotary ZIF connectors AMP 531414

Large dimensions due to pitch of 2.54 mm,  
length of connector body  $\approx$  150 mm

50 dual contacts, 200 contacts each 3 PMTs

Pro



Zero force, zero deformation of Mboard, torque  
not negligible but low bar deformation

Possible Cons

- Bandwidth not quoted
- Require access to cam levers
- Prone to bad contacts?

## Running out of production !!

Tyco does not suggest this family of  
connectors







# SuperB FDIRC Other suggested by TE






“If you want a product with bandwidth, please use:


1932632-1 the more available

1934768 less contacts “ (50 ... 110 ...170)

Still missing both bandwidth and insertion force



PART NUMBERS  
2-1934768-1 THRU 3-1934768-6  
DIFFERENTIAL PAIR CONFIGURATION



PART NUMBERS  
1934768-1 THRU 1-1934768-6  
INDIVIDUAL SIGNAL CONFIGURATION



## SuperB FDIRC HV distribution baseline: PMTs of type D



Baseline: HV and ground distribution by daisy chain




HV connectors on PCB just aside to PMTs HV connectors, short HV path

Cut on PCB to minimize risk of surface currents (as Hamamatsu)

Same for GND

HV+GND connectors not defined yet (any suggestion welcome).

Ground for signals can run separately







## SuperB FDIRC Safe backup: PMTs of type C



HV cables of each PMTs running between top of PMTs and bottom of PCB (7.5 mm gap)  
E.g. 12 cables per «crate» corner: not really a mess  
Requires dismounting additional 1 or 2 PMTs to remove PMTs of 2°, 3°, 4° 5° row.  
Gas tightness or air circulation of the 7.5 mm gap more difficult  
Handling, installation, dismounting of the 6 PMTs bar more difficult (bar with piggy tails)







## SuperB FDIRC Mboard assembly procedure



Preliminary acceptance checks of geometry / dimensions of  
PMTs, PCBs, alum. bars

Mount and screw PCB to bars (reference pins), check PCB  
position and flatness etc...

Insert PMTs on PCB connectors

Mount on jig (reference to bars end reference faces)

Level PMTs faces (e.g. set PMTs against reference face)

Tight set screw (acting on PMTs top face corners)

Tight M3 screw (center retaining screw)

CMM Measure, any other test (connections, HV, gnd ...)



## SuperB FDIRC Going to prototype




### HV and GND Daisy chain

- missing HV connectors definition
- Start test/assembly/produce daisy chain ...missing dedicated technicians

Do we design Mboard for current Fbox?

Or for the «final design» updated with crate interface?



### For more realistic model

- Missing FE boards and connection board dimension
- Missing connector FE boards to Connection board definition

